



NOTES:

- 1. Operation Temperature: -40°C∼+85°C.
- 2. Electrial Characteristics:
 - 2.1>Rated Current:125V AC, 1.5A@25°C.
 - 2.2>Contact Resistance:20mΩ Max.
 - 2. 3>Insulation Resistance:500MΩ Min, 100V DC/min.
 - 2.4>Voltage Proof: 1000V AC/1 minute no breakdown.
- 3. Mechanical Characteristics:
 - 3.1>Insertion Force & Withdrawal Force:30N Max.
 - 3.2>Durability:750 cycles Min.
- 4. Environmental compliance:
 - 4.1>the products are compliant with the RoHS, and REACH etc.

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	MD-18S
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

3	T-SLEEVE	1PCS	Four holes up and four holes down, Ф1.10mm, PC
2	HOUSING	1PCS	CAT6/FTP HOUSING,94V-2
1	CONTACTS	8PCS	2PRONGS,BRASS
NO.	PARTS NAME	Q'TY	SPECIFICATION

DESCRIPTION:

MODULAR PLUG,RJ45 conector for patchcable, Cat6, FTP, 20-pack

