

elipson® | Premium **SUB 12**

CAISSON DE BASSE ACTIF - BASS REFLEX LAMINAIRE FRONTAL



Équipé d'un haut-parleur de 300 mm en fibre de verre et d'un amplificateur de 500 W en classe D, Premium Sub 12 délivre des graves amples et percutants, idéals pour les grandes pièces ou les installations exigeantes.

Son coffret bass-reflex à rayonnement frontal et son design soigné assurent une parfaite intégration visuelle et sonore. Une expérience immersive, taillée pour révéler toute l'ampleur des bandes-son et des enregistrements musicaux les plus dynamiques.





TECHNIQUE

Type Caisson de basse actif Bass reflex laminaire frontal	DSP Boost +3dB @ 28 Hz
Puissance de sortie 500 W Class D	Phase 0° / 180°
Haut-parleur 300 mm membrane fibre de verre	Veille Automatique
Réponse en fréquence (±3dB) 22 Hz - 200 Hz	Entrées Ligne L/R (bas niveau) - LFE
Filtre subsonique 23 Hz / 12dB / oct	Sortie Ligne L/R (bas niveau)
Fréquence de coupure variable 30 Hz - 200 Hz	

DIMENSIONS
POIDS

Dimensions sans grille & pieds L410 x H430 x P480 mm	Poids 27 kg
Dimensions avec grille & pieds L410 x H452 x P492 mm	

PACKAGING

Packaging dimensions L617 x H571 x P547 mm	Poids brut 29,5 kg
--	------------------------------

FINITIONS
-
CODES
PRODUITS



Finition Noir	SKU ELIPRESUB12BK	EAN 3700795194843
-------------------------	-----------------------------	-----------------------------

elipson® | Premium **SUB 12**

POWERED SUBWOOFER - FRONT LAMINAR BASS REFLEX LOAD



Equipped with a 12" Glass fibre cone driver and a 500 W Class D amplifier, Premium Sub 12 delivers punchy, full-bodied bass, ideal for large rooms or demanding installations.

Its front-firing bass-reflex enclosure and meticulous design ensure perfect visual and sonic integration. An immersive experience, designed to reveal the full scope of the most dynamic soundtracks and musical recordings.





TECHNICAL

Type Powered subwoofer Front laminar bass reflex load	DSP Boost +3dB @ 28 Hz
Output power 500 W Class D	Phase 0° / 180°
Drive unit 12" Glass fibre cone	Stand-by Auto
Frequency response (±3dB) 22 Hz - 200 Hz	Inputs Stereo line (low level) - LFE
Subsonic filter 23 Hz / 12dB / oct	Output Stereo line (low level)
Variable cut-off frequency 30 Hz - 200 Hz	

DIMENSIONS
WEIGHTS

Dimensions without grille & feet W410 x H430 x D480 mm	Weight 27 kg
Dimensions with grille & feet W410 x H452 x D492 mm	

PACKAGING

Packaging dimensions W617 x H571 x D547 mm	Gross weight 29,5 kg
--	--------------------------------

FINISHES
-
PRODUCTS
CODES



Finish Black	SKU ELIPRESUB12BK	EAN 3700795194843
------------------------	-----------------------------	-----------------------------