

# 6.5CS-T

## 2-Way Coaxial In-Ceiling Speaker

The 6.5CS-T offers superior all-round qualities and is the ideal choice wherever background music is desired.

A polypropylene woofer and Mylar tweeter combination make this in-ceiling speaker suitable for occasionally damp areas such as garages, corridors, and terraces.

Supplied with a 70/100-volt transformer and an 8-ohm / high-power switch, the 6.5CS-T is a versatile solution for home or commercial use.

### Key Features

#### Switchable 8 Ohm / 70-100 Volt Impedance

Ensures flexible installation across residential and commercial setups.

#### Moisture-resistant Tweeter & Woofer

Ensures long-term reliability and stable performance in humid areas.

#### White Paintable Grille

Allows each speaker to completely disappear into any environment.



### Technical Specifications

Model Name	6.5CS-T
System Type	2-way in-ceiling
Tweeter (mm/inch)	13 mm / 0.5" Mylar
Woofer (mm/inch)	165 mm / 6.5" polypropylene
Frequency Response	75 Hz - 22 kHz
Power Handling (Long / Short)	25 W / 50 W
Impedance	8 Ω and 70 / 100 V switchable
Sensitivity	85 ± 3 dB
Installation Hole Diameter (mm/inch)	ø 198 mm / ø 7.8"
Product Dimensions - ø x Depth (mm/inch)	ø 227 x 81 mm / ø 8.9" x 3.2"
Grille	Metal
Finish	White grille / black chassis
Included Accessories	Paintable grille / cut out template
Net Product Weight (Pair)	2.63 kg / 5.8 lbs
Gross Weight (Packaging Included)	3.17 kg / 7 lbs