

Klipsch

RETAIL BUYERS GUIDE 2021 / 2022

EMEA EDITION



Over 70 years ago Something very special occurred in A TINY TIN SHED IN HOPE, ARKANSAS

In 1946 Paul W. Klipsch (PWK) – genius, madman and maverick – designed and hand-built the legendary Klipschorn® loudspeaker with the goal of bringing live music into his living room. He was an American audio pioneer and a true eccentric. PWK gave rise to speaker research and invention that would forever impact generations of music lovers.

Today, in this honored tradition, we move forward, pushing the boundaries of art and science – while driving new technologies – to deliver an ever-incredible listening experience. Remember great sound? We never forgot.

We are the KEEPERS OF THE SOUND®

Listeners appreciate a lack of distortion. -Paul W. Klipsch

Founder

HEADPHONES

40	T5 II TRUE WIRELESS SERIES
42	T5 SERIES

McLAREN

44	T5 II TRUE WIRELESS SPORT MCLAREN EDITION
44	T5 II TRUE WIRELESS ANC MCLAREN EDITION
45	THE FIVES McLAREN EDITION

POWERED AUDIO SYSTEMS

30	SOUND BARS
32	PROMEDIA
33	POWERED MONITORS

HERITAGE WIRELESS

	Se 121 25
THE SIXES	35

- THE FIVES 35
- THE THREE II 36

36

plywood

- full st THE ONE II
- HERITAGE GROOVE 37
- PROMEDIA HERITAGE 2.1 37

TABLE OF CONTENTS

HERITAGE SERIES

- KLIPSCHORN (AK6) LA SCALA (AL5) CORNWALL IV FORTE IV
 - FORTE IV
 6

 HERESY IV
 7

5

5

6

COMPONENT AUDIO

HORNS

9	REFERENCE III
10	C KII DOLBY ATMOS®
12	##REFERENCE PREMIERE
-18	n 12 - REFERENCE
22	SUBWOOFERS
25	REFERENCE PREMIERE DESIGNER ON WALL
27	REFERENCE THEATER PACK
28	REFERENCE CINEMA SYSTEM

Fillet bore in this section to expand from 0.700" diameter to 0.700" Sovere pross section



W

KLIPSCH

0

CART CAUDIO

CAUDIO

SUNE:

1

HERITAGE SERIES

HERITAGE SERIES

The vintage Klipschorn, La Scala, Cornwall and Heresy are among the most revered and highly acclaimed loudspeakers in the history of high fidelity audio. Driven by a love of music and desire to hear an "orchestra" in his home, audio pioneer Paul W. Klipsch revolutionized the way the world listened to recorded music when he began building his Heritage line of speakers in 1946. With cabinets still assembled by skilled craftsmen in Hope, Arkansas, where the Klipsch legacy began, the Heritage Series is a testament to high-performance audio that has stood the test of time.

KLIPSCHORN® AK6

PAUL W. KLIPSCH launched the Klipschorn loudspeaker in 1946 to enable people, for the first time ever, to experience the power, detail and emotion of a live performance at home. It is the only speaker in the world to be in continuous production for more than 70 years and has remained relatively unchanged since its inception. The remarkably uncommon Klipschorn includes a highly efficient horn-loaded tweeter and midrange compression driver. Its patented folded-horn woofer delivers powerful low frequencies.



FREQUENCY RESPONSE	33Hz - 20kHz +/- 4dB
SENSITIVITY	105dB @ 2.83V / 1m
IMPEDANCE	8 ohms compatible
POWER HANDLING (CONT/PEAK)	100W / 400W
CROSSOVER	HF: 4500Hz MF: 450Hz
HIGH FREQUENCY DRIVER	K-7711" (2.54cm) light-weight Polyimide diaphragm compression driver mated to a 90° x 40 Tractrix horn
MIDRANGE	K-55-X 2" (5.08cm) Phenolic diaphragm compression driver
LOW FREQUENCY DRIVER	K-33-E 15" (38.1cm) Fiber-composite cone woofer with a trihedral exponential folded horn
HEIGHT	53" (134.62 cm)
WIDTH	31.25" (79.38 cm)
DEPTH	28.25" (71.75 cm)
WEIGHT	220lbs (100 kg)
GRILLE CLOTH	Silver Metallic







POWER HANDLING (CONT/PEAK)	100W / 400W
CROSSOVER	HF: 4500Hz MF: 450Hz
HIGH FREQUENCY DRIVER	K-7711" (2.54cm) light-weight Polyimide diaphragm compression driver mated to a 9 \times 40 Tractrix horn
MIDRANGE	K-55-X 2" (5.08cm) Phenolic diaphragm compression driver
LOW FREQUENCY DRIVER	K-33-E 15" (38.1cm) Fiber-composite cone woofer with a trihedral exponential folded
HEIGHT	53" (134.62 cm)
WIDTH	31.25" (79.38 cm)
DEPTH	28.25" (71.75 cm)
WEIGHT	220lbs (100 kg)
GRILLE CLOTH	Silver Metallic
FINISH	Satin Black Ash. American Walnut. Natural Cherry

LA SCALA® AL5

When the La Scala first launched in 1963, PAUL W. KLIPSCH offered it to Arkansas gubernatorial candidate Winthrop Rockefeller to use as a public address speaker, and he did use one on a train car during a subsequent campaign. Despite its raw, unfinished appearance, the fully horn-loaded, three-way La Scala sounded so good people still wanted to put it in their living rooms.



FREQUENCY RESPONSE	51Hz - 20kHz (+/- 4 dB)
SENSITIVITY	105dB @ 2.83V / 1m
POWER HANDLING	100W / 400W
MAXIMUM SPL	121dB
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	HF: 450Hz MF: 400Hz
TWEETER	K-771 1" (2.54cm) Light-Weight Polyimide Diaphragm Compression Driver Mated to a 90° x 40° Tractrix Horn
HIGH FREQUENCY HORN	Tractrix
MIDRANGE	K-55-X 2" (5.08cm) Phenolic diaphragm compression driver
MID-FREQUENCY HORN	Exponential
WOOFER	K-33-E 15" (38.1cm) Fiber-composite cone with a folded horn.
ENCLOSURE MATERIAL	Birch plywood and MDF
ENCLOSURE TYPE	Fully horn-loaded
HEIGHT INCHES	40" (101.6 cm)
WIDTH INCHES	24 1/4" (61.59 cm)
DEPTH INCHES	25 5/16" (64.29 cm)
PRODUCT WEIGHT	190 lbs (86 kg)
FINISHES	Natural Cherry, Satin Black Ash, American Walnut
GRILLE CLOTH	Silver Metallic

CORNWALL IV

The Cornwall derives its name from being the first Klipsch loudspeaker designed to operate from either a corner or up against a wall (corn/wall). The Cornwall is an excellent combination of wide frequency response, low distortion, and high-power output. Within the Heritage series, the Cornwall delivers deep bass response that is surpassed only by the legendary Klipschorn[®].



FREQUENCY RESPONSE (+/-4 dB)	34Hz - 20kHz
SENSITIVITY ¹	102dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	100W/400W
MAXIMUM SPL	119dB Continuous
NOMINAL IMPEDANCE	8 ohms Compatible
CROSSOVER FREQUENCY	HF: 5000Hz MF: 700Hz
HIGH FREQUENCY DRIVER	K-107-Tl 1" (2.54cm) Titanium diaphragm compression driver
MIDRANGE	K-702 1.75" (4.45cm) Polyimide diaphragm compression driver
LOW FREQUENCY DRIVER	K-33-E 15" (38.1cm) Fiber-composite cone woofer
ENCLOSURE MATERIAL	MDF with fine veneers
INPUTS	Dual binding posts / bi-wire / bi-amp
HEIGHT	38" (96.52cm)
WIDTH	25.3" (64.3cm)
DEPTH	15.5" (39.4cm)
WEIGHT	73 lbs (33.1kg)
FINISH	Satin Black Ash, American Walnut, Natural Cherry



FORTE IV

First introduced in 1985, the Forte quickly established itself as the most popular Klipsch Heritage model. The elegant design and outstanding performance made the Forte a standout among its competitors in the industry for over a decade. In 2017, Klipsch re-introduced the Forte with upgraded cosmetics, a new midrange horn and compression driver, and a re-designed 12" woofer and 15" passive radiator. The new Forte IV still maintains all the original charm that made this loudspeaker so popular - but it now uses the latest technology that really brings the Forte IV into the 21st century.



FREQUENCY RESPONSE	38Hz-20kHz +/- 3dB
SENSITIVITY	99dB @ 2.83V/1 meter
IMPEDANCE	8 ohms compatible
POWER HANDLING (CONT/PEAK)	100W / 400W
CROSSOVER	HF: 5.2kHz MF: 650Hz
DRIVE COMPONENTS	Three-way system using one 1" (2.54cm) K-103 Titanium diaphragm compression tweeter, one 1.75" (4.45cm) K-70 Titanium diaphragm compression driver, one 12" (30.5cm) K-281 Fiber composite cone woofer and one 15" (38.1cm) KD-15 rear-mounted passive radiator
HEIGHT	35.75" (90.81cm)
WIDTH	16.63" (42.24cm)
DEPTH	13" (33cm)
WEIGHT	72 lbs (32.7kg)
FINISH	American Walnut, Natural Cherry, Black Ash, Distressed Oak



HERESY[®] IV

Because of its relatively "compact" size, this model offers the greatest degree of placement flexibility in the Heritage Series line. First introduced in 1957, this three-way horn-loaded loudspeaker is still able to deliver the awe-inspiring Klipsch sound that our fan around the world know and love.



FREQUENCY RESPONSE	48-20k +/-4dB
SENSITIVITY	99db @ 2.83V/1 meter
IMPEDANCE	8 ohms compatible
POWER HANDLING (CONT/PEAK)	100W / 400W
CROSSOVER	HF: 4500Hz MF: 850Hz
HIGH FREQUENCY DRIVER	K-107-Tl 1" (2.54cm) Titanium diaphragm compression driver
MIDRANGE	K-702 1.75" (4.45cm) polyimide diaphragm compression driver
LOW FREQUENCY DRIVER	K-28-E 12" (30.48cm) Fiber-composite cone woofer
INPUTS	Dual binding posts / bi-wire / bi-amp
HEIGHT	24.81" (63.01cm)
WIDTH	15.5" (39.37cm)
DEPTH	13.25" (33.66cm)
WEIGHT	44 lbs (20kg)
FINISH	Walnut, Cherry, Black Ash, Distressed Oak

SHIPPING QUANTITY: Single
SHIPPING WEIGHT: 24.4 kg
53.8 lbs
PART NUMBER
1068151 (Black Ash)
1068152 (Natural Cherry)
1068153 (Walnut)
1068358 (Distressed Oak)
NOTES:

Kipsch[®] Component Audio

W. KLIP

HC

AUL

1946

REFERENCE III SPEAKERS

Our flagship floorstanding speaker, the RF-7 III champions our legendary, high-performance Klipsch sound, while the RC-64 III center channel delivers real-life, front row, cinema-quality acoustics. Featuring cast basket Cerametallic[™] woofers, an all-new titanium compression driver, Tractrix[®] horn-loaded tweeter, a redesigned bifurcated cabinet and more.

DE-7 III

TOWERS



FREQUENCY RESPONSE	32-25kHz +/- 3dB
POWER HANDLING	250W / 1000W peak
SENSITIVITY	100 dB @ 2.83V / 1M
NOMINAL IMPEDANCE	8 ohms compatible
HIGH FREQUENCY HORN	8.5" square 90° x 90° Tractrix® Horn
HIGH FREQUENCY DRIVERS	1.75" (4.45cm) titanium diaphragm compression driver
CROSSOVER FREQUENCY	1,300 Hz
LOW FREQUENCY DRIVERS	Two 10" (25.4cm) Cerametallic cone woofers
INPUTS	Dual binding posts / bi-wire / bi-amp
ENCLOSURE TYPE	Dual chambered, bass-reflex – via dual rear-firing Tractrix ports
DIMENSIONS (Including Plinth)	49" (124.5cm) H x 13.875" (35.2cm) W x 17.875" (45.4cm) D
WEIGHT	95.24 lbs (43.2kg)
FINISH	Black Ash, Natural Cherry, Walnut



- All-New 1 ³/₄" Titanium Compression Driver
- 90° x 90° Compressed Molded-Rubber Tractrix Horn
- Dual Tractrix Ports
- Dual 10" Cast Basket Cerametallic Woofers

CENTERS



- All-New 1 ³/₄" Titanium Compression Driver
- 90° x 90° Compressed Molded-Rubber Tractrix Horn
- 2 1/2" Way Network Crossover Design
- Quad 6.5" Cast Basket Cerametallic Woofers

RC-64 III QUAD 6.5" CENTER

FREQUENCY RESPONSE	57-24kHz +/- 3dB
POWER HANDLING	200W / 800W peak
SENSITIVITY	99 dB @ 2.83V / 1M
NOMINAL IMPEDANCE	8 ohms compatible
HIGH FREQUENCY HORN	6.5" square 90° x 90° Tractrix® Horn
HIGH FREQUENCY DRIVERS	1.75" (4.45cm) titanium diaphragm compression driver
CROSSOVER FREQUENCY	1,000 Hz and 1,400 Hz
LOW FREQUENCY DRIVERS	Quad 6.5" (16.5cm) Cerametallic cone woofers
INPUTS	Dual binding posts / bi-wire / bi-amp
ENCLOSURE TYPE	Sealed
DIMENSIONS (Including Plinth)	8" (20.3cm) H x 35.8" (91cm) W x 15" (38.1cm) D
WEIGHT	55 lbs (25kg)
FINISH	Black Ash, Natural Cherry, Walnut

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 25.9 kg 57 lbs PART NUMBER 1064562 (Black Ash) 1064561 (Natural Cherry) 1065137 (Walnut)

COMPONENT AUDIO

REFERENCE WITH DOLBY ATMOS®

Dolby Atmos is the greatest advancement in cinema and home theater technology since the introduction of surround sound. Audio comes from all directions, including overhead. You are literally inside all of the action. Klipsch proprietary speaker technologies are ideal for delivering the most immersive, dynamic Dolby Atmos listening experience. Controlled directivity and high-performance have been an integral part of Klipsch acoustic design principals since 1946. Your music and movies will never sound the same.



REFERENCE PREMIERE



- Dual 8" Tower with built-in height channel
- Built-in, 2-way Elevation Channel for Dolby
- Atmos[®] • 90° x 90° composite-coated Tractrix[®] Horn
- Removable, magnetic grille





- Rear-firing Tractrix® port for faster, cleaner low frequency output
- Titanium Linear Travel Suspension (LTS) tweeter minimizes distortion and enhances detail

MAIN CHANNEL	
FREQUENCY RESPONSE	32-25kHz +/- 3dB
SENSITIVITY	98dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	150W / 600W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1750Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 8" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Dual Binding Posts
HEIGHT	43.12" (109.5 cm)
WIDTH	10.90" (27.7 cm)
DEPTH	19.80" (50.3 cm)
WEIGHT	71 lb (32.2 kg)
FINISH	Ebony, Walnut

RP-8060FA dual 8" Tower with built-in height channel

SHIPPING QUANTITY:	Single
SHIPPING WEIGHT:	38.1 kg 84 lbs
	04 IDS
PART N	UMBER
1065792 (Ebo	ny)
1065793 (Waln	ut)

HEIGHT CHANNEL	
FREQUENCY RESPONSE	Conforms to Dolby Atmos Specifications
SENSITIVITY	Conforms to Dolby Atmos Specifications
POWER HANDLING (CONT/PEAK)	75W / 300W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2kHz
HIGH FREQUENCY DRIVER	1" Titanium LTS Tweeter with Hybrid Tractrix Horn
LOW FREQUENCY DRIVER	6.5" Cerametallic Cone Woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Acoustic Suspension
INPUTS	Single Binding Posts



- Adds Dolby Atmos® experience to any tower/monitor speaker
- Can be used as surround speaker
- 90° x 90° composite-coated Tractrix[®] Horn .
- Removable, magnetic grille •

RP-500SA	5.25" ELEVATION SPEAKERS
EDEUTIENCA DESDUNCE	Conforms to Dolby Atmos Specifications

FREQUENCY RESPONSE	Conforms to Dolby Atmos Specifications	SH
SENSITIVITY	Conforms to Dolby Atmos Specifications	SH
POWER HANDLING (CONT/PEAK)	75W / 300W	_
NOMINAL IMPEDANCE	8 ohms compatible	
CROSSOVER FREQUENCY	Conforms to Dolby Atmos Specifications	
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn	
LOW FREQUENCY DRIVER	5.25" Cerametallic Cone Woofer	
ENCLOSURE MATERIAL	MDF	
ENCLOSURE TYPE	Sealed	
INPUTS	Single Binding Posts	NOTES
HEIGHT	7.39" (18.8 cm)	
WIDTH	6.81" (17.3 cm)	
DEPTH	11.16" (28.4 cm)	
WEIGHT	9.6 lbs (4.35 kg)	
FINISH	Ebony, Walnut	



REFERENCE



- Built-in Elevation Channel for Dolby Atmos®
- 90° x 90° Tractrix[®] Horn
- Rear-firing Tractrix® port
- Low-Profile Magnetic Grille



HEIGHT CHANNEL	
Frequency Response	Conforms to Dolby Atmos Specifications
Sensitivity	Conforms to Dolby Atmos Specifications
Power Handling	75W/150W
Nominal Impedance	8 ohms compatible
High Frequency Driver	1" Aluminum LTS tweeter mated to a 90° x 90° square Tractrix® Horn
Low Frequency Driver	5.25" spun-copper IMG woofer
Enclosure Type	Acoustic Suspension
Inputs	Single Gold Plated Binding Posts

R-625FA DUAL 6.5" TOWER WITH BUILT-IN HEIGHT CHANNEL

MAIN CHANNEL	
FREQUENCY RESPONSE	38Hz - 21kHz +/- 3dB
SENSITIVITY	96 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	100W/400W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2,000 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 6.5" spun-copper IMG woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via rear-firing Tractrix®ports
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	40" (101.7 cm)
WIDTH INCHES	9.4" (24 cm)
DEPTH INCHES	17.3" (43.9 cm)
PRODUCT WEIGHT LBS	49 lbs (22.2 kg)
FINISHES	Black Textured Wood Grain
INCLUDED ACCESSORIES	Injection molded feet and screws

NOTES:

NOTES:

SHIPPING QUANTITY: Pair SHIPPING WEIGHT: 7.4 kg

> 16.3 lbs PART NUMBER 1066235 (BLK/GNM)



- Adds Dolby Atmos® experience to any tower/monitor speaker
- Can be used as surround speaker
- 90° x 90° Tractrix Horn
- Low-profile magnetic grille

R-41SA 4" ELEVATION SPEAKER OR SURROUND SPEAKER

FREQUENCY RESPONSE	Conforms to Dolby Atmos Specifications
SENSITIVITY	Conforms to Dolby Atmos Specifications
POWER HANDLING (CONT/PEAK)	50W/100W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	4,237 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	4" spun-copper IMG woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Acoustic Suspension
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	7" (18 cm)
WIDTH INCHES	5.75" (14.6 cm)
DEPTH INCHES	13" (33.1 cm)
PRODUCT WEIGHT	6.75 lbs (3.1 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Rubber Feet (4)

REFERENCE PREMIERE SPEAKERS

Klipsch Reference Premiere speakers boldly delivers the power, detail and emotion of the live music experience. Exclusive Tractrix[®] Horn technology improves high-frequency response and extension, while enhancing imaging and dynamics. Proprietary Linear Travel Suspension titanium tweeter maximizes dynamics for detailed performances. Vented tweeter reduces unwanted harmonics for detail and clarity. Klipsch signature copper Cerametallic[™] woofers minimize distortion while prov<u>iding high efficiency</u>



TOWERS



RP-8000F DUAL 8" TOWER

FREQUENCY RESPONSE	32-25kHz +/- 3dB
SENSITIVITY	98dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	150/600
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1750Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 8" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Dual binding posts / bi-wire / bi-amp
HEIGHT	43.12" (109.5 cm)
WIDTH	10.90" (27.7 cm)
DEPTH	17.56" (44.6 cm)
WEIGHT	60 lb (27.2 kg)
FINISH	Ebony, Walnut

SHIPPING QUANTITY:	Single
SHIPPING WEIGHT:	31.3 kg 69 lbs
PART N	UMBER
1065795 (Ebo	ony)
1065796 (Wali	nut)

NOTES:

ALL REFERENCE PREMIERE TOWERS FEATURE:

- 90° x 90° composite-coated Tractrix[®] Horn
- Titanium Linear Travel Suspension Vented Tweeter
- Rear-firing Tractrix® port
- Magnetic grille



RP-6000F	DUAL 6.5" TOWER
-----------------	-----------------

FREQUENCY RESPONSE	34-25kHz +/- 3dB
SENSITIVITY	97dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	125W/500W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1800Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 6.5" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Dual binding posts / bi-wire / bi-amp
HEIGHT	39.62" (100.6 cm)
WIDTH	9.35" (23.7 cm)
DEPTH	17.02" (43.2 cm)
WEIGHT	49 lb (22.2 kg)
FINISH	Ebony, Walnut



NOTES:



RP-5000F	DUAL 5.25" TOWER
----------	------------------

FREQUENCY RESPONSE	35-25kHz +/- 3dB
SENSITIVITY	96dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	125W/500W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1800Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 5.25" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Dual binding posts / bi-wire / bi-amp
HEIGHT	36.12" (91.7 cm)
WIDTH	8.21" (20.8 cm)
DEPTH	14.38" (36.5 cm)
WEIGHT	37 lb (16.8 kg)
FINISH	Ebony, Walnut

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 19.1 kg 42 lbs PART NUMBER 1065801 (Ebony) 1065802 (Walnut)

NOTES:



RP-4000F DUAL 5.25" TOWER

FREQUENCY RESPONSE	37Hz - 25kHz
SENSITIVITY	95dB @2.83V / 1m
POWER HANDLING (CONT/PEAK)	75W / 300W
NOMINAL IMPEDANCE	8 chm compatible
CROSSOVER FREQUENCY	
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 4" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Single Binding Posts
HEIGHT	34.12" (86.7 cm)
WIDTH	7.42" (18.85 cm)
DEPTH	12.03" (30.56 cm)
WEIGHT	29 lb (13.1 kg)
FINISH	Ebony

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 14.5 kg 32 lbs PART NUMBER

1065917 (Ebony)

MONITORS



- 90° x 90° composite-coated Tractrix® Horn
- Titanium Linear Travel Suspension Vented Tweeter
- Rear-firing Tractrix® port
- Magnetic grille



- 90° x 90° composite-coated Tractrix[®] Horn
- Titanium Linear Travel Suspension Vented Tweeter
- Rear-firing Tractrix® port
- Magnetic grille



- 90° x 90° composite-coated Tractrix® Horn
- Titanium Linear Travel Suspension Vented Tweeter
- Rear-firing Tractrix® port
- Magnetic grille

RP-	60	OM	6.5″	MONITOR
-----	----	----	------	---------

RP-500M 6.5" MONITOR

POWER HANDLING (CONT/PEAK) 75W/300W

48-25kHz +/- 3dB

93dB @ 2.83V / 1m

8 ohms compatible

Single binding posts

13.50" (34.3 cm)

6.81" (17.3 cm)

9.50" (24.1 cm)

12 lb (5.4 kg)

Ebony, Walnut

Rubber Feet (8)

5.25" Cerametallic Cone Woofer

Bass Reflex via rear-firing Tractrix® Port

1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn

1500Hz

MDF

FREQUENCY RESPONSE

NOMINAL IMPEDANCE

CROSSOVER FREQUENCY

HIGH FREQUENCY DRIVER

LOW FREQUENCY DRIVER

ENCLOSURE MATERIAL

ENCLOSURE TYPE

INPUTS

HEIGHT

WIDTH

DEPTH

WEIGHT

FINISH

ACCESSORIES

SENSITIVITY

FREQUENCY RESPONSE	45-25kHz +/- 3dB
SENSITIVITY	96dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	100W/400W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1500Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	6.5" Cerametallic Cone Woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Dual binding posts/bi-wire/bi-amp
HEIGHT	15.69" (39.9 cm)
WIDTH	7.95" (20.2 cm)
DEPTH	11.85" (30.1 cm)
WEIGHT	16 lb (7.3 kg)
FINISH	Ebony, Walnut
ACCESSORIES	Rubber Feet (8)

SHIPPING WEIGHT: 17.1 kg 40 lbs PART NUMBER 1065804 (Ebony) 1065805 (Walnut)

SHIPPING QUANTITY: Pair

SHIPPING QUANTITY: Pair Shipping weight: 13.2 kg 29 lbs PART NUMBER

1065807 (Ebony)

NOTES:

RP-400M 6.5" MONITOR

FREQUENCY RESPONSE	52Hz - 25kHz
SENSITIVITY	93dB @2.83V / 1m
POWER HANDLING (CONT/PEAK)	50W / 200W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1500Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	4" Cerametallic Cone Woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Single Binding Posts
HEIGHT	11.73" (29.8 cm)
WIDTH	5.67" (14.4 cm)
DEPTH	7.50" (19.1 cm)
WEIGHT	9 lb (4.1 kg)
FINISH	Ebony
ACCESSORIES	Rubber Feet (8)

SHIPPING QUANTITY: Pair SHIPPING WEIGHT: 9.5 kg

21 lbs

PART NUMBER

1065931 (Ebony)

SHIPPING QUANTITY: Single

SHIPPING WEIGHT: 17.7 kg

39 lbs

PART NUMBER

1065810 (Ebony)

CENTERS

RP-504C QUAD 5.25" CENTER



- 90° x 90° composite-coated Tractrix® Horn
- Titanium Linear Travel Suspension Vented Tweeter
- Rear-firing Tractrix® port
- Magnetic grille



- 90° x 90° composite-coated Tractrix[®] Horn
- Titanium Linear Travel Suspension Vented
 Tweeter
- Rear-firing Tractrix® port
- Magnetic grille



- 90° x 90° composite-coated Tractrix $^{\scriptscriptstyle (\!8\!)}$ Horn
- Titanium Linear Travel Suspension Vented Tweeter
- Rear-firing Tractrix® port
- Magnetic grille

58-25kHz +/- 3dB
97dB @ 2.83V / 1m
150W/600W
8 ohms compatible
500Hz/1500Hz
1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
Quad 5.25" Cerametallic Cone Woofers
MDF
Bass Reflex via rear-firing Tractrix® Port
Single Binding Posts
6.81" (17.3 cm)
31.13" (79.1 cm)
14.46 (36.7 cm)
34 lb (15.4 kg)
Ebony, Walnut
Rubber Feet (4)

RP-404C QUAD 5.25" CENTER

FREQUENCY RESPONSE	59-25kHz +/- 3dB
SENSITIVITY	97dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	125W/500W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	500Hz/1500Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Quad 4″ Cerametallic™ Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Single Binding Posts
HEIGHT	5.7" (14.39 cm)
WIDTH	26.0" (66.04 cm)
DEPTH	13" (33.02 cm)
WEIGHT	28 lb (12.7 kg)
FINISH	Ebony, Walnut
ACCESSORIES	Rubber Feet (4)

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 14.5 kg 32 lbs PART NUMBER

1065813 (Ebony)

NOTES:

NOTES:

RP-600C DUAL 6.5" CENTER

FREQUENCY RESPONSE	58Hz - 25kHz
SENSITIVITY	97dB @2.83V / 1m
POWER HANDLING (CONT/PEAK)	125W / 500W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 6.5" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Single Binding Posts
HEIGHT	7.95" (20.2 cm)
WIDTH	21.93" (55.7 cm)
DEPTH	11.96" (30.4 cm)
WEIGHT	24 lb (10.9 kg)
FINISH	Ebony, Walnut
ACCESSORIES	Rubber Feet (4)



PART NUMBER 1065816 (Ebony) 1065817 (Walnut)



- 90° x 90° composite-coated Tractrix® Horn
 Titanium Linear Travel Suspension Vented Tweeter
- Rear-firing Tractrix® port
- Magnetic grille

FREQUENCY RESPONSE	60-25kHz +/- 3dB
SENSITIVITY	96dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	100W/400W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1800Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 5.25" Cerametallic™ Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Single Binding Posts
HEIGHT	6.81" (17.3 cm)
WIDTH	18.50" (47 cm)
DEPTH	9.5" (22.3 cm)
WEIGHT	18 lb (8.2 kg)
FINISH	Ebony, Walnut
ACCESSORIES	Rubber Feet (4)



NOTES:

- 90° x 90° composite-coated Tractrix® Horn
- Titanium Linear Travel Suspension Vented
 Tweeter
- Rear-firing Tractrix® port
- Magnetic grille

RP-400C DUAL 4.5" CENTER

RP-500C DUAL 5.25" CENTER

FREQUENCY RESPONSE	65Hz - 25kHz
SENSITIVITY	95dB @2.83V / 1m
POWER HANDLING (CONT/PEAK)	75W / 300W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 4" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Single Binding Posts
HEIGHT	5.6" (14.24 cm)
WIDTH	16" (40.64 cm)
DEPTH	9.65" (22.86 cm)
WEIGHT	14 lb (6.4 kg)
FINISH	Ebony
ACCESSORIES	Rubber Feet (4)

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 8.2 kg 18 lbs

PART NUMBER

1065935 (Ebony)

```
NOTES:
```

SHIPPING QUANTITY: Pair

SHIPPING WEIGHT: 17.2 kg

38 lbs

PART NUMBER

1065822 (Ebony) 1065824 (Walnut)

SURROUNDS



- 90° x 90° composite-coated Tractrix® Horn ٠
- Titanium Linear Travel Suspension Vented
- Tweeter •
- Removable, magnetic grille

CROSSOVER FREQUENCY	1400Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 5.25" Cerametallic Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Sealed
INPUTS	Single Binding Posts
HEIGHT	13.85" (35.2 cm)
WIDTH	11.88" (30.2 cm)
DEPTH	7.49" (19 cm)
WEIGHT	16 lb (7.3 kg)
FINISH	Ebony, Walnut
ACCESSORIES	Rubber Feet (8)

• WDST[®] Surround Technology



- 90° x 90° composite-coated Tractrix® Horn
- Titanium Linear Travel Suspension Vented • Tweeter
- Removable, magnetic grille
- WDST[®] Surround Technology

RP-402S DUAL 4.5" SURROUND

RP-502S DUAL 5.25" SURROUND

POWER HANDLING (CONT/PEAK) 100W/400W

58-25kHz +/- 3dB

95dB @ 2.83V / 1m

8 ohms compatible

FREQUENCY RESPONSE

NOMINAL IMPEDANCE

SENSITIVITY

FREQUENCY RESPONSE	62-25kHz +/- 3dB
SENSITIVITY	93dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	75W/300W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1500Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 4" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Sealed
INPUTS	Single Binding Posts
HEIGHT	11.85" (30.1 cm)
WIDTH	10.26" (26.1 cm)
DEPTH	6.51" (16.5 cm)
WEIGHT	13 lb (5.9 kg)
FINISH	Ebony, Walnut
ACCESSORIES	Rubber Feet (8)

SHIPPING QUANTITY: Pair SHIPPING WEIGHT: 15.4 kg 34 lbs PART NUMBER

1065826 (Ebony) 1065827 (Walnut)

NOTES:

COMPONENT AUDIO

REFERENCE SPEAKERS

Now in its sixth generation, the Reference series speakers deliver even higher sound quality precision, clarity and effortless power. A new, larger proprietary Tractrix[®] horn provides improved coverage and bandwidth, and new tweeter and phase plugs ensure greater accuracy. The new rear Tractrix ports produce deep, powerful bass. The line also exudes modern elegance with several new cosmetic upgrades, including angled feet, full-length low-profile magnetic grilles, and a scratch-resistant black wood grain vinyl finish.



TOWERS



- 90° x 90° Tractrix Horn for clean, natural sound
- Rear-firing Tractrix port
- Low-profile magnetic grille



- 90° x 90° Tractrix Horn for clean, natural sound
- Rear-firing Tractrix port
- Low-profile magnetic grille

R-820F DUAL 8" TOWER

FREQUENCY RESPONSE	35Hz - 21kHz +/- 3dB
SENSITIVITY	97 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	150W/600W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1,700 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 8" spun-copper IMG woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via rear-firing Tractrix® ports
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	43" (109.3 cm)
WIDTH INCHES	10.9" (27.7 cm)
DEPTH INCHES	17.5" (44.3 cm)
PRODUCT WEIGHT	54 lbs (24.5 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Injection molded feet and screws

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 28.1 kg 62 lbs

PART NUMBER

1066228 (BLK/GNM)

NOTES:

R-620F DUAL 6.5" TOWER

FREQUENCY RESPONSE	38Hz - 21kHz +/- 3dB
SENSITIVITY	96 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	100W/400W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2,000 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a $90^{\rm o}x90^{\rm o}$ square Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 6.5" spun-copper IMG woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via rear-firing Tractrix® ports
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	40" (101.7 cm)
WIDTH INCHES	9.4" (24 cm)
DEPTH INCHES	15.2" (38.6 cm)
PRODUCT WEIGHT	41 lbs (18.6 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Injection molded feet and screws

SHIPPING QUANTITY: Single
SHIPPING WEIGHT: 22.2 kg
49 lbs
PART NUMBER
1066229 (BLK/GNM)
IOTES:

R-610F 6.5" TOWER



- 90° x 90° Tractrix Horn for clean, natural sound
- Rear-firing Tractrix port
- Low-profile magnetic grille

FREQUENCY RESPONSE	45Hz - 21kHz +/- 3dB
SENSITIVITY	94 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	85W/340W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1,800 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Single 6.5" spun-copper IMG woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via rear-firing Tractrix [®] ports
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	37" (94 cm)
WIDTH INCHES	9.4" (24 cm)
DEPTH INCHES	15.1" (38.4 cm)
PRODUCT WEIGHT	36 lbs (16.3 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Injection molded feet and screws

SHIPPING QUANTITY: Single Shipping Weight: 20 kg 44 lbs Part Number

1066230 (BLK/GNM)

SHIPPING QUANTITY: Pair SHIPPING WEIGHT: 9.8 kg

NOTES:

21.5 lbs **PART NUMBER** 1066234 (BLK/GNM)

NOTES:

MONITORS

R-51M 5.25" MONITORS

FREQUENCY RESPONSE	62Hz - 21kHz +/- 3dB
SENSITIVITY	93 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	85W/340W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1,660 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Single 5.25" spun-copper IMG woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via rear-firing ports
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	13.3" (33.8 cm)
WIDTH INCHES	7" (17.8 cm)
DEPTH INCHES	8.5" (21.5 cm)
PRODUCT WEIGHT	9.1 lbs (4.1 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Rubber Feet (4)

- 90° x 90° Tractrix Horn for clean, natural sound
- Linear Travel Suspension (LTS) tweeter minimizes distortion and enhances detail
- Low-Profile Magnetic Grille


NOTES:

SHIPPING QUANTITY: Pair SHIPPING WEIGHT: 7.4 kg

> 16.3 lbs PART NUMBER 1066233 (BLK/GNM)



- 90° x 90° Tractrix Horn for clean, natural sound
- Linear Travel Suspension (LTS) tweeter minimizes distortion and enhances detail
- Low-Profile Magnetic Grille



FREQUENCY RESPONSE	68Hz - 21kHz +/- 3dB
SENSITIVITY	90 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	50W/200W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1,730 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a $90^{o}x90^{o}squareTractrix^{\otimes}Horn$
LOW FREQUENCY DRIVER	Single 4" spun-copper IMG woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via rear-firing ports
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	11.3" (28.7 cm)
WIDTH INCHES	5.75" (14.6 cm)
DEPTH INCHES	7.9" (20 cm)
PRODUCT WEIGHT	7 lbs (3.2 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Rubber Feet (4)

CENTERS



- 90° x 90° Tractrix Horn for clean, natural sound
- Linear Travel Suspension (LTS) tweeter minimizes distortion and enhances detail
- Low-Profile Magnetic Grille



- 90° x 90° Tractrix Horn for clean, natural sound
- Linear Travel Suspension (LTS) tweeter minimizes distortion and enhances detail
- Low-Profile Magnetic Grille
- Two front-firing Tractrix® ports

R-52C DUAL 5.25" CENTER

FREQUENCY RESPONSE	89Hz - 21kHz +/- 3dB
SENSITIVITY	95 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	100W/400W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1,630 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a 90° x 90° square Tractrix $^{\rm \oplus}$ Horn
LOW FREQUENCY DRIVER	Dual 5.25" spun-copper IMG woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Sealed
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	7.3" (18.5 cm)
WIDTH INCHES	18.75" (47.6 cm)
DEPTH INCHES	7.6" (19.4 cm)
PRODUCT WEIGHT	13.5 lbs (6.1 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Rubber Feet (4)

R-34C DUAL 5.25" CENTER

FREQUENCY RESPONSE	82Hz - 21kHz +/- 3dB
SENSITIVITY	96 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	100W/400W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1,600 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a $90^{o}x90^{o}squareTractrix^{\otimes}Horn$
LOW FREQUENCY DRIVER	Quad 3.5" spun-copper IMG woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via forward-firing Tractrix®ports
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	5.2" (13.3 cm)
WIDTH INCHES	26" (66 cm)
DEPTH INCHES	6.2" (15.7 cm)
PRODUCT WEIGHT	13 lbs (5.9 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Rubber Feet (4)



SHIPPING QUANTITY: Single SHIPPING WEIGHT: 7.3 kg

NOTES:

16 lbs PART NUMBER 1066231 (BLK/GNM)

1066232 (BLK/GNM)

NOTES:

FOR THE LASTEST SPECS AND PRICES VISIT KLIPSCH.COM

SURROUNDS



- Adds Dolby Atmos® experience to any tower/monitor speaker
- Can be used as surround speaker
- 90° x 90° Tractrix Horn
- Low-profile magnetic grille

R-41SA 4" DOLBY-ATMOS ELEVATION SPEAKER OR SURROUND SPEAKER

FREQUENCY RESPONSE	Conforms to Dolby Atmos Specifications
SENSITIVITY	Conforms to Dolby Atmos Specifications
POWER HANDLING (CONT/PEAK)	50W/100W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	4,237 Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS tweeter mated to a 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	4" spun-copper IMG woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Acoustic Suspension
INPUTS	Single Gold Plated Binding Posts
HEIGHT INCHES	7" (18 cm)
WIDTH INCHES	5.75" (14.6 cm)
DEPTH INCHES	13" (33.1 cm)
PRODUCT WEIGHT	6.75 lbs (3.1 kg)
FINISHES	Black Textured Wood Grain Vinyl
INCLUDED ACCESSORIES	Rubber Feet (4)

SHIPPING QUANTITY: Pair Shipping Weight: 7.4 kg

16.3 lbs Part Number

1066235 (BLK/GNM)

COMPONENT AUDIO

SPL SUBWOOFERS

The SPL subwoofer line combines high performance at moderate prices with class leading maximum output levels. Comprised of three subwoofers, the SPL series boasts copper Cerametallic[™] woofers that minimize distortion while providing high efficiency. All subs have all-digital amplifiers that provide more impact and powerful bass. The front-firing slot port allows for placement flexibility.



NOTES:

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 40.82 kg

> 90 lbs PART NUMBER 1067309 (Black EUA)



- 400W RMS/ 800W Peak Power
- Front-firing slot port
- Low-pass crossover and phase control
- WA-2 Wireless Subwoofer Kit capable



- 300W RMS / 600W Peak
- Front-firing slot port
- Low-pass crossover and phase control
- WA-2 Wireless Subwoofer Kit capable



- 200W RMS / 450W Peak Power
- Front-firing slot port
- Low-pass crossover and phase control
- WA-2 Wireless Subwoofer Kit capable

SPL 150 15" POWERED SUBWOOFER

FREQUENCY RESPONSE	18Hz - 125Hz
MAXIMUM ACOUSTIC OUTPUT	122dB
AMPLIFIER TYPE	All digital
AMPLIFIER POWER	400W / 800W
WOOFER	15" (38.1 cm) long-throw copper spun cerametallic, front-firing woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex
INPUTS	L/R line-level/LFE RCA jacks, Wireless WA-2 Port
HEIGHT	21.5" (54.61 cm)
WIDTH	19.5" (49.53 cm)
DEPTH	22.3" (56.64 cm)
WEIGHT	75.4 lbs / 34.2 kg
FINISH	Ebony Vinyl

SPL 120 12" POWERED SUBWOOFER

FREQUENCY RESPONSE	24Hz - 125Hz
MAXIMUM ACOUSTIC OUTPUT	118dB
AMPLIFIER TYPE	Class D with Analog Preamp Stage
AMPLIFIER POWER	300W RMS / 600W Peak
WOOFER	12" Long-Throw Cerametallic
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via Front-Firing Slot Port
INPUTS	Dual RCA/LFE Line In, WA-2 Wireless Port
HEIGHT	17-3/4" (45.1 cm)
WIDTH	14-11/16" (37.4 cm)
DEPTH	19-7/8" (50.6 cm)
WEIGHT	45 lbs (20.4kg)
FINISH	Ebony Vinyl

SHIPPING WEIGHT: 27.6 kg 61 lbs PART NUMBER 1065967 (Black EUA) NOTES:

SHIPPING QUANTITY: Single

SPL 100 10" POWERED SUBWOOFER

FREQUENCY RESPONSE	27Hz - 125Hz
MAXIMUM ACOUSTIC OUTPUT	114dB
AMPLIFIER TYPE	Class D with Analog Preamp Stage
AMPLIFIER POWER	200 W RMS / 450 W Peak
WOOFER	10" Long-Throw Cerametallic
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via Front-Firing Slot Port
INPUTS	Dual RCA/LFE Line In, WA-2 Wireless Port
HEIGHT	16-9/16" (42.1 cm)
WIDTH	14" (35.6 cm)
DEPTH	17-5/16" (45.1 cm)
WEIGHT	37 lbs (16.8kg)
FINISH	Ebony Vinyl

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 25 kg 55 lbs PART NUMBER

1065965 (Black EUA)

WIRELESS KITS



- Allows for powerful bass extension with fewer wires
- Hassle-free setup
- Plug 'n play functionality
- Compatible with SPL-150, SPL-120 and SPL-100

WA-2 WIRELESS SUBWOOFER KIT

FREQUENCY OF OPERATION	2.4 GHz ISM band	SHIPPING QUANTITY: Single
CHANNEL SELECTION	Automatic	SHIPPING WEIGHT: 0.45 kg
SIGNAL RANGE	50 feet (15m)	1.01 lbs
FREQUENCY RESPONSE	15 Hz - 150 Hz +/- 3 dB	PART NUMBER
		1013170 (Black CE)

REFERENCE SUBWOOFERS

Prepare to be moved. Reference subwoofers are the perfect combination of power, sophistication and heart-pounding bass. Packing a serious punch, these subwoofers will not only wake your neighbors, they'll piss them off. Reference Subwoofers provide thunderous, detailed bass and create a solid foundation for any audio system.





- All-digital amp delivers 400 watts of dynamic power
- Front-firing driver
- Low pass crossover and phase control

R-120SW 12" POWERED SUBWOOFER

FREQUENCY RESPONSE	29Hz - 120Hz +/- 3dB
MAXIMUM ACOUSTIC OUTPUT	116 dB
AMPLIFIER	All-digital
AMPLIFIER POWER (CONT/PEAK)	200W/400W
AMPLIFIER FEATURES	Volume, Low-pass, 0/180 phase, Auto Power On
DRIVER COMPONENTS	12" high excursion spun-copper IMG woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via rear-firing port
INPUTS	Line level/LFE RCA jacks
HEIGHT	16.5" (41.9 cm)
WIDTH	14" (35.6 cm)
DEPTH	19.2" (48.8 cm)
WEIGHT	31 lbs (14.1 kg)
FINISHES	Black Textured Wood Grain Vinyl

SHIPPING QUANTITY: Single
SHIPPING WEIGHT: 18 kg
39.7 lbs
PART NUMBER
1065960 (BLK/GNM EUA)

NOTES:

I

SHIPPING QUANTITY: Single SHIPPING WEIGHT: 14.5 kg

NOTES:

32 lbs

PART NUMBER 1065958 (BLK/GNM EUA)



- All-digital amp delivers 300 watts of dynamic power
- Front-firing driver
- Low pass crossover and phase control

R-100SW 10" POWERED SUBWOOFER

FREQUENCY RESPONSE	32Hz - 120Hz +/- 3dB
MAXIMUM ACOUSTIC OUTPUT	112 dB
AMPLIFIER	All-digital
AMPLIFIER POWER (CONT/PEAK)	150W/300W
AMPLIFIER FEATURES	Volume, Low-pass, 0/180 phase, Auto Power On
DRIVER COMPONENTS	10" high excursion spun-copper IMG woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-Reflex via rear-firing port
INPUTS	Line level/LFE RCA jacks
HEIGHT	14.5" (36.8 cm)
WIDTH	12.5" (31.8 cm)
DEPTH	16.4" (41.7 cm)
WEIGHT	24 lbs (10.9 kg)
FINISHES	Black Textured Wood Grain Vinyl



- All-digital amplifier delivers 150 watts with high efficiency
- Down-firing driver
- Low pass crossover and phase control

R-8SW 8" SUBWOOFER

FREQUENCY RESPONSE	38 Hz - 120 Hz +/- 3dB	Sł
MAXIMUM ACOUSTIC OUTPUT	108dB	
AMPLIFIER	All-digital	
AMPLIFIER POWER	50W / 150W	
DRIVE COMPONENTS	8" (20.3cm) high excursion, IMG, down-firing woofer	
ENCLOSURE MATERIAL	MDF	
ENCLOSURE TYPE	Bass Reflex via down-firing tube port	NOT
INPUTS	Line level/LFE RCA jacks	
HEIGHT	13.25" (33.66 cm)	
WIDTH	11.75" (29.85cm)	
DEPTH	11.75" (29.85cm)	
WEIGHT	15.0 lbs (6.8kg)	
FINISH	Brushed Black Polymer Veneer	
FEATURES	Volume, Lowpass, Phase, Auto Power	
PHASE	Switchable 0-180 degrees	

PPING QUANTITY: Single SHIPPING WEIGHT: 12.4 kg

27.3 lbs

PART NUMBER

1063512 (Black CE)

S:

DESIGNER ON-WALL

REFERENCE PREMIERE DESIGNER ON-WALL

Klipsch Reference Premiere Designer On-Wall is a first class low-profile home audio solution, offering minimalist home theater system speakers that add beauty to any room. With its modern-day aesthetic and legendary sonic signature – great sound has never looked so good.



SHIPPING QUANTITY: Single

NOTES:

SHIPPING WEIGHT: 6 kg

13.22 lbs PART NUMBER 1064178 (Black)



- 3-Channel passive LCR sound bar
- Wall-mountable or table-mountable with included glass base
- True Reference Premiere acoustics in a slim on-wall solution

FREQUENCY RESPONSE	65Hz - 24Hz +/-3dB
SENSITIVITY	92 dB @ 2.83V/1 meter
POWER HANDLING (CONT/PEAK)	50W/200W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2200Hz
HIGH FREQUENCY DRIVER	Three 1" (2.54cm) Titanium diaphragm compression drivers mated to a 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Four 3.5" (8.89 cm) active long-throw Cerametallic woofers (One each for left and right channels, two for center channel)
ENCLOSURE MATERIAL	Injection molded polymer
ENCLOSURE TYPE	Bass-reflex
INPUTS	Single wire 5-way binding posts (3 sets)
HEIGHT	6 " (15.24cm)
WIDTH	42" (106.68cm)
DEPTH	2.4" (6.10cm)
WEIGHT	12 lbs (5.44 kg)
FINISH	Matte black paint

RP-440D SB SLIM ON-WALL 3-CHANNEL PASSIVE LCR SOUND BAR



- Slim on-wall LCRS speaker
- Wall-mountable or table-mountable with inluded glass base
- True Reference Premiere acoustics in a slim on-wall solution

RP-640D SLIM ON-WALL LCRS SPEAKER

FREQUENCY RESPONSE	55Hz - 24kHz +/-3dB
SENSITIVITY	94dB @ 2.83V/1 meter
POWER HANDLING (CONT/PEAK)	75W/300W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2200Hz
HIGH FREQUENCY DRIVER	1" (2.54cm) Titanium diaphragm compression driver mated to a 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Two 3.5" (8.89 cm) active long-throw Cerametallic woofers Four 3.5" (8.89 cm) passive Cerametallic radiators
ENCLOSURE MATERIAL	Injection molded polymer
ENCLOSURE TYPE	Bass-reflex via passive radiators
INPUTS	Single wire 5-way binding posts
HEIGHT	28.5 " (72.39cm)
WIDTH	6" (15.24cm)
DEPTH	2.4" (6.1cm)
WEIGHT	8 lbs (3.63 kg)
FINISH	Matte black paint

SHIPPING QUANTITY:	Single
SHIPPING WEIGHT	4.1 kg 9 lbs
PART N	JMBER

1064179 (Black)

NOTES:



- Slim on-wall LCRS speaker
- Wall-mountable or table-mountable with included glass base
- True Reference Premiere acoustics in a slim on-wall solution

RP-240D SLIM ON-WALL LCRS SPEAKER

FREQUENCY RESPONSE	67Hz - 24kHz +/-3dB	
SENSITIVITY	94dB @ 2.83V/1 meter	
POWER HANDLING (CONT/PEAK)	75W/300W	
NOMINAL IMPEDANCE	8 ohms compatible	
CROSSOVER FREQUENCY	2200Hz	
HIGH FREQUENCY DRIVER	1" (2.54cm) Titanium diaphragm compression driver mated to a 90° x 90° square Tractrix® Horn	
LOW FREQUENCY DRIVER	Two 3.5" (8.89 cm) long-throw Cerametallic woofers	
ENCLOSURE MATERIAL	Injection molded polymer	
ENCLOSURE TYPE	Bass-reflex	
INPUTS	Single wire 5-way binding posts	
HEIGHT	16 " (40.64cm)	
WIDTH	6" (15.24cm)	
DEPTH	2.4" (6.1cm)	
WEIGHT	5.25lbs (2.38 kg)	
FINISH	Matte black paint	

SHIPPING QUANTITY:	Single
SHIPPING WEIGHT:	2.9 kg 6.4 lbs
PART NUMBER	

1064180 (Black)

NOTES:



- Slim on-wall LCRS speaker
- Wall-mountable or table-mountable with included glass base
- True Reference Premiere acoustics in a slim on-wall solution

RP-140D SLIM ON-WALL LCRS SPEAKER

69Hz - 24kHz+/-3dB
91dB @ 2.83V/1 meter
50W/200W
8 ohms compatible
2200Hz
1" (2.54cm) Titanium diaphragm compression driver mated to a 90° x 90° square Tractrix® Horn
3.5" (8.89 cm) long-throw Cerametallic woofer
Injection molded polymer
Bass-reflex
Single wire 5-way binding posts
12 " (30.48cm)
6" (15.24cm)
2.4" (6.1cm)
3.75 lbs (1.7 kg)
Matte black paint

SHIPPING QUANTITY: Single
SHIPPING WEIGHT: 2.2 kg 4.85 lbs
PART NUMBER
1064181 (Black)

REFERENCE THEATER PACK

We've taken the premium materials and acoustic technology of our revered Reference series and designed a beautiful 5.0 surround sound system to pair with your favorite subwoofer and AV receiver. The Reference Theater Pack brings the Klipsch cinematic sound into your home with an incredibly minimal footprint.





- Spun Copper IMG Woofers
- Linear Travel Suspension Horn-Loaded
 Tweeters
- AV Receiver and Subwoofer not included

REFERENCE THEATER PACK 5.0 HOME THEATER SYSTEM

SATELLITE and CENTE	RCHANNEL	SHIPPING QUANTITY: System
FREQUENCY RESPONSE	110Hz - 23kHz +/- 3dB	SHIPPING WEIGHT: 10.8 kg
SENSITIVITY	Satellite: 91dB @ 2.83 volts / 1 meter Center: 94dB @ 2.83 volts / 1 meter	23.81 lbs PART NUMBER
POWER HANDLING	Satellite: 50 watts (200 watts peak) Center: 75 watts (300 watts peak)	1064662 (Black)
NOMINAL IMPEDANCE	8 ohms compatible	-
HIGH FREQUENCY DRIVER	Satellite and Center: 3/4" (1.9 cm) aluminum diaphragm compression driver mated to 90° x 90° Tractrix® horn	NOTES:
LOW FREQUENCY DRIVER	Satellite: 3.5" (8.9 cm) copper IMG woofer Center: Dual 3.5" (8.9 cm) copper IMG woofer	-
DIMENSIONS	Satellite: 7.75" (19.7cm) H x 4.38" (11.1cm) W x 5.37" (13.7cm) D Center: 4.38" (11.1cm) H x 10.75" (27.3cm) W x 5.37" (13.7cm) D	-
WEIGHT	Satellite: 3 lbs (1.4kg) Center: 5 lbs (2.3kg)	-
MOUNTING	Satellite: Keyhole and 1/4" x 20 threaded insert Center: Dual Keyhole with dual 1/4" x 20 threaded insert	-
SPEAKER WIRE	14-18 gauge compatible	-

REFERENCE CINEMA SYSTEM

REFERENCE CINEMA SYSTEM

The Reference Cinema System with Dolby Atmos combines the acoustic technology of our coveted Reference Series with Dolby Atmos technology to bring you an immersive, multidimensional home theater system to pair with your favorite A/V receiver.





- 360° Dolby Atmos® listening experience
- 90° X 90° TRACTRIX[®] HORN
- LINEAR TRAVEL SUSPENSION (LTS) ALUMINUM TWEETER
- SPUN COPPER IMG WOOFER
- Easily add a subwoofer

REFERENCE C	INEMA SYSTEM	WITH DOLBY ATMOS 5.0.4 HOME THEATER SYSTEM
SATELLITE		
FREQUENCY RESPONSE	90Hz-20kHz (+/- 3dB)	
SENSITIVITY	92 dB @ 2.83V / 1M	
POWER HANDLING (CONT/PEAK)	75W/300W	
NOMINAL IMPEDANCE	8 ohms compatible	

CROSSOVER FREQUENCY	2000Hz	
HIGH FREQUENCY DRIVER	1" Aluminum LTS Tweeter Mated to a 90x90 Tractrix® Horn	
LOW FREQUENCY DRIVER	5.25" Spun-Copper IMG Woofer	
INPUTS	Single Gold Plated Binding Posts	
ENCLOSURE TYPE	Bass-Reflex via dual front-firing ports	
HEIGHT	13.47" (342.1 mm)	
WIDTH	6.47" (164.3 mm)	
DEPTH	7.45" (189.2 mm)	
WEIGHT	8.2 lb (3.72 kg)	
MOUNTING	1/4" x 20 Threaded Insert	

SHIPPING QUANTITY: System	
SHIPPING WEIGHT: 18.03 kg	
39.75 lbs	
PART NUMBER	
1069251	

CENTER CHANNEL	
FREQUENCY RESPONSE	80Hz-20kHz (+/- 3dB)
SENSITIVITY	91 dB @ 2.83V/1M
POWER HANDLING (CONT/PEAK)	75W/300W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1800Hz
HIGH FREQUENCY DRIVER	1" Aluminum LTS Tweeter Mated to a 90x90 Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 4" Spun-Copper IMG Woofers
INPUTS	Single Gold Plated Binding Posts
ENCLOSURE TYPE	Bass-Reflex via dual front-firing ports
HEIGHT	5.16" (131.1 mm)
WIDTH	17.60" (447.0 mm)
DEPTH	6.07" (154.2 mm)
WEIGHT	7.4 lb (3.36 kg)
MOUNTING	Dual 1/4" x 20 Threaded Insert

HEIGHT CHANNEL		
FREQUENCY RESPONSE	Conforms to Dolby Atmos Specifications	
SENSITIVITY	Conforms to Dolby Atmos Specifications	
POWER HANDLING (CONT/PEAK)	40W/160W	
NOMINAL IMPEDANCE	8 ohms compatible	
DRIVER	4" Polyfiber Woofer	
ENCLOSURE TYPE	Acoustic Suspension	
INPUTS	Single Gold Plated Binding Posts	



POWERED AUDIO SYSTEMS

CINEMA SOUND BARS

Combining the left, right and center channels into one slick package, our sound bars will free you from underperforming TV speakers and deliver a world of powerful, crisp sound in an extremely thin package. Klipsch sound bars are designed with a combination of hand-crafted, high-quality wood materials and legendary Klipsch technology to bring you sound as big as the picture.

CINEMA 1200





- 7.1.4 Dolby Atmos Decoding
- Wireless 12" Subwoofer
- Independent Wireless Surrounds Included
- HDMI-eArc
- 8K video Pass-Through 30 Hz / 4K video Pass-Through 120 Hz

5.1.4 DOLBY ATMOS SOUN	D BAR SYSTEM WITH 12" WIRELESS SUB AND WIRELESS SURROUNDS
SPEAKER SYSTEM	54" 5.1.4 Dolby Atmos Soundbar System with 12" Wireless Subwoofer and Wireless Surround Speakers
MAX ACOUSTIC OUTPUT	109 dB
HIGH FREQUENCY DRIVERS	(3) 1" (25.4mm) soft dome tweeters mated to Tractrix* horns
MIDRANGE	(6) 3" (76.2mm) high output oval fiber composite cone woofers
HEIGHT CHANNELS	3" (76.2mm) high output Cerametallic cone woofers
SURROUNDS	3" (76.2mm) high output fiber composite cone woofers
SUBWOOFER	12" (305mm) wireless ported subwoofer
ENCLOSURE TYPE	Bar: Wood • Subwoofer: Wood • Surround: Wood
TOTAL SYSTEM POWER	1200W
FREQUENCY RESPONSE	22-20kHz
INPUTS	HDMI-eARC • (2) HDMI • Bluetooth® • 3.5mm Analog • Optical Digital
OUTPUTS	Subwoofer (RCA) Output
DIMENSIONS (BAR)	54" (137.2 cm) W x 2 15/16" (7.5cm) H x 6 3/16" (15.7cm) D
DIMENSIONS (SUBWOOFER)	15 5/8" (39.6cm) W x 20 3/8" (51.6cm) H x 15 7/8" (40.3cm) D
FINISH	Black (interchangeable walnut end caps included)
VOLTAGE	100-240V 50/60Hz internal power supply
WEIGHT	42 lbs (14.52kg)
INCLUDED ACCESSORIES	LED Backlit Remote control (2) 1.5m power cord (Region specific) (2) Keyhole mounting clip(With 1/4 - 20 Screw) Wall mount template (2) AA batteries (1) 1.5m HDMI Cable
MOUNTING OPTIONS	1/4-20 Keyhole Mount • Included slim-depth wall brackets

CINEMA 800

3.1 SOUNDBAR WITH 10" WIRELESS SUBWOOFER

500	NEW
	1

- 7.1.4 Dolby Atmos Decoding
- Wireless 10" Subwoofer
- Surround 3 compatible
- HDMI-eArc
- 8K video Pass-Through 30 Hz / 4K video Pass-Through 120 Hz

MOUNTING OPTIONS	1/4-20 Keyhole Mount • Included slim-depth wall brackets
INCLUDED ACCESSORIES	LED Backlit Remote control (2) 1.5m power cord (Region specific) (2) Keyhole mounting clip(With 1/4 - 20 Screw) Wall mount template (2) AA batteries (1) 1.5m HDMI Cable
WEIGHT	42 lbs (14.52kg)
VOLTAGE	100-240V 50/60Hz internal power supply
WEIGHT	22 lbs (9.98 kg)
VOLTAGE	100-240V 50/60Hz internal power supply
FINISH	Black (interchangeable walnut end caps included)
DIMENSIONS (SUBWOOFER)	14 1/4" (36.8) W x 18 1/2" (47.1cm) H x 14 1/2 (36.8cm) D
DIMENSIONS (BAR)	48" (121.9cm) W x 2 7/8" (7.3cm) H x 3 3/8 (8.6cm) D
OUTPUTS	Subwoofer (RCA) Output
INPUTS	HDMI-eARC ${\boldsymbol{\cdot}}$ (2) HDMI ${\boldsymbol{\cdot}}$ Bluetooth ${}^{\scriptscriptstyle (\! 0\!)} {\boldsymbol{\cdot}}$ 3.5mm Analog ${\boldsymbol{\cdot}}$ Optical Digital
FREQUENCY RESPONSE	28-20kHz
SYSTEM POWER	800W
ENCLOSURE TYPE	Bar: Wood • Subwoofer: Wood
SUBWOOFER	10" (254mm) wireless ported subwoofer
MIDRANGE	(4) 3" (76.2mm) high output oval fiber composite cone woofers
HIGH FREQUENCY DRIVERS	(3) 1" (25.4mm) soft dome tweeters mated to Tractrix® horns
MAX ACOUSTIC OUTPUT	107dB
SPEAKER SYSTEM	48" 3.1 Dolby Atmos soundbar with 10" wireless subwoofer



SHIPPING QUANTITY	/: Single	
SHIPPING WEIGHT:	14.92 kg 32.9 lbs	
	02.7 100	

PART NUMBER 1067540 (Black EUA)

Klipsch
Dolby Atmos

■●●Dolby Atmos speaker system

🚯 Bluetooth

Homi

Google Chromecast

Google Assistant

alexa

UNTING OPTIONS



- Wireless 10" subwoofer
- HDMI connection
- High-quality wood materials
- Surround 3 compatible

3.1 SOUNDBAR WITH 10'	' WIRELESS SUBWOOFER	
SPEAKER SYSTEM	45" 3.1 soundbar with 10" wireless subwoofer	SHIPPING QUANTITY: Single
MAX ACOUSTIC OUTPUT	103 dB	SHIPPING WEIGHT: 13.25 kg
HIGH FREQUENCY DRIVERS	(3) 1" (25.4mm) soft dome tweeters mated to Tractrix $^{\otimes}$ horns	23.2 IU3
MIDRANGE	(4) 3" (76.2mm) high output oval fiber composite cone woofers	PART NUMBER
SUBWOOFER	10" (254 mm) wireless ported subwoofer	1068778 (Black EUA)
ENCLOSURE TYPE	Bar: Wood • Subwoofer: Wood	Klipsch
SYSTEM POWER	600W	CONNECT
FREQUENCY RESPONSE	28-20kHz	🛞 Bluetooth
INPUTS	HDMI-ARC • Bluetooth® • 3.5mm Analog • Optical Digital	TI DOLBY AUDIO
OUTPUTS	Subwoofer (RCA) Output	
DIMENSIONS (BAR)	45" (114.3cm) W x 2 7/8" (7.3cm) H x 3 3/8 (8.6cm) D	
DIMENSIONS (SUBWOOFER)	14 1/4" (36cm) W x 18 1/2" (47cm) H x 14 1/2" (37cm) D	
FINISH	Black	
VOLTAGE	100-240V 50/60Hz internal power supply	
WEIGHT	30.8 lbs (13.97 kg)	
INCLUDED ACCESSORIES	LED Backlit Remote control (2) 1.5m power cords (Region specific) (2) Keyhole mounting Clips (with 1/4 - 20 Screw) Wall mount template (2) AAA batteries 1.5m HDMI Cable	
MOUNTING OPTIONS	1/4 20 Thread • Included slim-depth wall brackets	



- Wireless 8" subwoofer
- HDMI connection
- High-quality wood materials

CINEMA 400

CINEMA 600

2.1 SOUNDBAR WITH 8"	WIRELESS SUBWOOFER	
SPEAKER SYSTEM	40" 2.1 soundbar with 8" wireless subwoofer	SHIPPING QUANTITY: Single
MAX ACOUSTIC OUTPUT	99 dB	SHIPPING WEIGHT: 9.07 kg
HIGH FREQUENCY DRIVERS	(2) 1" (25mm) soft dome tweeters mated to Tractrix® horn	20105
MIDRANGE	(2) 3" (76.2mm) oval fiber composite cone woofers	PART NUMBER
SUBWOOFER	8" (203mm) ported subwoofer	1068775 (Black EUA)
ENCLOSURE TYPE	Bar: Wood (Sealed) • Subwoofer: Wood	
SYSTEM POWER	TBA	😽 Bluetooth
FREQUENCY RESPONSE	35-20KHz	DOLBY AUDIO
INPUTS	HDMI-ARC • Bluetooth® • 3.5mm Analog • Optical Digital	– Homi
OUTPUTS	Subwoofer Output	A DEPENDENT OF MALTHEAD PRIMARY
DIMENSIONS (BAR)	39 15/16" (101.4cm) W x 2 7/8" (7.3cm) H x 3 3/8 (8.6cm) D	
DIMENSIONS (SUBWOOFER)	11 7/8" (30.2cm) W x 16 1/8" (41cm) H x 16 1/8" (41cm) D	
FINISH	Black	
VOLTAGE	100-240V 50/60Hz internal power supply	
WEIGHT	27.5 lbs (12.47 kg)	
INCLUDED ACCESSORIES	Remote control (2) 1.5m power cord (Region specific) (2) Keyhole mounting clip (With 1/4 - 20 Screw) Wall mount template (2) AAA batteries HDMI Cable	
MOUNTING OPTIONS	1/4 20 Thread • Included slim-depth wall brackets	

31



• Compatible with Cinema 600 and Cinema 800

• High-quality wood materials

SPEAKER SYSTEM	2.0 Wireless Surround (Pair)
MAX ACOUSTIC OUTPUT	94dB @1M Anechoic each / 100dB @1M Anechoic pair
FULL RANGE WOOFER	3"
ENCLOSURE TYPE	Wood (Sealed)
SYSTEM POWER	60 watts
FREQUENCY RESPONSE	120 Hz - 20kHz
HEIGHT	6.5" (16.5 cm)
WIDTH	4.25" (10.8 cm)
DEPTH	4.25" (10.8 cm)
MOUNTING	1/4" x 20 threaded insert
FINISH	Black
VOLTAGE	100-240V 50/60Hz internal power supply
WEIGHT	2.2 lbs
INCLUDED ACCESSORIES	(2) 1.5m power cord (Region specific) Wireless dongle for Sound Bar

SURROUND 3 WIRELESS SURROUNDS

SHIPPING QUANTITY: Pair SHIPPING WEIGHT: 2.5 kg

5.5 lbs

PART NUMBER

1067531 (Black EUA)

NOTES:

PROMEDIA

The Klipsch ProMedia desktop system single-handedly raises the bar on what is defined as exceptional sound from a computer audio system. Dual horn-loaded satellite speakers and a robust subwoofer deliver room-filling, crystal-clear acoustics that takes your games, movies, and music to the next level.





- Powerful enough to double as an entertainment center
- Wireless Bluetooth® Connectivity • Compatible with other devices via a •
- Headphone Jack and Mini Plug Input

PROMEDIA 2.1 BLUETOOTH DESKTOP SYSTEM

SYSTEM POWER	Total System Power: 100 watts continuous/200 watts peak @ <0.2% THD 260 watts short-term peak power Satellites: 18 watts/channel continuous @ <0.2% THD, 1kHz 26 watts/channel short-term power @ <5% THD, 1kHz Subwoofer: 65 watts continuous @ <0.2% THD, 50 Hz 80 watts short-term power @ <5% THD, 50Hz	SHIPPING QUANTITY Shipping weigh Part 1064066 (B
FREQUENCY RESPONSE	35Hz ~ 22kHz	1064066 (E
SATELLITE CROSSOVER FREQUENCY	3.5kHz	
ENCLOSURE MATERIAL	Satellites: ABS	😵 Bluetootl
ENCLOSURE TYPE	Subwoofer: MDF	NOTES:
HIGH FREQUENCY HORN	Satellites: Sealed	NUTES:
INPUTS	Subwoofer: Bass Reflex	
TYPICAL MAXIMUM OUTPUT	90° x 40° MicroTractrix®	
OUTPUTS	3.5mm miniplug	
DIMENSIONS	Satellite: 8.5" (21.59cm) H x 4.2" (10.67cm) W x 5.67" (14.4cm) D Subwoofer: 9.5" (24.13cm) H x 9.8" (24.9cm) W x 10.2" (25.9cm) D	
FINISH	Black	
SUBWOOFER	One, side-firing 6.5" (16.51cm) long-throw fiber composite cone	
TWEETER	19mm PEI dome	
VOLTAGE	110/120 VAC	
WEIGHT	Satellite: 2.11bs (0.95kg) Subwoofer: 11 lbs (5kg)	

Y: System GHT: 8.7 kg 19.18 lbs

> RT NUMBER (Black EUA)



POWERED AUDIO SYSTEMS

POWERED MONITORS

A truly powerful, small form-factor music monster packed with Klipsch acoustics with integrated power and Bluetooth® wireless technology. Add any Klipsch subwoofer for a full-fledged 2.1 stereo sound system that will bully any sound bar on the planet. These versatile speakers connect to virtually anything -Bluetooth® wireless technology, phono pre-amp, USB, optical, and analog. Small, yet powerful, the R-51PM and R-41PM use aluminum Linear Travel Suspension horn-loaded tweeters and copper-spun, high-output IMG woofers to deliver true Klipsch Reference acoustics.





• 90° x 90° Tractrix Horn for clean, natural sound

- Bluetooth[®] Wireless Technology
- Connect to virtually any source

R-51PM 5.25" POWERED MONITORS	S
-------------------------------	---

FREQUENCY RESPONSE	68Hz - 21kHz
DYNAMIC BASS EXTENSION	49Hz @ 35% Volume
MAX OUTPUT	107.3 dB
TOTAL SYSTEM POWER	120W Total System Power (140W Peak) 60W per channel cont. @<%1 THD
HIGH FREQUENCY DRIVER	1" (2.5cm) Aluminum diaphragm compression driver mated to 90° x 90° square Tractrix® horn
LOW FREQUENCY DRIVER	5.25" (13.3cm) copper-spun magnetically shielded IMG woofer
CROSSOVER FREQUENCY	1663 Hz (Passive)
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-reflex via rear-firing port
INPUTS	Bluetooth [®] wireless technology • Phono/Line analog (with switch and ground screw terminal) • 3.5mm analog mini jack • USB digital • Optical digital
OUTPUTS	Single RCA line level output for connection to subwoofer
DIMENSIONS	13" (33.02 cm) H X 7" (17.78 cm) W x 8.5" (21.59 cm) D
WEIGHT	10.6 lbs (4.8 kg)
FINISH	Black
VOLTAGE	100V-240V 50/60Hz internal power supply with region specific power cords
INCLUDED ACCESSORIES	Remote control (with 2 x AAA batteries) • 4M speaker wire with soldered tips • 2M power cord (region specific) • 2M USB Type A to Type B cable • Rubber feet



- 90° x 90° Tractrix Horn for clean, natural sound
- Bluetooth[®] Wireless Technology
- Connect to virtually any source

R-41PM 4" POWERED MONITORS

FREQUENCY RESPONSE	64Hz - 21 kHz
DYNAMIC BASS EXTENSION	40 Hz @ 35% Volume
MAX OUTPUT	105.5dB
TOTAL SYSTEM POWER	70W Total System Power (140W Peak) 35W per channel cont. @ <%1 THD
HIGH FREQUENCY DRIVER	1" (2.5cm) Aluminum diaphragm compression driver mated to 90° x 90° square Tractrix® horn
LOW FREQUENCY DRIVER	4" (10.2cm) copper-spun magnetically shielded IMG woofer
CROSSOVER FREQUENCY	1730 Hz (Passive)
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-reflex via rear-firing port
INPUTS	Bluetooth® wireless technology • Phono/Line analog (with switch and ground screw terminal) • 3.5mm analog mini jack • USB digital • Optical digital
OUTPUTS	Single RCA line level output for connection to subwoofer
DIMENSIONS	11.3" (28.7 cm) H X 5.75" (14.6 cm) W X 7.9" (20.06 cm) D
WEIGHT	8.1 lbs (3.7 kg)
FINISH	Black
VOLTAGE	100V-240V 50/60Hz internal power supply with region specific power cords
INCLUDED ACCESSORIES	Remote control (with 2 x AAA batteries) • 4M speaker wire with soldered tips • 2M power cord (region specific) • 2M USB Type A to Type B cable • Rubber feet

SHIPPING QUANTITY: Pair
SHIPPING WEIGHT: 10.6 kg 23.4 lbs
PART NUMBER
1066255 (BLK/GNM EUA)

🚯 Bluetooth

NOTES:

SHIPPING QUANTIT	ry:	Pair
SHIPPING WEIGHT:		1.6 kg .4 lbs
PART		

1066253 (BLK/GNM EUA)

8 Bluetooth







0

KLIPSCH

W

4. 2 H &

KIDSCH HARINAGE WIRELESS

and Service

HERITAGE WIRELESS

HERITAGE WIRELESS

Incorporating luxury materials such as real wood veneer and tactile switches and knobs, the Klipsch Heritage Wireless series of powered audio systems blends the acoustics and classic design legacy of Paul W. Klipsch with the latest technologies available today.





- 1" Titanium-loaded Tweeters with Tractrix Horns
- 6.5" Woofers with a Ported Enclosure
- 1 x pair of RCA phono level inputs with switch for Phono/Line input versatility (Phono Pre-amp with ground screw terminal)
- Bluetooth® wireless technology
- Single RCA line level output for connection to sub.

THE SIXES POWERED MONITORS

MAX ACOUSTIC OUTPUT	106dB (1M stereo pair)			
HIGH FREQUENCY DRIVERS	1" (25.4mm) titanium tweeters on Tractrix® horns (each speaker)			
WOOFER	6.5" (165.1mm) long-throw woofer (each speaker)			
ENCLOSURE TYPE	Bass reflex			
SYSTEM POWER	100W x 2 continuous @<1% THD 200W x 2 short term peak power			
FREQUENCY RESPONSE	40Hz ~20kHz @ -3dB			
INPUTS	Bluetooth® wireless technology 1x 3.5mm miniplug (analog) 1 x Phono pre-amp / RCA Analog 1 x USB Type B 1 x Optical digital (RCA)			
OUTPUTS	Subwoofer output			
DIMENSIONS	8.625" (22cm) H x 16.75" (42.55cm) W x 11" (27.9cm) D			
FINISH	Walnut			
VOLTAGE	110/240 VAC			
WEIGHT	Right speaker: 17.74 lbs (8.05kg) Left speaker: 16.00 lbs (7.26kg)			
INCLUDED ACCESSORIES	4-conductor speaker cable (for R to L connection) 3.5mm aux cable USB Type B to USB Type A cable Optical (TOSLink) Cable Wireless Remote Control Power Cord			



1063288 (Walnut) (CE)



NOTES:



- Discrete left and right channels
- Multiple Input Options
- HDMI-ARC
- 192kHz/24-bit decoding
- Built-in dynamic bass equalization
- Free pair of beige grilles included

THE FIVES POWERED MONITORS

SYSTEM DESCRIPTION	Powered Monitor (pair)		
FREQUENCY RESPONSE	50Hz - 25kHz		
DYNAMIC BASS EXTENSION	46Hz @ 35% Volume		
MAX OUTPUT	109 dB (1M Stereo Pair)		
TOTAL SYSTEM POWER	160W Total System Power (320W Peak)		
HIGH FREQUENCY DRIVER	60W LF, 20W HF		
LOW FREQUENCY DRIVER	1" (2.5cm) Titanium LTS vented tweeter with Tractrix® horn		
ENCLOSURE MATERIAL	4.5" (11.43cm) high-excursion fiber-composite cone woofer		
ENCLOSURE TYPE	MDF with genuine wood veneer		
INPUTS	 HDMI-ARC with CEC Bluetooth® 5.0 aptX HD Phono/Line analog (with switch and ground screw terminal) 3.5mm analog mini jack USB digital Optical digital 		
OUTPUTS	Single RCA line level output for connection to subwoofer		
DIMENSIONS	12" (30.48 cm) H x 6.5" (16.51 cm) W x 9.25" (23.40 cm) D		
WEIGHT	Primary: 11.8 lbs (5.35kg) - Secondary: 10.7 lbs (4.85kg)		
FINISH	Walnut / Matte Black		
VOLTAGE	100V-240V 50/60Hz internal power supply with region specific power cords		
INCLUDED ACCESSORIES	Region-Specific power cord (2.0m) Remote control (with 2 x AAA batteries) 4-conductor speaker cable (4m) USB Type-8 to USB Type-A cable (1.5m) HDMI Cable (1.5m)		

SHIPPING QUANTITY: Pair SHIPPING WEIGHT: 134.29 kg 29.3 lbs

PART NUMBER

1068026 (Matte Black) (EUA) 1067563 (Walnut) (EUA) 1070315 (Fives McLaren / Matte Black) (EUA)





- Astounding, room-filling acoustics
- Bluetooth[®] wireless technology
- RCA analog / phono pre-amp input

THE THREE II	TABLETOP STEREO SYSTEM
MAX ACOUSTIC OUTPUT	106dB (0.5M near field)
HIGH FREQUENCY DRIVERS	2 x 2 1/4" (57.15mm) full range drivers
SUBWOOFER	5.25" (133.4mm) long-throw woofer 2 x 5.25" (133.4mm) dual opposed passive radiators
ENCLOSURE TYPE	Sealed
POWER	120W Peak
FREQUENCY RESPONSE	45Hz ~20kHz @ -3dB
INPUTS	Bluetooth® 3.5mm miniplug (analog) Phono pre-amp / RCA analog USB Type B
OUTPUTS	None
DIMENSIONS	3.7" (34.82cm) H x 7" (17.78cm) W x 8" (20.3cm) D
FINISH OPTIONS	Walnut, Matte Black
VOLTAGE	110/240 VAC
WEIGHT	10.32lbs (4.7kg)
INCLUDED ACCESSORIES	3.5mm aux cable USB Type B to USB Type A cable Wireless Remote Control Power Cord





NOTES:



- Incredible acoustic performance
- Bluetooth® Wireless Technology
- 3.5mm Analog Audio Input

THE ONE II TABLETOP STEREO SYSTEM

MAX ACOUSTIC OUTPUT	103dB	SHIPPING QUAN
HIGH FREQUENCY DRIVERS	2 1/4" (57.15mm) full range drivers	SHIPPING WE
SUBWOOFER	4.5" (114.3mm) woofer	
ENCLOSURE TYPE	sealed	P
POWER	60 Watts	1067552 (Ma
FREQUENCY RESPONSE	56Hz ~ 20kHz @ -3dB	1067555
INPUTS	<i>Bluetooth</i> ® 3.5mm miniplug (analog)	🛞 Bluet
OUTPUTS	None	NOTES:
DIMENSIONS	12.67" (32.2cm) H x 6.125" (15.56cm) W x 5.25" (13.3cm) D	
FINISH OPTIONS	Walnut, Matte Black	
VOLTAGE	110/240 VAC	
WEIGHT	8.5lbs (3.86kg)	

ANTITY: Single VEIGHT: 4.5 kg 10 lbs

PART NUMBER

Aatte Black EUA) 55 (Walnut EUA)

etooth

HERITAGE GROOVE PORTABLE SPEAKER



- 8-hour battery life
- 1 microphone for hands-free calling
- Bluetooth[®] Wireless Technology

DC INPUT	5V, 1A
AMPLIFIER OUTPUT	20W Peak
FREQUENCY RESPONSE	65Hz-22kHz +/- 3dB
ENCLOSURE TYPE	Bass reflex via dual opposing passive radiators
DRIVER	1 x 3" aluminum full-range high excursion
PASSIVE BASS RADIATOR	2 x side-firing
MAXIMUM ACOUSTIC OUTPUT	97dB at 0.5m
INPUTS	Bluetooth® , 3.5mm Analog In
BATTERY LIFE	8 hours
BATTERY TYPE	Rechargeable Lithium 7.4V 2 cell 2200mAh
ACCESSORIES	AC power adaptor, micro USB charging cable
FINISH	Walnut, Matte Black
DIMENSIONS	5" (12.7 cm) H x 6" (15.2 cm) W x 7.75" (19.7 cm) D
WEIGHT	Speaker: 2.2 lbs (.99kg) w/ cable and USB charger: 2.1 lbs (.95kg)





NOTES:



- Compact, High-Performance Desktop System
- Wireless Streaming from any Computer or Device
- No Receiver Necessary
- Best-In-Class Subwoofer

PROMEDIA HERITAGE 2.1 DESKTOP SYSTEM

SYSTEM POWER	220W Peak Power, Satellites: 35W / Channel, Subwoofer: 150W	
FREQUENCY RESPONSE	29Hz - 20kHz	
ENCLOSURE MATERIAL	MDF	
ENCLOSURE TYPE	Satellites: Sealed Box Subwoofer: Bass Reflex via Rear-Firing Tube Port	
HIGH FREQ. HORN (SATELLITES)	Tractrix Horn	
HIGH FREQ. DRIVER (SATELLITES)	1" Polymer Compression Driver	
LOW FREQ. DRIVER (SATELLITES)	4" Polyfiber Cone	
SUBWOOFER DRIVER	8" Long-Throw Polyfiber Cone	
INPUTS	Bluetooth Wireless Stereo Analog RCA USB-A	
MAXIMUM OUTPUT (IN ROOM)	110dB	
FINISHES	Black Ash, Walnut	
VOLTAGE	120V - 240V	
WEIGHT	Satellites: 1.5 lbs Subwoofer: 14 lbs	
DIMENSIONS (HXWXD)	Satellite (Single): 8" x 5.5" x 4.3" • 203mm x 140mm x 109mm Subwoofer: 12" x 10" x 15" • 305mm x 254mm x 381mm	

SHIPPING WEIGHT: 12.5 kg 27.56 lbs

SHIPPING QUANTITY: System

PART NUMBER

1070161 (Matte Black) EUA 1070158 (Walnut) EUA

8 Bluetooth

NOTES:

Klipsch Headphones

NOTES MOTAAN

HEADPHONES

T5 II TRUE WIRELESS SERIES

The Klipsch True Wireless earphones are the ultimate combination of comfort, design, efficiency, and legendary acoustic clarity. Outfitted with the latest Bluetooth® technology, amazing battery life and charging cases, Klipsch True Wireless earphones provide incredible comfort, clarity and freedom for you to enjoy your music all day with no wires.







- Water-resistant (IPX4), patented oval ear tips
- Al and head gesture user interface
- 8-hour battery, 24-hour charging case (6-18H w/ ANC)
- Signal boost antenna
- Wireless charging pad included
- Digital assistant ready

TRUE WIRELESS SMART E	ARPHONES WITH ANC AND WIRELESS CHARGING CASE		
STYLE	In-Ear Monitor		
DRIVER DESIGN	Dynamic Moving Coil Micro Speaker		
DRIVER DIAMETER	5.8 mm		
MIC/REMOTE	Six-mic Beamforming		
FREQUENCY RESPONSE	10Hz-19kHz		
NOISE ISOLATION	-22dB		
INPUT CONNECTIONS	Bluetooth		
BATTERY (EARPIECES)	50 mAh		
BATTERY (CHARGING CASE)	360 mAh		
BLUETOOTH® SPECIFICATIONS	Version: Bluetooth 5.0 Profiles: A2DP 1.3, AVRCP 1.6, HSP 1.2, HFP 1.7 A2DP Codecs: SBC, AAC® Range: Up to 10m (33ft.) Input Rating: SV DC, 1.0A Battery Status: IOS & Android Battery Status Monitor		
WEIGHT	Buds: 10.72g (.024 lbs) Case: 42.9g (.095 lbs) Buds and Case: 53.62g (.118 lbs)		
COLORS	Black		

T5 II TRUE WIRELESS ANC MCLAREN EDITION



SHIPPING QUANTITY: Each

NOTES:



- Water-resistant (IPX4), patented oval ear tips AI and head gesture user interface
- Al and head gesture user interface
- 8-hour battery, 24-hour charging case (6-18H w/ ANC)
- Transparency mode
- Signal boost antenna
- Digital assistant ready

T5 II TRUE WIRELESS ANC

TRUE WIRELESS SMART EARPHONES WITH ANC AND WIRELESS CHARGING CASE

STYLE	In-Ear Monitor	
DRIVER DESIGN	Dynamic Moving Coil Micro Speaker	
DRIVER DIAMETER	5.8 mm	
MIC/REMOTE	Six-mic Beamforming	
FREQUENCY RESPONSE	10Hz-19kHz	
NOISE ISOLATION	-22dB	
INPUT CONNECTIONS	Bluetooth	
BATTERY (EARPIECES)	50 mAh	
BATTERY (CHARGING CASE)	360 mAh	
BLUETOOTH® SPECIFICATIONS	Version: Bluetooth 5.0 Profiles: A2DP 1.3, AVRCP 1.6, HSP 1.2, HFP 1.7 A2DP Codecs: SBC, AAC® Range: Up to 10m (33ft.) Input Rating: SV DC, 1.0A Battery Status: iOS & Android Battery Status Monitor	
WEIGHT	Buds: 10.72g (.024 lbs) Case: 90.2g (.20 lbs) Buds and Case: 100.92g (.222 lbs)	
COLORS	Gunmetal, Silver	

SHIPPING QUANTITY: Each SHIPPING WEIGHT: TBD PART NUMBER 1069030 (Gunmetal) 1069031 (Silver)



NOTES:



T5 II TRUE WIRELESS SPORT MCLAREN EDITION

TRUE WIRELESS EARPHONES WITH WIRELESS CHARGING CASE AND CHARGING PAD

STYLE	In-Ear Monitor	SHIPPING QUANTITY: Each
DRIVER DESIGN	Dynamic Moving Coil Micro Speaker	SHIPPING WEIGHT: 0.40 kg
DRIVER DIAMETER	5.0 mm	0.88 lbs
MIC/REMOTE	cVc 8.0 Quad-mic	PART NUMBER
FREQUENCY RESPONSE	10Hz-19kHz	1069154 (Black)
NOISE ISOLATION	-22dB	_
INPUT CONNECTIONS	Bluetooth	_
BATTERY (EARPIECES)	50 mAh	Klipsch Commect
BATTERY (CHARGING CASE)	360 mAh	🛞 Bluetooth
BLUETOOTH® SPECIFICATIONS	Version: Bluetooth 5.0 Profiles: A2DP 1.3, AVRCP 1.6, HSP 1.2, HFP 1.7 A2DP Codecs: SBC, AAC®, aptX® Range: Up to 10m (33ft.) Input Rating: SV DC, 1.0A Battery Status: iOS & Android Battery Status Monitor	Qualcomm' aptX'
WEIGHT	Buds: 12.3g (.027 lbs) Case: 82.4g (.18 lbs) Buds and Case: 94.7g (.21 lbs)	
COLORS	Gunmetal, Silver	_

- Patented oval ear tips
- IP67 rated earphones and case with moisture removal system
- Wireless charging pad included
- 8-hour battery, 24-hour charging case
- Signal boost antenna
- Transparency mode
- Digital assistant ready



- Patented oval ear tips
- IP67 rated earphones and case with moisture . removal system
- 8-hour battery, 24-hour charging case
- Signal boost antenna
- Transparency mode
- Digital assistant ready

T5 II TRUE WIRELESS SPORT

IRUE WIRELESS EARPHO	NES WITH CHARGING CASE	
STYLE	In-Ear Monitor	SHIPPING QUANTITY: Each
DRIVER DESIGN	Dynamic Moving Coil Micro Speaker	SHIPPING WEIGHT: 0.35 kg
DRIVER DIAMETER	5.0 mm	0.77 lbs
MIC/REMOTE	cVc 8.0 Quad-mic	PART NUMBER
FREQUENCY RESPONSE	10Hz-19kHz	1069027 (Black)
NOISE ISOLATION	-22dB	1069028 (White)
INPUT CONNECTIONS	Bluetooth	
BATTERY (EARPIECES)	50 mAh	Klipsich CONNECT
BATTERY (CHARGING CASE)	360 mAh	🛞 Bluetooth
BLUETOOTH® SPECIFICATIONS	Version: Bluetooth 5.0 Profiles: A2DP 1.3, AVRCP 1.6, HSP 1.2, HFP 1.7 A2DP Codecs: SBC, AAC [®] , aptX [®] Range: Up to 10m (33ft.) Input Rating: 5V DC, 1.0A	Qualcomm [*] aptX [*]
	Battery Status: iOS & Android Battery Status Monitor	NOTES:
WEIGHT	Buds: 12.3g (.027 lbs) Case: 82g (.18 lbs) Buds and Case: 94.3g (.21 lbs)	
COLORS	Black, White	

T5 II TRUE WIRELESS TRUE WIRELESS EARPHONES WITH CHARGING CASE



- IP67 rated, patented oval ear tips
- 8-hour battery, 24-hour charging case
- Signal boost antenna
- Transparency mode
- Digital assistant ready

IRUE WIRELESS EARPHU	NES WITH CHARGING CASE	
STYLE	In-Ear Monitor	SHIPPING QUANTITY: Each
DRIVER DESIGN	Dynamic Moving Coil Micro Speaker	SHIPPING WEIGHT: 0.30 kg
DRIVER DIAMETER	5.0 mm	0.67 lbs
MIC/REMOTE	cVc 8.0 Quad-mic	PART NUMBER
FREQUENCY RESPONSE	10Hz-19kHz	1069025 (Gunmetal)
NOISE ISOLATION	-22dB	1069026 (Silver)
INPUT CONNECTIONS	Bluetooth	
BATTERY (EARPIECES)	50 mAh	Klipsch connect
BATTERY (CHARGING CASE)	360 mAh	🚯 Bluetooth
BLUETOOTH [®] SPECIFICATIONS	Version: Bluetooth 5.0 Profiles: A2DP 1.3, AVRCP 1.6, HSP 1.2, HFP 1.7 A2DP Codecs: SBC, AAC®, aptX® Range: Up to 10m (33ft.) Input Rating: 5V DC, 1.0A Battery Status: iOS & Android Battery Status Monitor	Qualcomm [*] aptX [*]
WEIGHT	Buds: 10.6g (.023 lbs) Case: 89.3g (.19 lbs) Buds and Case: 100g (.22 lbs)	
COLORS	Gunmetal, Silver	

HEADPHONES

T5 SERIES

The T5 series offers wireless and wired options with unparalleled comfort, performance and the legendary Klipsch sound. Featuring sweat/water resistance, braided cords, crystal clear mics and patented ear tips, the T5 line provides the perfect solution to your earphone needs.





T5M WIRED IN-EAR EARPHONES

STYLE	In-Ear Monitor	SHIPPING QUANTITY: Each
DRIVER DESIGN	Dynamic Moving Coil Micro Speaker	SHIPPING WEIGHT: 0.14 kg
DRIVER DIAMETER	5.0 mm	0.31 lbs
MIC/REMOTE	Single Button	PART NUMBER
FREQUENCY RESPONSE	10Hz-19kHz	1067635 (Black)
SENSITIVITY (1MW)	98dB	
IMPEDANCE (1KHZ)	16 ohms	
NOISE ISOLATION	-22dB	NOTES:
INPUT CONNECTIONS	3.5 mm	
WEIGHT	11.6g	
COLORS	Black	
DIMENSIONS (PACKAGING)	6.7" (17.02cm) H x 3.4" (8.64cm) W x 1.5" (3.81cm) D	

- Sweat-resistant, patented oval ear tips • Works with any device
- Best-in-class, static-free microphone

INPUT CONN



McLAREN

Klipsch and McLaren have forged a partnership steeped in technology and built for performance. Our goal is to design sleek, smart, premium headphones and portable speakers built to withstand the loudest, harshest environments on the planet.





- Patented oval ear tips
- IP67 rated earphones and case with moisture removal system
- Wireless charging pad included •
- 8-hour battery, 24-hour charging case
- Signal boost antenna •
- Transparency mode •
- Digital assistant ready

STYLE	In-Ear Monitor	
DRIVER DESIGN	Dynamic Moving Coil Micro Speaker	
DRIVER DIAMETER	5.0 mm	
MIC/REMOTE	cVc 8.0 Quad-mic	
FREQUENCY RESPONSE	10Hz-19kHz	
NOISE ISOLATION	-22dB	
INPUT CONNECTIONS	Bluetooth	
BATTERY (EARPIECES)	50 mAh	
BATTERY (CHARGING CASE)	360 mAh	
BLUETOOTH® SPECIFICATIONS	Version: Bluetooth 5.0 Profiles: A2DP 1.3, AVRCP 1.6, HSP 1.2, HFP 1.7 A2DP Codecs: SBC, AAC®, aptX [®] Range: Up to 10m (33ft.) Input Rating: 5V DC, 1.0A Battery Status: iOS & Android Battery Status Monitor	
WEIGHT	Buds: 10.6g (.023 lbs) Case: 89.3g (.19 lbs) Buds and Case: 100g (.22 lbs)	
COLORS	Gunmetal, Silver	

T5 II TRUE WIRELESS SPORT MCLAREN EDITION

TRUE WIRELESS EARPHONES WITH WIRELESS CHARGING CASE AND CHARGING PAD



SHIPPING QUANTITY: Each SHIPPING WEIGHT: 0.40 kg

NOTES:



NEW

- Water-resistant (IPX4), patented oval ear tips
- Al and head gesture user interface
- 8-hour battery, 24-hour charging case (6-18H w/ ANC)
- Signal boost antenna
- Wireless charging pad included
- Digital assistant ready

T5 II TRUE WIRELESS ANC MCLAREN EDITION

TRUE WIRELESS SMART EARPHONES WITH ANC AND WIRELESS CHARGING CASE

INUE WIRELESS SMARTI	LARPHONES WITH AND AND WIRELESS CHARGING CASE	
STYLE	In-Ear Monitor	SHIPPING QUANTITY: Each
DRIVER DESIGN	Dynamic Moving Coil Micro Speaker	SHIPPING WEIGHT: TBD
DRIVER DIAMETER	5.8 mm	PART NUMBER
MIC/REMOTE	Six-mic Beamforming	1069155 (Black)
FREQUENCY RESPONSE	10Hz-19kHz	
NOISE ISOLATION	-22dB	_
INPUT CONNECTIONS	Bluetooth	Klipsch connect
BATTERY (EARPIECES)	50 mAh	💦 😵 Bluetooth
BATTERY (CHARGING CASE)	360 mAh	
BLUETOOTH® SPECIFICATIONS	Version: Bluetooth 5.0 Profiles: A2DP 1.3, AVRCP 1.6, HSP 1.2, HFP 1.7 A2DP Codecs: SBC, AAC® Range: Up to 10m (33ft.) Input Rating: SV DC, 1.0A Battery Status: iOS & Android Battery Status Monitor	NOTES:
WEIGHT	Buds: 5.5g (.012 lbs) Case: 76.9g (.17 lbs) Buds and Case: 82.4g (.18 lbs)	
COLORS	Black	



- Discrete left and right channels
- Multiple Input Options
- HDMI-ARC
- 192kHz/24-bit decoding
- Built-in dynamic bass equalization

THE FIVES POWERED MONITORS

SYSTEM DESCRIPTION	Powered Monitor (pair)	SHIPPING QUANTITY: Pair
FREQUENCY RESPONSE	50Hz - 25kHz	SHIPPING WEIGHT: 134.29 kg
DYNAMIC BASS EXTENSION	46Hz @ 35% Volume	29.3 lbs
MAX OUTPUT	109 dB (1M Stereo Pair)	PART NUMBER
TOTAL SYSTEM POWER	160W Total System Power (320W Peak)	1068026 (Matte Black) (EUA)
HIGH FREQUENCY DRIVER	60W LF, 20W HF	1067563 (Walnut) (EUA)
LOW FREQUENCY DRIVER	1" (2.5cm) Titanium LTS vented tweeter with Tractrix® horn	1070315 (Fives McLaren / Matte
ENCLOSURE MATERIAL	4.5" (11.43cm) high-excursion fiber-composite cone woofer	— Black) (EUA)
ENCLOSURE TYPE	MDF with genuine wood veneer	_
INPUTS	 HDMI-ARC with CEC Bluetooth* 5.0 aptX HD Phono/Line analog (with switch and ground screw terminal) 3.5mm analog mini jack USB digital Optical digital 	Runch Bluetooth
OUTPUTS	Single RCA line level output for connection to subwoofer	
DIMENSIONS	12" (30.48 cm) H x 6.5" (16.51 cm) W x 9.25" (23.40 cm) D	
WEIGHT	Primary: 11.8 lbs (5.35kg) - Secondary: 10.7 lbs (4.85kg)	NOTES:
FINISH	Walnut / Matte Black	_
VOLTAGE	100V-240V 50/60Hz internal power supply with region specific power cords	_
	Region-Specific power cord (2.0m) Remote control (with 2 x AAA batteries)	_

INCLUDED ACCESSORIES

- 4-conductor speaker cable (4m)
 USB Type-B to USB Type-A cable (1.5m)
 HDMI Cable (1.5m)



WE NEVER, ever STOP INNOVATING

For over 70 years Klipsch has designed and engineered its products in-house with some of the most talented, skilled and passionate people in the industry - starting with our founder, Paul W. Klipsch (PWK), in a tin shed in Hope, Arkansas. Today, our advanced acoustic research and development continues at our state-of-the-art facility in Indianapolis, Indiana. The world-class Klipsch Design and Technology Center is home to some of the most brilliant minds in consumer electronics and some of the most legendary products the industry has ever heard. We continue to innovate, honoring the principals and ideals of PWK, reaching ever-farther towards that perfect sound.



VISIT KLIPSCH.COM FOR ALL SORTS OF badassery

FOLLOW US, WE HAVE A BLAST



© 2020 Klipsch Group, Inc., a wholly-owned subsidiary of Voxx International Corp. Klipsch and Tractrix are registered trademarks of Klipsch Group, Inc. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Klipsch Group, Inc. is under license.



Visit KlipschMuseum.org for an amazing journey through the dawn of hi-fi. Help preserve audio's legendary history and consider donating today. Your support helps continue the museum's mission of focus on science education, artifact preservation and encouraging the spirit of invention. Klipsch Museum of Audio History is an independent 501(c)(3) entity.

POWER DETAIL EMOTION







3502 WOODVIEW TRACE, INDIANAPOLIS, IN, USA KLIPSCH.COM

