



# PA-1480

Order No.: 0171110

## PRODUCTINFOS

### Mono PA power amplifier

- 1 x 480 W
- Switchable 400 Hz high-pass filter 6 dB/oct.
- Temperature-controlled fan, continuously adjustable
- LED indication for clip, protect, overtemperature and output level
- Feed-through output (link)
- Mains operation or 24 V emergency power operation

### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG  
Zum Falsch 36  
28307 Bremen  
Germany  
info@monacor.com

### Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

During operation, there may be a hazard of contact with a dangerous voltage of up to 100 V at the speaker terminals. Always switch off the amplifier before making or changing any connections.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar

accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated inside the unit must be dissipated by air circulation; never cover the air vents of the housing.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

## TECHNICAL SPECIFICATIONS

### PA-1480

Peak output power	480 W
Power rating	480 W
Power rating at 8 Ω	480 W
Power rating at 100 V	480 W
Power rating at 70 V	480 W
Output impedance	62 V/8 Ω, 70 V/10 Ω, 100 V/21 Ω
Channels	1
Inputs	1.2 V, bal.
Frequency range	35-20,000 Hz
S/N ratio	> 100 dB(A)
THD	< 1%
Power supply	~ 230 V/50 Hz/1,400 VA, DC 24 V/40 A
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,400 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 40 A
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	88 mm
Depth	374 mm
Rack units, RU	2
Weight	15.2 kg
Connections	XLR/screw contacts (inputs) screw contacts (speakers)
Packaging dimensions (W x H x L)	0.54 x 0.18 x 0.48 m

**PA-1480**

Gross weight 17.24 kg

Net weight 15.22 kg

**PA-1480**

EAN code 4007754159653

Net weight 15.22 kg