



STA-200D

Order No.: 0255070

PRODUCTINFOS

Stereo class D PA amplifier, 250 W

- 5 switchable line inputs
- Silent operation due to fanless cooling concept
- High power reserves due to generously dimensioned toroidal core transformer
- High-efficiency power amplifiers
- 3.5 mm stereo jack connection with switchable sensitivity on the front panel
- 4 x RCA input
- 2 x SPEAKER output
- 4 x terminal strip output
- 2 level controls
- Protected against short circuit, overvoltage and overtemperature
- LEDs for indicating power, overload (clip), protect and overheating
- Super slimline and robust design, 1 RS

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Zum Falsch 36
28307 Bremen
Germany
info@monacor.com

Warning and Safety Instructions

The device is supplied with dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Risk of electric shock!

Do not use this device and disconnect it immediately from the power supply if the device or the power

supply cable is visibly damaged, if a defect might have occurred after the device was dropped or suffered a similar accident, if malfunctions occur. Any repairs must be carried out by specialists.

The product is suitable for indoor use only. Protect it against dripping water, splash water and high air humidity (admissible ambient temperature range is 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated in the device must be dissipated by air circulation. Never cover the air vents of the housing.

If the device is to be put out of operation definitely, dispose of the product in accordance with local regulations.

TECHNICAL SPECIFICATIONS

STA-200D

Peak output power	300 W
Power rating	250 W
Power rating at 4 Ω	2 x 125 W
Power rating at 8 Ω	2 x 75 W
Channels	2
Inputs	1 V/23 kΩ (RCA), 90 mV-1 V (jack)
Frequency range	20-20,000 Hz
S/N ratio	> 100 dB(A)
Crosstalk attenuation	> 56 dB
THD	< 0.05%
Power supply	~ 230 V/50 Hz/350 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	350 VA
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	44 mm
Depth	268 mm
Rack units, RU	1
Weight	5 kg
Connections	1 x 3.5 mm stereo jack 4 x RCA L/R 1 x SPEAKER L/R 1 x spring-load. speaker term. L/R
Packaging dimensions (W x H x L)	0.34 x 0.1 x 0.46 m

STA-200D

Gross weight 5.9 kg

Net weight 5.15 kg

STA-200D

EAN code 4007754236590

Net weight 5.15 kg