



DRM-44

Order No.: 1001514

PRODUCTINFOS

Bi-directional analogue/Dante® bridge

- 4 balanced analogue inputs and 4 balanced analogue outputs via network (Dante®/AES67) for fixed installations
- Built-in DSP audio processing on all channels: parametric EQs, compressors, delays, etc.
- 8x8 audio matrix for flexible routing and premixing between inputs and outputs
- Web server with graphical interface for easy configuration and control via network devices
- Very high audio quality: signal-to-noise ratio > 120 dB, distortion factor < 0.003 %
- GPI/GPO connections (inputs/outputs) for controlling external devices or recording control inputs (e.g. buttons, sensors, alarm systems)
- Flexible power supply: via included power supply unit (DC24 V) or via PoE (Power over Ethernet)
- 241 mm housing (1½ 19") for rack mounting (supplied with rack bracket)

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).

Do not operate the appliance if there is visible damage to the appliance, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialised workshop for repair.

If the appliance is to be taken out of service permanently, hand it over to a local recycling centre for environmentally friendly disposal.

TECHNICAL SPECIFICATIONS

DRM-44

Description	Bi-directional analogue/Dante® bridge
Colour	Black
Power supply	PoE or enclosed power supply unit
Admiss. ambient temp.	0-40 °C
Dimensions	
Weight	1.4 kg
Connections	clip and screw terminals, 2 x RJ45
Other features	Signal-to-noise ratio > 120 dB, Distortion factor < 0.003 %
Packing unit	1
Packaging dimensions (W x H x L)	0.345 x 0.26 x 0.145 m
Gross weight	2.62 kg
Net weight	1.23 kg

DRM-44

EAN code	4007754430455
Net weight	1.23 kg