



EPS110/RS485

Order No.: 1000871

PRODUCTINFOS

MP3 player,

event-driven.

- For mounting onto DIN rails according to DIN EN 60715, 2 HP
- For SDHC/SD/MMC cards up to 32 GB (FAT32), not included in the scope of delivery
- Extensive playback functions
- 7 binary inputs
- In/Out string triggers
- RS-485 interface for communication
- Decentral extensions
- Connection for EIB push-button sensor
- Balanced stereo line output, can also be used as a headphone output
- Delay function up to 60 seconds
- Free configuration software
- Firmware update possible

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG

Zum Falsch 36
28307 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: -25 °C up to +50 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: -35 °C up to + 55 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

EPS110/RS485

Description	MP3 player
Media	MP3, WAV
Frequency range	18-20,000 Hz
THD	0.001%
Output, analogue	2 V/600 Ω
Operating voltage (possible alternative)	7-24 V
Power supply (possible alternative)	60 mA (7 V) 25 mA (24 V)
Admiss. ambient temp.	-35-+55 °C
Dimensions	74 x 113 x 35 mm
Weight	96 g
Connections	7 binary inputs
Packaging dimensions (W x H x L)	0.037 x 0.095 x 0.075 m
Gross weight	0.1155 kg

EPS110/RS485

EAN code	4007754419740
Net weight	0.096 kg