



# SKYROCK



Order No.: 1000873

## **PRODUCTINFOS**

#### Portable PA speaker system,

with integrated Bluetooth receiver.

- Operation via mains connection or optional rechargeable lead gel battery 12 V/18 Ah (operating time at moderate volume: up to 40 hours, operating time at full volume: up to 10 hours), with LED for indicating charging status
- Bluetooth receiver (version 5.0) for wireless connection of portable audio players
- Bluetooth TWS feature (True Wireless Stereo) for pairing 2 x PA speaker system SKYROCK to form a stereo speaker system
- High-performance class D version 120 W
- 2-way speaker system with 38 cm (15") bass speaker and 25.4 mm (1") horn tweeter
- 1 adjustable microphone input via comb. jack (XLR/6.3 mm)
- 1 adjustable aux input (3.5 mm jack)
- Adjustable reverb via microphone input
- USB charging port for portable audio players

Supplied w/o rechargeable lead gel battery. Matching rechargeable battery WP18-12SHR is available at option.



#### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG Konsul-Smidt-Str. 68 28217 Bremen Germany info@monacor.com

#### Warning and Safety Instructions

The device is supplied with dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Risk of electric shock!

Do not use this device and disconnect it immediately from the power supply if the device or the power supply cable is visibly damaged, if a defect might have occurred after the device was dropped or suffered a similar accident, if malfunctions occur. Any repairs must be carried out by specialists.

The product is suitable for indoor use only. Protect it against dripping water, splash water and high air humidity (admissible ambient temperature range is 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated in the device must be dissipated by air circulation. Never cover the air vents of the housing.

If the device is to be put out of operation definitely, dispose of the product in accordance with local regulations.

Never put (rechargeable) batteries in the household waste. Always dispose of the batteries in accordance with local regulations.

# **TECHNICAL SPECIFICATIONS**

#### SKYROCK

Rated power ( $P_{RMS}$ )	55 W (bass) 21 W (tweeter)
Peak output power	130 W
Frequency range	38-20,000 Hz
Inputs	12 mV/1 kΩ (mic), 70 mV/3 kΩ (aux)
Max. SPL	129 dB
Power supply	<sup>~</sup> 100-240 V/50-60 Hz/120 VA, optional rech. batt. 12 V/18 Ah (WP18-12SHR)
Admiss. ambient temp.	0-40 °C
Dimensions	470 x 815 x 365 mm
Weight	23.4 kg



### SKYROCK

Conn	ections
001111	cccions

## SKYROCK

EAN code

Net weight

1 x XLR/6.3 mm jack (mic), 1 x 3.5 mm jack (aux) 1 x USB Type-A

4007754418514 23.45 kg