optomaeurope.com

UZ36X

UZ36X 4K UHD Home Projector



- **4K UHD dual-laser technology - Immerse yourself in stunning visuals with 3600 ISO lumens and 95% Rec.709 colour accuracy**
- **PureEngine™ - Enjoy smooth motion, sharp details, and customised picture settings**
- **PureMotion™ MEMC technology - Keeps fast-moving action smooth and sharp, reducing motion blur for more fluid, realistic visuals.**
- **Quick and easy setup - Auto vertical keystone correction and 1.3x zoom**



Bring bright, cinematic entertainment into your home with the Photon Beam UZ36X 4K UHD laser projector. Powered by PureEngine™ technology for stunning visuals and unmatched clarity and colour accuracy.

Enjoy smooth motion, sharp details and customised picture settings with PureEngine™ and PureMotion™ MEMC. Watch films as the director intended with Filmmaker mode. Plus, with flexible installation options and long-lasting performance, the UZ36X is the perfect choice for creating the big screen experience at home.

Specifications

EAN: 5055387600416, Colour: Black



Display/image	
Display technology	DLP®
Resolution	UHD (3840x2160)
ISO 21118 brightness	3,600
Contrast ratio	1,500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Keystone correction - horizontal	30°
Keystone correction - vertical	30°
Has vertical auto keystone correction	Yes
Horizontal scan rate	15 ~ 255Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	80%
Screen size	0.71m ~ 7.62m (28" ~ 300") diagonal
Lamp info	
Light source type	DuraCore Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.21:1 ~ 1.59:1
Projection distance (m)	1m - 8m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	12.81 ~ 16.74
Native offset	105%
Connectivity	
Connections	**Inputs** 2 x HDMI 2.0 **Outputs** 1 x USB-A power 1.5A, 1 x Audio 3.5mm, 1 x 12V trigger **Control** 1 x RS232
General	
Noise level (min)	28dB
Noise level (max)	33dB
3D compatibility	Yes
3D	Full 3D
Security	Security bar, Kensington Lock
IP rating	IP6X (Optical Engine only)
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	Operating Altitude: 0~2,500 ft. for 0°C~40°C, 2,500~5,000 ft. for 0°C~35°C, 5,000~10,000 ft. for 0°C~30°C, Non-Operating < 40,000 ft.
Remote control	Yes
Speaker count	1
Watts per speaker	15W
In the box	Power adaptor Remote control Basic user manual 2x AAA Battery
Power	
Power supply	VAC 100-240V (50/60Hz)
Power consumption (standby)	0.5W
Power consumption (min)	83W
Power consumption (max)	150W
Weight and dimensions	
Dimensions (W x D x H) mm	238 x 215 x 130
Gross weight	5 kg
Net weight	3.4 kg

Copyright © 2026, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners.Errors and omissions excepted, all specifications are subject to change without notice.All images are for representation purposes only and may be simulated. 30092026025255