

## JENTECH SKYFLEX 2X2.5/H FRHF

Twisted Loudspeaker cable - halogen free & flame retardant

Gauge: 2x2.5mm<sup>2</sup> / AWG 13

Rev.date: 2022-08-30

Customs tariff no: 8544499390

Country of origin: Sweden

- Excellent flame-retardancy
- Halogen-free
- Double insulated, approved for 100V systems
- Low friction jacket, perfect for installation in conduit pipes



### Skyflex 2x2.5/H FRHF - - Halogen free & flame retardant

Twin core and multi-pair Install Grade loudspeaker cables. This range of Low Smoke Zero Halogen (LSZH) speaker cable is perfect for installations in public buildings and other areas where LSZH materials are specified such as new-build housing and marine installations. Available in a variety of core sizes and from single pair to four pair options. The special FRHF PE jacket adds both ruggedness and flexibility. Approved for 100V systems.

SUPRA cables is considered as a trustworthy and responsible partner for installations in public and official premises. We meet the latest regulation of flame retardancy and toxic emissions.

Standard CPS; Construction Products Regulation; EN 50399:2011 and EN 60322-1-2:2004/A1:2015/A11:2016. CE marking; EN 50399 and EN60322

Fire retardancy performance:

Fire behavior: DCA, Smoke protection: s1, Flaming droplets: d1 Reaction to fire classification: Dca-s1, d1 Report 0402-CPR-7P04047-1

### CONSTRUCTION

Conductor (x2): OFC Copper wire 204x0.127 mm  
Diameter: 2.3 mm  
Cross section Area: 2x2.5mm<sup>2</sup> / AWG 13  
Insulation: Red + & Black -  
Insulation thickness: 0.7 mm  
Jacket: PE ECCOH 5943 FRHF, round  
Jacket thickness: 1.5 mm  
Diameter: 7,5 mm  
Colour: Black (other colours upon order)  
Marking: JENTECH SKYFLEX 2x2.5/H + Made in Sweden + Meter mark  
Weight: 92 kg/km  
Packing: Bobbin 100m & 400m (other lengths upon order)



**FLAME  
RETARDANT**



**Dca-s1,d1**  
0402-CPR-7P04047-1  
EN50399:2011 &  
EN60322-1-2:2004/A1  
:2015/A11:2016  
[www.supracables.se](http://www.supracables.se)

### ELECTRICAL SPECIFICATION

Resistance: 6.8 ohm/km  
Inductance: 0.45 uH/m  
Rated voltage: 100V



PRODUCT	Qty	Part.no	EAN-13	E-no
SKYFLEX 2X2.5 FRHF BLACK B400	400M	2000000758	7330060207921	6222267
SKYFLEX 2X2.5 FRHF BLACK B100	100M	2000000766	7330060207914	6222266