

MPN: VLSPSUB100

Active powered Subwoofer 8" 50W + 2x25W 2.1

Vivolink Active Subwoofer is a perfect match to all Vivolink speakers. It is designed to be mounted over ceiling or under furniture

Ideal for meeting rooms, hotels and auditoriums.

It have line input and loop out for active satellite speakers. Subwoofer can also be used together with passive satellite speakers using the internal power amplifier for satellite speakers on 2 x 25W



- For rooms up to 200m²

- Power effect for subwoofer: 50 Watts

- Power effect for passive ceiling speakers:

(VLSPMTC60WT) 2x25Watts

- Inputs: 100V, Balanced in and RCA line in

- Outputs: RCA line out and Speaker out 2x 25W

- Line out for active speakers (VLSP60/65/61/70)

- Frequency range: 80Hz-20kHz

- Impedance: 8 Ohm

- 2 x 30 Watt active speakers
- Automatic ECO mode after 90 seconds (less than 0,5 Watt)
- Audio inputs: 2xRCA + Stereo 3,5 mm
- Switchable stereo / mono output
- One pair of speakers (one active + one passive)
- 140cm 230V Powercord

Specifikationer

Amplifier	Amplifier	Built-in
	Amplifier class	D
	Amplifier output power	110 Watt
	Amplifier output power (tweeter)	30 Watt
	Amplifier output power (woofer)	50 Watt
	Number of amplifier channels	3 kanály/kanálů
Audio	Crossover frequency	200 Hz
	Frequency range	40 - 20000 Hz
	Impedance	4 ohm
	RMS rated power	110 Watt
	Speakers RMS power	60 Watt

Audio	Subwoofer RMS power	50 Watt
Loudspeakers	Audio output channels	2.1 kanály/kanálů
	Number of drivers	3
	Speaker placement	Ceiling-mountable, Wall-mountable
	Subwoofer RMS power	50 Watt
	Woofers	Yes
	Woofers diameter (imperial)	8 "
	Other features	Accessories included
Adaptor plug		EU
Audio (L/R) in		1
Case colour		Black
Front speaker frequency range		80 - 20000 Hz
Front speaker impedance		4 ohm
Housing colour		Black
Manual		Yes
Speakers weight		6,36 g
Package dimensions		Depth (package,cm)
	Gross Weight (Package, kg)	6,75 kg
	Height (package,cm)	26,5 cm
	Width (package,cm)	44 cm
Packaging content	Cables included	AC
	Mounting brackets included	Yes
Performance	Certification	CE
	Housing material	Plastic
	Magnetically shielded	Yes
	On/off switch	Yes
	Product colour	Black
	Volume control	Rotary
Ports & interfaces	3.5 mm (1/8-inch) in	Yes
	6.35 mm (1/4-inch) input	1
	Audio RCA inputs	1
	Connectivity technology	Wired
Power	AC input voltage	230 - 240 V
	Current	1 A
	Power consumption (standby)	0,5 Watt
	Power consumption (typical)	75 Watt
	Power source type	AC
Product dimensions	Net Weight (Product, kg)	6,2600000000000001 kg
	Product Depth	16,2 cm
	Product Height	24 cm

Product dimensions	Product Width	17,8 cm
Technical details	Warranty period	3 rok/roky
Vendor information	Brand Name	Vivolink
	Warranty	3 År

Andre billeder



Anbefalet tilbehør



**Vivolink Active Speaker Set, 2x30W, 5,25",
White**
MPN: VLSP60AW



Vivolink 2-way 70w frameless ceiling
MPN: VLSPMTC60WT



**Vivolink Active Speaker Set, 2x30W, 5,25",
White**
MPN: VLSP65AW



**Vivolink Active Speaker Set, 2x30W, 5,25",
Black**
MPN: VLSP65AB



**Vivolink Vivolink Studio 70 Active
Speaker**
MPN: VLSP70