

MPN: VLSP65AB

Active Speaker Set, 2x30W, 5,25", Black

Professional stereo speakers in a rugged and durable design for meetingrooms, conferencerooms and classrooms.

Professional Speakers with Powersaving stand-by function.

The VLSP65AW is a step-up model with ballanced inputs and powerfull stereo speakersystem suitable for meeting- and conferencerooms, classrooms and more. Despite the compact design, the VLSP65AW deliver excellent sound through use of the integrated 2-way speaker units.

The VLSP65AW is equipped with a powerfull basswoofer and a combined midrange and tweeter unit which contributes to powerfull and great sound.



The speaker mounts are included and can be used in horizontal and vertical position. The system includes 10 meters speaker cable for use between the active and the passive unit.

- 2 x 30 Watt active speakers
- Automatic ECO mode after 90 seconds (0,5 Watt)
- Audio inputs: 2xRCA + Stereo 3,5 mm
- Switchable stereo / mono output
- One pair of speakers (one active + one passive)
- 140cm 230V Powercord

Specifikationer

Audio	Frequency range	45 - 20000 Hz
	Impedance	4 ohm
	Peak Music Power Output (PMPO)	300 Watt
	RMS rated power	60 Watt
	Sensitivity	88 dB
	Speakers RMS power	30 Watt
Front speakers	Front speaker frequency range	45 - 20000 Hz
	Front speaker impedance	4 ohm
	Front speaker sensitivity	88 dB
	Front speaker tweeter diameter	1 "
	Front speaker type	2-way
	Front speaker woofer diameter (imperial)	5,25 "
	Front speakers RMS power	30 Watt
Loudspeakers	Audio output channels	2.0 kanály/kanálů
	Number of drivers	2
	Speaker type	2-way
	Tweeter	Yes
	Tweeter diameter (imperial)	1 "
	Woofer	Yes
	Woofer diameter (imperial)	5,25 "

Other features	Audio RCA inputs	1
	Front speaker frequency range	45 - 20000 Hz
	Front speaker impedance	4 ohm
	Front speaker sensitivity	88 dB
	Housing colour	White
	Magnetically shielded	Yes
	Speaker weight	6,36 g
Package dimensions	Depth (package,cm)	21 cm
	Gross Weight (Package, kg)	6,75 kg
	Height (package,cm)	26,5 cm
	Width (package,cm)	44 cm
Packaging content	Cables included	AC
	Mounting brackets included	Yes
	Mounting kit	Yes
Performance	Audio output channels	2.0 kanály/kanálů
	Certification	CE
	Housing material	Plastic
	Magnetically shielded	Yes
	On/off switch	Yes
	Recommended usage	Universal
	RMS rated power	60 Watt
Volume control	Rotary	
Ports & interfaces	3.5 mm (1/8-inch) in	Yes
	6.35 mm (1/4-inch) input	1
	Audio RCA inputs	1
	Connectivity technology	Wired
	Line-in connectivity	3,5 cm
Power	AC input voltage	230 - 240 V
	Current	1 A
	Power consumption (standby)	0,5 Watt
	Power consumption (typical)	75 Watt
	Power source	AC
	Power source type	AC
Product dimensions	Net Weight (Product, kg)	6,2600000000000001 kg
	Product Depth	16,2 cm
	Product Height	24 cm
	Product Width	17,8 cm
Technical details	Connector(s)	RCA, Minijack, Phoenix
	Frequency range	45 - 20000 Hz
	Impedance	4 ohm

Technical details	Number of speakers	2
	Peak Music Power Output (PMPO)	300 Watt
	Plug and Play	Yes
	Speaker placement	Wall-mountable
	Tweeter	Yes
Vendor information	Brand Name	Vivolink
	Warranty	3 År
Weight & dimensions	Cord length	10 m

Andre billeder

