<section-header>

Powerful 12,000-lumen WUXGA 3LCD laser projector offering outstanding image sharpness and brightness, and long-lasting, low maintenance performance.

The EB-L1500UH installation laser projector offers powerful 12,000-lumen WUXGA performance with rich, vivid colours, for large rooms and venues, as well as reliable fit and forget performance. With flexible installation and low maintenance, this 4K-enhanced projector offers a perfect solution for scenarios where only maximum performance and durability will do.

Laser-sharp images

Ensure that your presentations, images and video pack a punch with the vivid, sharp projection offered by this 3LCD laser projector. Designed for larger venues, its high resolution WUXGA images are vivid and bright, even in daylight, while inorganic phosphor wheel technology provides superior light and heat resistance to deliver excellent reliability that lasts for up to 83,000 hours¹.

4K enhancement

For a next-level viewing experience, the projector features ingenious 4K enhancement technology, giving images exceptional sharpness and clarity, and ensuring that text in presentations is clearly legible.

Flexible positioning

Thanks to a wide range of motorised lenses, including optional ultra-short-throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image. The projector also has a built-in camera to ensure accurate calibration and capture diagnostic images (this can be fully disabled to prevent remote access).

Versatile new software

All models in the EB-L1000 series can take advantage of free Epson Professional Projector Tool software from December 2017. It allows you to set up multi-projector installations straight out of the box, simply and quickly, as well as utilising advanced techniques such as projection-mapping and edge-blending.

DATASHEET / BROCHURE



KEY FEATURES

- Laser light source technology Outstanding brightness and colour, with fit and forget reliability
- HD images with 4K enhancement Exceptional sharpness, clarity and detail for crisp images and legible text
- Versatile new software Set up multiple projector installations and utilise advanced projection techniques
- Flexible 360° installation True flexibility without distortion or loss of brightness
- Added peace of mind Product comes with five-year, 20,000hour warranty





PRODUCT SPECIFICATIONS

TECHNOLOGY Projection System	3LCD Technology
LCD Panel	1,03 inch with C2 Fine
	·
Color Light Output	12.000 Lumen- 8.400 Lumen (economy) In accordance with ISO 21118:2013 12.000 Lumen - 8.400 Lumen (economy) In accordance with ISO 21118:2013
White Light Output Portrait Colour Light Output	12.000 Lumen - 6.400 Lumen (economy) in accordance with ISO 21118.2013
Portrait White Light Output	12.000 lm
Resolution	WUXGA, 1920 x 1200, 16:10
High Definition	4K enhancement
Aspect Ratio	16:10
Contrast Ratio	2.500.000 : 1
Native Contrast	2.000 : 1
Light source	Laser
Laser Light source	20.000 hours Durability High, 30.000 hours Durability Eco
Keystone Correction	Manual vertical: ± 45 °, Manual horizontal ± 30 $^\circ$
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1,57 - 2,56:1
Zoom	Motorized, Factor: 1 - 1,6
Projection Lens Zoom Ratio	1,57 - 2,56 : 1
Lens	Optical
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %
Lens position memory	10 positions
Screen Size	60 inches - 500 inches
Projection Distance Wide	2 m - 17,2 m
Projection Distance Tele	3,3 m - 27,8 m
Projection Distance Wide/Tele	e 1,99 m - 27,77 m
Projection Lens F Number	1,8 - 2,5
Projection Lens Focal Length	36 mm - 57,35 mm
Projection Lens Focus	Motorized
nterchangeable Lens	Yes
CONNECTIVITY	
CONNECTIVIT	
Interfaces	Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in,
	Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B
	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B
nterfaces	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional)
nterfaces Epson iProjection App	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional)
nterfaces Epson iProjection App ADVANCED FEATURES	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure
nterfaces Epson iProjection App ADVANCED FEATURES	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password
nterfaces Epson iProjection App ADVANCED FEATURES Security	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection
nterfaces Epson iProjection App ADVANCED FEATURES Security	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame
nterfaces Epson iProjection App ADVANCED FEATURES Security Other features	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory
nterfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron
Interfaces Epson iProjection App ADVANCED FEATURES Security Dther features Video Color Modes Projector control GENERAL	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron
Interfaces Epson iProjection App ADVANCED FEATURES Security Dther features Video Color Modes Projector control GENERAL	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height)
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF)
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF) Storage -10° C - 60° C
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, iProjection
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Dytions	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, iProjection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Dytions	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, iProjection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Room Type / Application	 VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, iProjection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Signage / Retail, Visitor Attraction
Interfaces Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimen	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 908 Watt, 597 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 833 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23,7 kg Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, iProjection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted

EB-L1500UH

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)

EPSON[®]

- Computer cable
- Cable cover
- CD Manual

OPTIONAL ACCESSORIES

- Wireless LAN Adapter ELPAP10 V12H731P01
- HDBaseT Transmitter ELPHD01 V12H547040
- Ceiling Mount ELPMB48 High EB-G7000/L1000 V12H803010
- Ceiling Mount ELPMB47 Low EB-G7000/L1000 V12H802010
- Air Filter ELPAF51
 V13H134A51
- 3D Polarizer ELPPL01
 V12H618A01
- Stacking Frame ELPMB59 L1000 Series (EVO) V12H996B59

OPTIONAL LENSES

- Lens ELPLU03S L & G Series ST off axis 1 V12H004UA3
- Lens ELPLX02 UST Lens L1500/1700 Series V12H004X02
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1 V12H004W05
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLM15 Mid Throw L1500/L1700 Series V12H004M0F
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLW08 Wide throw
- V12H004W08
- Lens ELPLX02W UST Lens L1500/1700 Series V12H004Y02

LOGISTICS INFORMATION

ѕки	V11H910040
EAN code	8715946646985
Country of Origin	China

Produktoplysninger kan ændres uden varsel.

Epson Danmark Transformervej 6 2860 Søborg Danmark

Varemærker og registrerede varemærker tilhører Seiko Epson Corporation eller deres respektive ejere.

1. - Laser life of up to 83,000 hours in custom mode.



EB-L1500UH