

PRODUCT CATALOG

SRP 12-2021



inakustik

KABEL | LAUTSPRECHER | MUSIK

CURRENT HIGHLIGHTS

OUR FOCUS PRODUCTS



10K HDMI UP TO 100M

HDMI cable with professional fibre optic technology. This technology facilitates data rates of up to 48 Gbps on a transmission path of up to 100m. It therefore supports high-resolution 10K formats with 120 Hz as well as HDR.

AIR CABLE

„This cable carries a lot of consideration and manual work. The LS-4004 AIR is one of the finest cables we’ve ever heard. It is gifted with a phenomenal analysis. Moreover it features a lush bass and a great panorama.” stereoplay 01-2018 | LS-4004

MICRO AIR CABLE

The cables in the Reference AIR series have already caused a sensation in the world of high-end connections: “It is the best cable ever placed between amp and speakers.” AUDIO 02-2020 | LS-2404 AIR PURE SILVER. We have developed the Reference MICRO AIR series based on the same approach to physics. As the name suggests, insulating air also plays a central role in the new Reference MICRO AIR series due to its excellent dielectric properties.

POWER STATION

„We have seen many phony. They promised holy water and supplied tap water. In-akustik shows what a good power supply filter can do. The sound gain was clear, even outstanding. There is no better way to improve the high end. We are critical - but here we give a clear highlight.” stereoplay 07-2019

IN-AKUSTIK

QUALITY MANAGEMENT	06
QUALITY LEVELS	08

HOME HIFI

10

SPEAKER CABLE	12
MINI SPOOLS	18
ACCESSORIES FOR SPEAKER CABLES	20
AUDIO CABLE	22
SUBWOOFER CABLE	25
DIGITAL COAX	26
DIGITAL OPTO	27
PHONO CABLE	28
ACCESSORIES	30

HOME VIDEO

36

HDMI CABLE	38
HDMI WIRELESS	44
HDMI SWITCH	44
HDMI SPLITTER	45
ANTENNA CABLE	46
VIDEO CABLE	49
S-VIDEO CABLE	49
DISPLAYPORT CABLE	49
SCART CABLE	49
RGB/YUV	49
ACCESSORIES	50

POWER SUPPLY

52

POWER FILTER	54
POWER BAR	56
MAINS CABLE	57
POWER CABLE	57

MOBILE & HEADPHONE

58

JACK CABLE	60
HEADPHONE EXTENSION	60
JACK PLUG ADAPTER	60
USB CHARGING ADAPTER	62
HEADPHONE AMP	62

NETWORK | STREAMING | WIRELESS

64

WIFI BLUETOOTH	66
DLNA STICK & MHL ADAPTER	67
USB- & CAT CABLE	67
FIREWIRE CABLE	71

INSTALLATION

74

HDMI OPTICAL FIBRE	76
HDMI CABLE PLUG TESTER	78
POWER CABLE	78
ANTENNA	80
CAT CABLE	80
SPEAKER CABLE	81
AV PANELS	81
AV TERMINALS	82
HDMI SPLITTER	84
HDMI SWITCH	85
HD BASE-T RECEIVER	85
HDMI REPEATER	86
HDMI DIGITAL ANALOG AUDIO CONVERTER	87

AMBIENTECH

88

AMBIENTRACK	90
AMBIENART	93
AMBIENTONE	96

REFERENZ AIR

98

SPEAKER CABLE	100
DIGITAL CABLE	103
PHONO CABLE	103
AUDIO CABLE	104
MAINS CABLE	106

STOIC

112

WALL MOUNTS & ABSORBER BASES (FREE-STANDING)	112
--	-----

MUSIC & MEDIA

116

HIGHLIGHTS CD	116
HIGHLIGHTS LP	118
MASTERTAPE SELECTION	119

WORTH KNOWING

WHITELINE SERIES	72
LEGAL NOTICE	118





PHYSICS NOT VOODOO

Losses occur at every connection. The challenge is to minimise these losses with appropriate cables. The best cable is the one that least affects the reproduction quality of the Hi-Fi or video chain and transmits the original signal with the minimum loss. And we have been fighting for this for over four decades. With products we have developed ourselves and our own cable manufacturing unit in which most cables from our Reference and Excellence quality levels are manufactured. Perfect performance instead of unnecessary losses. Physics instead of voodoo – that is our credo. For the highest quality video and audio enjoyment.

inakustik
KABEL | LOUDBREKERS | WIRK

B **BRAUNKABEL**
Verbindung aus Leidenschaft

BRAWA
LIEBE ZUM DETAIL

EAGLE CABLE

in-akustik is part of the family-run Braun Group, which, includes the cable specialist Braunkabel, the model railway manufacturer BRAWA and eagle cable.



QUALITY MANAGEMENT

In our product design we do everything to ensure excellent Quality from the outset. We subject our products to intense scrutiny and continuously carry out quality controls during the production process. For example, we inspect all materials for compliance with the acceptable quality level (AQL), the standard for "imported" materials and finished products. We check the tolerances of each individual part, the print quality, the colours and the construction. We investigate chemical and hazardous substances in accordance with RoHS and REACH. We test the electrics for short circuits and configuration at each production step. We carry out both functional and mechanical tests. And, of course, we test the live performance. This is what we mean by maximum precision



E.g. all our products comply with the stringent RoHS directive. RoHS (Restriction Of Hazardous Substances) is an EU directive (2011/65/ EG) aimed at reducing the use of substances in electronic devices that are harmful to health and the environment.

The European REACH ordinance is intended to protect people and the environment from harmful chemicals. Among other things, REACH specifies the obligation to provide information on substances of particular concern in order to minimise their use.




QUALITY LEVELS

REFERENZ – THE BENCHMARK FOR PICTURE AND SOUND – SIMPLY CAN'T BEAT IT!




EXZELLENZ – FOR THE LOVERS OF PERFECT PICTURE AND SOUND EXPERIENCES.




AUDIO

PREMIUM – PICTURE AND SOUND FOR ADVANCED USERS.



STAR – THE BEST GATEWAY TO THE WORLD OF PICTURE AND SOUND.USERS.



REFERENZ – THE BENCHMARK FOR PICTURE AND SOUND – SIMPLY CAN'T BEAT IT!



CAT

USB

HIGH TECH ABSORBER

POWER SUPPLY

EXZELLEENZ – FOR THE LOVERS OF PERFECT PICTURE AND SOUND EXPERIENCES.



HDMI

ANTENNA CABLE

CAT CABLE

USB CABLE


ABSORBER

POWER BARS

HDMI WIRELESS



PREMIUM – PICTURE AND SOUND FOR ADVANCED USERS.



HDMI

HDMI MINI | MICRO

VIDEO CABLE

ANTENNA CABLE

CAT

USB

MHL ADAPTER

HDMI SWITCH

STAR – THE BEST GATEWAY TO THE WORLD OF PICTURE AND SOUND.



HDMI

ANTENNA CABLE

YUV

S-VIDEO CABLE

VIDEO CABLE

HDMI SWITCH

DAC



SPEAKER CABLE	12	26	DIGITAL COAX
MINI SPOOLS	18	27	DIGITAL OPTO
ACCESSORIES SPEAKER CABLE	20	28	PHONO CABLE
AUDIO CABLE	22	30	ACCESSORIES HOME HIFI
SUBWOOFER CABLE	25		



HOME HIFI

Our physical approach: Cables as such produce no sound, but have a filter effect and interact with the components. In our opinion, audio connections should be as inconspicuous as possible and should not produce any sound colouration. Because these may be astonishing when heard for the first time, but in the end they distort the original sound and over the course of time they become highly irritating. The trick is therefore to adapt the unavoidable physical filter effect of the cables by means of the architecture and choice of materials in such a way that losses and interactions are reduced to a minimum.







LS-204 XL MICRO AIR



We are continuing the story of AIR technology with the new REFERENCE MICRO AIR series: As with the already legendary AIR Helix cables, air is a central component of the insulation concept in the new REFERENCE MICRO AIR technology. However, due to the low loudspeaker impedances low line resistances and low inductance are also very important for loudspeaker cables. For this reason, a total of 6 concentric copper conductors are used in the REFERENCE LS-204 XL MICRO AIR in addition to the air dielectric. Thanks to this multicore architecture, the magnetic fields of the positive and negative conductors overlap and neutralise each other. This reduces the inductance of the cable considerably, thereby guaranteeing unadulterated transmission of the audio signal over a broad frequency range. The LS-204 XL follows this approach and has a well-balanced sound character with precise timing with a well-controlled foundation. This cable is therefore primarily designed for fully-sized floor-standing loudspeakers. Of course, sound always is evaluated subjectively and ultimately depends on the overall constellation of the hi-fi system. In the end the decisive factor is your very personal auditory impression.


The REFERENCE LS-204 XL MICRO AIR is available with BFA Bananas or with cable lugs or as Easy-Plug version. The surfaces of the BFA Bananas and the cable lugs are finished with a rhodium coating and are therefore extremely durable. The contact surfaces and the screw connection of the cable lugs are manufactured from a single piece, thereby avoiding contact resistance. The contact surface, which has slits on the side, changes to a concave shape when the device terminal connections are tightened, thus preventing the cable lugs from sliding out.

- Micro Air technology
- Air dielectric
- Concentric copper wire construction
- 6-fold multicore architecture
- Single Wire
- Made in Germany
- Standard length: 2 x 3.0 m
- Available as BFA, Cable lug or Easy-Plug variant



ITEM NO	CONNECTION		LENGTH	SRP
007716231	Easy Plug	SingleWire	2x3,0m	758,00
007716232	BFA Banana	SingleWire	2x3,0m	842,00
007716233	Spade	SingleWire	2x3,0m	898,00

LS-204 MICRO AIR



MICRO AIR "Air Chambers"


Like the flagship model, the LS-204 is also based on MICRO AIR technology. The difference lies in the multicore architecture. Compared to the XL version, the LS-204 has four instead of six concentric copper wires. This impressively agile cable was primarily developed for slim floor-standing speakers with smaller bass drivers. The REFERENCE LS-204 MICRO AIR is available as Single-Wire and Single-BiWire version with BFA Bananas or cable lugs or as Easy-Plug version.

- Micro Air technology
- Air dielectric
- Concentric copper wire construction
- 4-fold multicore architecture
- Made in Germany
- Single wire & Single BiWire
- Standard length: 2 × 3.0 m
- Available as BFA, cable lug or Easy-Plug variant



ITEM NO	CONNECTION		LENGTH	SRP
007716131	Easy Plug	Singlewire	2x3,0m	617,00
007716132	BFA Banana	Singlewire	2x3,0m	702,00
007716133	Spade	Singlewire	2x3,0m	758,00
0077161311	Easy Plug	Single-BiWire	2x3,0m	641,00
0077161321	BFA Banana	Single-BiWire	2x3,0m	758,00
0077161331	Spade	Single-BiWire	2x3,0m	814,00

LS-104 MICRO AIR



MICRO AIR "Air Chambers"

The LS-104 is an excellent entry-level model to the MICRO AIR series. It already clearly stands out from standard cables and demonstrates the acoustic potential of this technology. Especially sensitive amplifiers harmonise perfectly with this cable. The REFERENCE LS-104 MICRO AIR provides an open and more relaxed sound. It is also available with BFA Bananas or cable lugs and as an Easy-Plug variant.

- Micro Air technology
- Air dielectric
- Concentric copper wire construction
- Made in Germany
- Single wire
- Standard length: 2 × 3.0 m
- Available as BFA, cable lug or Easy-Plug variant



ITEM NO	CONNECTION		LENGTH	SRP
007716031	Easy Plug	Singlewire	2x3,0m	449,00
007716032	BFA Banana	Singlewire	2x3,0m	534,00
007716033	Spade	Singlewire	2x3,0m	590,00



LS-803



The little brother of the LS-1203 has an 8-fold multicore design. The tightlypacked PE-Network Jacket holds the wires together and reduces micro-vibrations (High Power Management), which occur in the cable from the changing magnetic fields in the beat of the music. The cable therefore also transmits high level and extreme dynamic peaks with absolute precision. As the frequency rises, the signal increasingly flows on the conductor surface. The higher the frequency, the lower the effective cross-section, and the greater the resistance. The cable sounds „bass-heavy“. The conductors from the Referenz loudspeaker cable have a core made of polyethylene. In this way a circular waveguide is formed and the actual cross-section used is the same for all sound frequencies. The result: a homogeneous, balanced loudspeaker cable with a wide-ranging sound spectrum.

- 8-fold Multicore
- High Speed waveguide technology
- Concentric Copper
- DUO-PE II insulation around each conductor
- High Power Management
- PE-Network Jacket

ITEM NO		LENGTH	SRP
0077008	Referenz LS-803 On Spool; Price/m	50m	126,00
007700832	Referenz LS-803 BFA; SW	2x3,0m	1006,00
0077008321	Referenz LS-803 BFA; SBW	2x3,0m	1071,00
007700835	Referenz LS-803 BFA 45°; SW	2x3,0m	1103,00
0077008351	Referenz LS-803 BFA 45°; SBW	2x3,0m	1242,00
007700833	Referenz LS-803 Spade Lug; SW	2x3,0m	1042,00
0077008331	Referenz LS-803 Spade Lug; SBW	2x3,0m	1130,00

LS-603



The Referenz LS-603 with its 6-fold multicore design has considerable electrical and tonal characteristics. The large cable section provides an excellent and controlled low frequency response and high efficiency.

- 6-fold Multicore
- High Speed waveguide technology
- Concentric Copper
- DUO-PE II insulation around each conductor
- High Power Management
- PE-Network Jacket

ITEM NO		LENGTH	SRP
007700632	Referenz LS-603 BFA; SW	2x3,0m	696,00
007700635	Referenz LS-603 BFA 45°; SW	2x3,0m	791,00
007700633	Referenz LS-603 Spade Lug; SW	2x3,0m	751,00

LS-1102



- Hexa CC-187 Design; 6 x 1,87 mm²
- 3-fold symmetrical design
- 37 wires concentrically stranded per conductor
- DUO-PE II insulation around each conductor
- Low induction for homogeneous reproduction
- PE-Network Jacket

ITEM NO		LENGTH	SRP
00781102	Referenz LS-1102; Price/m	50m	47,99

LS-1002



- Quatro CC-297 Design; 4 x 2,97 mm²
- Double-symmetrical design
- 37 wires concentrically stranded per conductor
- DUO-PE II insulation around each conductor
- Low induction for homogeneous reproduction
- PE-Network Jacket

ITEM NO		LENGTH	SRP
00781002	Referenz LS-1002; Price/m	50m	36,99

LS-602

★★★★★
REFERENZ

The Referenz LS-602 is a double-symmetrical cable design. The high density reduces the inductance factor to the benefit of the middle and high-frequency ranges.

- Quatro CC-187 Design; 4 x 1,87 mm²
- Double-symmetrical design
- 37 wires concentrically stranded per conductor
- DUO-PE II insulation around each conductor
- Low induction for homogeneous reproduction
- PE-Network Jacket

ITEM NO	LENGTH	SRP
00780602 Referenz LS-602; Price/m	50m	26,99

LS-502

★★★★★
REFERENZ

The LS-502 has two symmetrically arranged strands, each containing 37 concentrically stranded wires. The thick wires demonstrate its class even when used with high-performance systems. AUDIO (LS-502): "... the sound is so warm, just as you would expect from in-akustik Referenz – direct, honest, straightforward."

- Duo CC-297 Design; 2 x 2,97 mm²
- Symmetrical design
- 37 wires concentrically stranded per conductor
- DUO-PE II insulation around each conductor
- Low induction for homogeneous reproduction
- PE-Network Jacket

ITEM NO	LENGTH	SRP
00780502 Referenz LS-502; Price/m	50m	21,49

LS-40

★★★★★
EXZELLENZ

The speaker cable Exzellenz LS-40 is based on the technical principles of the legendary Referenz Series. It consists of four twisted wires. The PE Network Jacket holds the wires tightly together. The insulation is made of high quality, solid PE (Polyethylene). The elaborately finished cable offers a powerfull, dynamic and very clear sound. The 4-wire construction allows the use as a single bi-wire cable.

- 2 x 5,0mm² (4 x 2,5mm²)
- Low-loss PE insulation
- Copper wires with 50 x 0.25 mm strands
- Additional support elements made of PE
- Double symmetrical, 4-wire construction
- Low induction for homogeneous high-frequency reproduction

ITEM NO	LENGTH	SRP
00602740 Exzellenz LS-40 2,5mm ² ; Price/m	50m	21,49
00602743 Exzellenz LS-40 2,5mm ² ; Easy-Plug SW	2x3,0m	247,00
006027431 Exzellenz LS-40 2,5mm ² ; Easy-Plug SBW	2x3,0m	260,00

LS-20

★★★★★
EXZELLENZ


Das Speaker Cable Exzellenz LS-20 basiert auf den technischen Grundlagen der legendären Referenz-Serie. Es besteht aus zwei miteinander verseilten Adern. Das PE Network Jacket hält die Adern kompakt zusammen. Die Kupferlitzen sind mit hochwertigem, massivem PE (Polyethylen) isoliert. Das aufwendig verarbeitete Cable besticht durch einen straffen, dynamischen und sehr klaren Klang.

- 2 x 2,5mm²
- Low-loss PE insulation
- Copper wires with 50 x 0.25 mm strands
- Additional support elements made of PE
- Symmetrical, 2-wire construction
- Low induction for homogeneous high-frequency reproduction

ITEM NO	LENGTH	SRP
00602720 Exzellenz LS-20 2,5mm ² ; Price/m	50m	14,29
00602723 Exzellenz LS-20 2,5mm ² ; Easy-Plug SW	2x3,0m	217,00



SPEAKER CABLE MSR




- MSR®-Technology
- Pure grade (oxygen free) copper
- Finest stranded (diameter 0,07 mm)
- 1302 / 2100 / 3150 strands
- Highly flexible!



Cable with MSR-Technology
with regulated current
distribution

ATMOS AIR



- Rich in sound concentric copper conductor
- Loss-free air insulation
- Precise, concentric conductor design
- Additional air dielectric
- Plus/minus recognition

SPEAKER CABLE SILVER



- High frequency range optimised, silver-plated concentric copper conductor (15 g/kg)
- Low-loss PE insulation
- Additional PE dielectric
- Finest 0.07 mm wire design
- Opposing S/Z stranding (easy to install)

ITEM NO		LENGTH	SRP
0060242	MSR 2,5mm ²	100m	8,19
0060244	MSR 4,0mm ²	80m	12,19
0060246	MSR 6,0mm ²	50m	14,99

ITEM NO		LENGTH	SRP
0060223	Atmos Air 2,97mm ²	50m	9,69

ITEM NO		LENGTH	SRP
0060212	LS Silver 2,5mm ²	70 m	16,69

SPEAKER CABLE FLAT



- Finely-stranded: 0.10 mm (1.5 mm²) / 0.07 mm (2.5 mm²)
- "Invisible" to lay under carpets or behind skirting boards
- Flat, compact design
- Plus/minus recognition

SPEAKER CABLE SILVER



- High frequency range optimised, silver-plated concentric copper conductor (5 g/kg)
- Opposing S/Z stranding (easy to install)
- Resistant insulation
- Plus/minus recognition

SPEAKER CABLE CU



- Finely-stranded: 0.15 mm wire design
- Opposing S/Z stranding (easy to install)
- Resistant insulation
- Plus/minus recognition

ITEM NO		LENGTH	SRP
00402326	LS Flat 2,5mm ²	130m	7,59

ITEM NO		LENGTH	SRP
0040214	LS Silver 4,0mm ²	100m	11,49
0040212	LS Silver 2,5mm ²	120m	7,69
0040211	LS Silver 1,5mm ²	180m	4,91

ITEM NO		LENGTH	SRP
004024	4,0mm ² Trans	100m	8,99
0040246	4,0mm ² White	100m	8,99
00402498	4,0mm ² Trans	400m	8,99
004022	2,5mm ² Trans	120m	5,19
00402298	2,5mm ² Trans	500m	5,19
004021	1,5mm ² Trans	180m	3,61

SPEAKER CABLE
FLAME RETARDANT

- Cross section: 1,5mm² & 2,5mm²
- Structure 30 x 0.25 mm CU & 50 x 0.25 mm CU
- High flexibility due to transposed wires
- Extruded sheathing simplifies removal of the insulation
- Insulation: PVC
- Diameter: approx. 6,5mm & 9,5mm
- Flame-retardant, conforms to IEC 60332-1-2 Class E
- Conforms to RoHS Directive 2011/65/EU



ITEM NO		LENGTH	SRP
00402709	2x1,5mm ²	150m	3,87
00402718	2x2,5mm ²	100m	5,69

SPEAKER CABLE CU



- Universal speaker cable for any application
- Flexible and easy to install with opposing S/Z stranding
- Plus/minus recognition

ITEM NO		LENGTH	SRP
003022	2,5mm ² Trans	150m	4,40
00302298	2,5mm ² Trans	500m	4,40
0030226	2,5mm ² White	150m	4,40
003021	1,5mm ² Trans	200m	2,70
00302198	1,5mm ² Trans	1000m	2,70
0030216	1,5mm ² Weiß	200m	2,70
0030218	1,5mm ² Anthracite	200m	2,70
003020	0,75mm ² Trans	400m	1,54
0030206	0,75mm ² White	400m	1,54

CABLE UNWINDER



An innovative solo unwinder for dealing with metre goods professionally:

- Allows metre goods to be stored easily on the peg-board in any combination with any number of spools.
- Uses the sales area extremely efficiently.
- Ideal for secondary placement.
- Easy to handle when replacing spools.
- Useful winding spools for convenient use

ITEM NO		UNIT	SRP
0102711	Cable Unwinder	1 pc	-

SPEAKER CABLE CU



- Finely-stranded: 0.15 mm wire design
- Opposing S/Z stranding (easy to install)
- Resistant insulation
- Plus/minus recognition

ITEM NO		LENGTH	SRP
00402410	4,0mm ² Trans	10m	97,00

SPECIAL EDITION



- Flexible, easy to install
- Universal speaker cable for any application
- Plus/minus recognition
- Mini spool with pamel for easy handling*

ITEM NO		LENGTH	SRP
01002430	1,5mm ² Trans	30m	72,00
01002436	1,5mm ² White	30m	72,00
010024369	1,5mm ² White*	30m	74,00
01004425	2,5mm ² Trans	25m	97,00

CABLE RING



- Flexible, easy to install
- Universal speaker cable for any application
- Plus/minus recognition

ITEM NO		LENGTH	SRP
003020006	0,75mm ² Trans	6m	10,79
003020010	0,75mm ² Trans	10m	16,29
003021010	1,5mm ² Trans	10m	26,99
0030216102	1,5mm ² White	10m	26,99
003021020	1,5mm ² Trans	20m	54,00
003022010	2,5mm ² Trans	10m	42,99



REFERENCE SOUND EDITION

The samplers of our Reference Sound Edition have been assembled with a love of musical detail. RESO Mastering (Reference Sound Mastering), the high definition mastering procedure, provides significant acoustic improvements in transparency, dynamics, bass reproduction and depth differentiation. The music is gaining more atmosphere and emotion. To best transmit this musical experience, instead of a normal CD, a HQCD respectively to get even closer to the master quality, a UHQ-CD is used as sound carrier and instead of normal LP vinyl, 180g audiophile Virgin Vinyl. **NEW:** 4 samplers of the RESO-Edition are now also available as Mastertape (Direct to Tape Mastertape).



RESO GREAT VOICES VOL. 1

INAK 75015 UHQCD
INAK 75011 HQCD
INAK 75011 2LP - 180 Gr. Virgin Vinyl
INAK 75019 MS - Mastertape Selection



RESO GREAT VOICES VOL. 2

INAK 7502 HQCD
INAK 75021 2LP - 180 Gr. Virgin Vinyl
INAK 75029 MS - Mastertape Selection



RESO GREAT COVER VERSIONS

INAK 7503 HQCD
INAK 75031 2LP - 180 Gr. Virgin Vinyl
INAK 75031 MS - Mastertape Selection



RESO GREAT GUITAR TUNES

INAK 7504 HQCD
INAK 75041 2LP - 180 Gr. Virgin Vinyl



SOUND CHECK

INAK 7505 HQCD
INAK 75051 2LP - 180 Gr. Virgin Vinyl



RESO GREAT WOMEN OF SONG

INAK 7506 HQCD
INAK 75061 2LP - 180 Gr. Virgin Vinyl
INAK 75069 MS - Mastertape Selection



RESO GREAT MEN OF SONG

INAK 7507 HQCD
INAK 75071 2LP - 180 Gr. Virgin Vinyl



RESO GREAT VOICES VOL. 3

INAK 75085 UHQCD
INAK 7508 HQCD
INAK 75081 2LP - 180 Gr. Virgin Vinyl

BANANA BFA-103

★★★★★
REFERENZ



- Rhodium-coated
- Dimensions: 45 x 15 mm (L x D)
- Cable cross-section: 10 mm²
- Cable diameter: 8.2 mm max.
- Cable diameter: 7,5 mm max (BFA 45°)
- Full-surface contact
- Fully insulated connector with screws

ITEM NO	UNIT	SRP
00719001	Set of 4	85,00
007891800	bulk	15,99
007891801	Bulk 45°	25,99

SCREW TYPE

★★★★★
REFERENZ



The BFA, flexible pin and spade lug adapter all provide several connection options, for instance, if the amplifier or speaker is replaced and different connections are required.

ITEM NO	UNIT	SRP
00971100	Basic Adapter	5,89
00789168BW	BFA	8,79
009711018	Spade Lug	7,99
009711048	Flexible Pin	7,09

BANANA BFA

★★★★★
EXZELLENZ



- Dimensions: 45 x 15 mm (L x D)
- Cable cross-section: 6 mm²
- Cable diameter: 8.2 mm max.
- Full-surface contact
- Fully insulated connector with screws
- 24c gold plated or silver plated
- Red/Black or White/Black coding

ITEM NO	UNIT	SRP
00789169BW	bulk (b/w)	8,99
008169	bulk (r/b)	9,59
0081691	Set of 4 (r/b)	38,99

BANANA BFA

★★★★★
EXZELLENZ



- Cable cross-section: 6 mm²
- Cable diameter: 8.2 mm max.
- Full-surface contact
- 24c gold plated
- Red/Black coding

ITEM NO	UNIT	SRP
006500021	Set of 4	70,00

BANANA MULTI CONTACT

★★★★★
PREMIUM



- Cable cross-section: up to 16 mm²
- Red/Black coding
- With screw connection
- 24c gold plated

ITEM NO	UNIT	SRP
008147	bulk	11,09
0081471	Set of 4	47,99

BANANA MULTI TIP

★★★★★
PREMIUM



- Cable cross-section: up to 16 mm²
- Red/Black coding
- With soldered connection
- 24c gold plated

ITEM NO	UNIT	SRP
0081483	bulk; 6mm ²	4,40
00814831	Set of 4; 6mm ²	18,69
0081484	bulk; 10mm ²	4,40
00814841	Set of 4; 10mm ²	18,69

FLEXIBLE PIN

★★★★★
PREMIUM



- Cable cross-section: up to 6 mm²
- For safe and easy connections on clip terminals
- For crimping or soldering
- 24c gold plated

ITEM NO	UNIT	SRP
008155	bulk	4,78
0081551	Set of 4	20,49

HOLLOW TIP

★★★★★
PREMIUM



- Cable cross-section: 6 mm²
- Full-surface contact
- For crimping or soldering
- 24c gold plated or silver plated

ITEM NO	UNIT	SRP
008149	bulk	2,58
0081492	bulk; silver plated	2,70



SPADE LUG KS-103



- Rhodium-coated
- Spade Lug in one piece
- Cable cross-section: 10 mm²
- Cable diameter: 9.2 mm max.
- Spring-loaded for better contact
- Staged spade lug 8 mm/6 mm

ITEM NO	UNIT	SRP
007890802	bulk; 7,0mm	25,99
007890801	bulk; 9,2mm	25,99

SPADE LUG KS-60



- 24c gold plated contacts
- Cable cross-section: up to 6 mm²
- For crimping or soldering
- Black/White coding
- Staged spade lug 8 mm/6 mm

ITEM NO	UNIT	SRP
007896	bulk	11,49

SPADE LUG



- 24c gold plated contacts
- Cable cross-section: up to 4 mm²
- For crimping or soldering
- Black/Red coding
- Staged spade lug 8 mm/6 mm

ITEM NO	UNIT	SRP
00450022	bulk	2,32

SOLDER



RoHS compliant special solder with high silver content. This ensures perfect and corrosion-free connections

ITEM NO	UNIT	SRP
010291	bulk	45,99

BI-WIRE JUMPER



High-end bi-wire jumper based on the LS-803. Fitted with the KS-103 Referenz spade lug or BFA Banana. The rhodium surface treatment is extremely durable. The contact surfaces and the screw connection are manufactured from a single piece, allowing contact resistance to be avoided. The contact surface of the spade, which is slitted on the side, changes to a concave shape when the screw connections are tightened, thus preventing the spade lug from sliding out.

- Length: 20cm; Set of 2

ITEM NO	SRP
00719302 LS-803; Spade Lug	217,00
00719303 LS-803; BFA	174,00

BI-WIRE JUMPER



High-end bi-wire jumper based on the LS-1002. Fitted with the KS-60 Referenz spade lug (6/8 mm)

- Length: 15cm; Set of 2

ITEM NO	SRP
00719301 LS-1002; Spade Lug	153,00





NF-204 MICRO AIR



Since the outputs of hi-fi devices only provide very weak signals and react sensitively to high cable capacitance, the cable capacitance plays a significant role when connecting up hifi components. What is known as a low-pass filter is produced that cuts off high frequencies and also causes phase shifts. For this reason, RCA and XLR audio cables are predestined for the air-based insulation of MICRO AIR technology. Another special feature of the NF-204 MICRO AIR is its symmetrical architecture that guarantees a high level of immunity to electromagnetic emissions. We have also developed a completely new RCA connector that is completely solder-free for the MICRO AIR series. It consists of several parts, which are only joined together over the course of manufacturing. The cable ends are prepared with a great deal of passion and a delicate touch in our cable manufacturing plant, into which contact pins made of tellurium copper are inserted and pressed with a pressure of 1.5 tons. The NF-204 MICRO AIR is also available in an XLR version for those devices with balanced inputs and outputs.

- Micro Air technology
- Air dielectric
- Concentric copper wire construction
- Symmetrical architecture
- Signal-free, double shielding
- Direct pressure injected RCA connector (1.5 tons of pressure)
- Plug with tellurium copper with rhodium-coated contacts
- PE network jacket
- Made in Germany
- Standard lengths: 0.75 m, 1.0 m, 1.5 m
- Available as RCA or XLR version



ITEM NO	CONNECTION	LENGTH	SRP
0071881075	RCA	0,75m	315,00
007188110	RCA	1,0m	360,00
007188115	RCA	1,5m	449,00
00718810753	XLR	0,75m	337,00
0071881103	XLR	1,0m	382,00
0071881153	XLR	1,5m	472,00



NF-104 MICRO AIR



Compared to the NF-204 MICRO AIR, the NF-104 MICRO AIR has a conventional, coaxial architecture. In addition to the MICRO AIR technology, the newly developed RCA connector, which is completely solder-free, is another special feature of the NF-104. By omitting the solder, transition resistances and element formation are significantly reduced. As the name suggests, the NF-104 harmonises particularly well with the LS-104 speaker cable. The two cables are perfect entry-level models for MICRO AIR technology.

- Micro Air technology
- Air dielectric
- Concentric copper wire construction
- Coaxial architecture
- Double shielding
- Direct pressed connector (1.5 tons of pressure)
- Plug with tellurium copper with rhodium-coated contacts
- PE network jacket
- Made in Germany



ITEM NO	CONNECTION	LENGTH	SRP
0071880075	RCA	0,75m	253,00
007188010	RCA	1,0m	281,00
007188015	RCA	1,5m	337,00



NF-803 | RCA & XLR



The audio cable NF-803 from the in-akustik Referenz series convinces with outstanding clarity, precision and accuracy. Two high speed signal conductors provide the signal transport. At the same time, the DUO-PE II insulation and the air-filled PE tubes reduce unwanted capacitance and enable the signal source to work "comfortably". The PE-Network Jacket also prevents micro-vibrations. Another highlight are the Referenz GAP II RCA plugs which take the symmetrical design to the limit.

GAP II RCA-STECKER

This high end plug enables a symmetrical connection to be made up to the terminals of the equipment. Thanks to its two-piece earth ring, this RCA plug has three contacts, exactly like an XLR plug. The screening and negative conductors are only brought together again when at the terminals of the equipment.

HIGH SPEED SIGNALLEITER

The NF-803 has fine stranded signal wires, with each individual wire having a lacquer coating. This coating insulates the wires from each other which creates a larger effective conductor surface. It also prevents eddy currents between the wires. A conductor that can also transmit extremely dynamic signal sequences very quickly and precisely.

ITEM NO		LENGTH	SRP
007184007	Referenz Audio Cable NF-803 RCA	0,75m	313,00
007184010	Referenz Audio Cable NF-803 RCA	1,0m	352,00
007184015	Referenz Audio Cable NF-803 RCA	1,5m	428,00
0071840073	Referenz Audio Cable NF-803 XLR	0,75	374,00
0071840103	Referenz Audio Cable NF-803 XLR	1,0m	414,00
0071840153	Referenz Audio Cable NF-803 XLR	1,5m	490,00

NF-202 | RCA



Precisely because audio signals are so sensitive, we have equipped our Referenz NF-202 audio cable with some highly-effective technology: optimum DUO-PE II insulation with air-filled PE tubes, an innovative GAP plug, but also in particular an extremely sophisticated, solid conductor made of high-purity OFC copper, which all ensure uniform transit times and crystal-clear signal transmission. The earth and signal conductors are the same size and arranged symmetrically. The PE network jacket prevents micro-vibrations.

- Symmetrical design (two solid conductors)
- PE network jacket against micro-vibrations
- Wires made of high-purity OFC copper
- Foil shielding and weave sleeve made of OFC copper
- DUO-PE II insulation around each conductor
- Polyethylene tubes filled with air (best insulator) reduce unwanted capacitance

ITEM NO		LENGTH	SRP
0078202	Referenz Audio Cable NF-202 RCA; Price/m	50m	37,49
00718106	Referenz Audio Cable NF-202 RCA	0,6m	250,00
00718112	Referenz Audio Cable NF-202 RCA	1,2m	293,00

EXZELLENZ | RCA



- 2 fold coaxial construction | Double Mono Design
- 2 x 2 fold shielding
- Silver plated
- Solide conductor
- High-purity OFC copper
- Low-loss PE insulation
- 24k gold plated contacts

ITEM NO		LENGTH	SRP
0060410098	Exzellenz Audio Cable Coax Mono Price/m from 1,0m		35,49
006041007	Exzellenz Audio Cable RCA	0,75m	131,00
006041015	Exzellenz Audio Cable RCA	1,5m	166,00
00604103	Exzellenz Audio Cable RCA	3,0m	237,00

EXZELLENZ | XLR



- Doublesymmetrical Design | Double mono construction
- 2 x 2-fold shielding
- Silver plated
- Very low capacity
- High-purity OFC copper
- Low-loss PE insulation
- 24c gold-plated contacts

ITEM NO		LENGTH	SRP
0060500098	Exzellenz Audio Cable Sym. Mono Price/m from 1,0m		38,49
006050007	Exzellenz Audio Cable XLR	0,75m	202,00
006050015	Exzellenz Audio Cable XLR	1,5m	248,00
00605003	Exzellenz Audio Cable XLR	3,0m	373,00



AUDIO CABLE | RCA




ITEM NO		LENGTH	SRP
00404007	Premium RCA	0,75m	43,99
00404015	Premium RCA	1,5m	52,00
0040403	Premium RCA	3,0m	68,00
0040405	Premium RCA	5,0m	86,00

AUDIO CABLE | XLR



ITEM NO		LENGTH	SRP
00405007	Premium XLR	0,75m	69,00
00405015	Premium XLR	1,5m	83,00
0040503	Premium XLR	3,0m	109,00
0040505	Premium XLR	5,0m	137,00

AUDIO CABLE | RCA



ITEM NO		LENGTH	SRP
00304000	On Spool Stereo	50m	6,09
00304107	Star RCA	0,75m	25,99
00304115	Star RCA	1,5m	33,49
0030413	Star RCA	3,0m	41,99
0030415	Star RCA	5,0m	54,00


SUBWOOFER CABLE

SUB CABLE | MONO




ITEM NO		LENGTH	SRP
0060410098	On Spool Price/m	from 1,0m	35,49
00604202	Exzellenz Mono-Sub	2,0m	103,00
00604203	Exzellenz Mono-Sub	3,0m	124,00
00604205	Exzellenz Mono-Sub	5,0m	172,00
006042075	Exzellenz Mono-Sub	7,5m	275,00
00604210	Exzellenz Mono-Sub	10,0m	345,00
00604212	Exzellenz Mono-Sub	12,0m	453,00

SUB CABLE | Y-SUB



ITEM NO		LENGTH	SRP
0040802	Premium Y-Sub	2,0m	37,49
0040803	Premium Y-Sub	3,0m	41,99
0040805	Premium Y-Sub	5,0m	51,00

SUB CABLE | MONO




ITEM NO		LENGTH	SRP
004080200	On Spool Price/m	50m	5,59
00408021	Premium Mono-Sub	2,0m	30,99
00408031	Premium Mono-Sub	3,0m	36,99
00408051	Premium Mono-Sub	5,0m	47,99

SUB-CABLE | Y-SUB



STAR




ITEM NO		LENGTH	SRP
0030822	Star Y-Sub	2,0m	22,49
0030823	Star Y-Sub	3,0m	26,99
0030825	Star Y-Sub	5,0m	36,49
00308275	Star Y-Sub	7,5m	40,49
00308310	Star Y-Sub	10,0m	48,99
00308312	Star Y-Sub	12,0m	60,00

SUB-CABLE | MONO



STAR



ITEM NO		LENGTH	SRP
00308221	Star Mono-Sub	2,0m	17,69
00308231	Star Mono-Sub	3,0m	20,49
00308251	Star Mono-Sub	5,0m	24,99
003082751	Star Mono-Sub	7,5m	35,99
003083101	Star Mono-Sub	10,0m	38,99
003083121	Star Mono-Sub	12,0m	40,49

A TASTY SOUND COLLECTION



Tracks as blue as the kind of atmosphere you can only really get through with a good single malt in your hand. Songs from singers and songwriters to savour like fine wine. Relaxing music to unwind with a nice, hot cup of tea. Latin American rhythms. From salsa to Latin jazz – a mix of coffee, Cuba and Caribbean. That is the Tasty Sound Series from in-akustik.

ITEM-NO	TITEL	ITEM NO	TITEL
0167961	Coffee & Latin	0167965	Champagne & Songs
0167962	Tea & Tones	0167966	Cocktails & Guitars
0167963	Wine & Vocals	0167967	Cigars & Sounds
0167964	Whisky & Blues	0167968	Absinthe & Voices
		0167969	Beer & Rock

DIGITAL COAX

COAX DIGITAL CABLE



EXZELLENZ



The Excellence digital cable has two separately routed shields. This means that the sensitive audio data is optimally protected from external interferences. The digital music signal is precisely transmitted through the silver-plated conductor and the perfectly adapted impedance (Low Jitter). This enables a natural and dynamic sound for high resolution audio formats. The solid 24 carat gold-plated metal connectors constantly ensure maximum contact and minimal contact resistance.

ITEM NO		LENGTH	SRP
0060410098	Exzellenz Audio Cable Coax Mono Price/m from 1,0m		35,49
006044007	Exzellenz Digital Cable	0,75m	79,00
006044015	Exzellenz Digital Cable	1,5m	96,00
00604403	Exzellenz Digital Cable	3,0m	130,00

XLR AES/EBU DIGITAL CABLE



EXZELLENZ



This Excellence digital cable is specially designed for the professional 110 Ohm AES/EBU standard. The symmetrical structure and double shielding minimise interferences and provide the sensitive audio data with the best possible protection. The digital music signal is precisely transmitted through silver-plated conductors and the perfectly adapted impedance (Low Jitter). This enables a natural and dynamic sound especially for high resolution audio formats.

ITEM NO		LENGTH	SRP
0060500098	Exzellenz Audio Cable Sym. Mono Price/m from 1,0m		38,49
006051007	Exzellenz Digital Cable XLR AES/EBU	0,75m	119,00
006051015	Exzellenz Digital Cable XLR AES/EBU	1,5m	137,00
00605103	Exzellenz Digital Cable XLR AES/EBU	3,0m	204,00



COAX DIGITAL CABLE



PREMIUM

ABSCHIRMUNG
SHIELDINGVERGOLDET
GOLD-PLATEDOFC COPPER
HOCHREIN
HIGH PURITYMassiMeiter
Solid Conductor75 OHM
IMPEDANZRoHS
Compliant

ITEM NO		LENGTH	SRP
0041401	Video/Digital	1,0m	29,99
0041403	Video/Digital	3,0m	48,49

COAX DIGITAL CABLE



STAR

ABSCHIRMUNG
SHIELDINGOFC COPPER
HOCHREIN
HIGH PURITYVERGOLDET
GOLD-PLATEDRoHS
Compliant

ITEM NO		LENGTH	SRP
00316207	Video/Digital	0,75m	12,99
00316215	Video/Digital	1,5m	16,69
0031623	Video/Digital	3,0m	18,89
0031625	Video/Digital	5,0m	24,99
00316310	Video/Digital	10m	40,49

AUDIOPHILE HIGHLIGHT:
REFERENCE SOUND EDITION

RESO Mastering (Reference Sound Mastering), the high definition mastering procedure, provides significant acoustic improvements in transparency, dynamics, bass reproduction and depth differentiation. The music is gaining more atmosphere and emotion.

NEW: 4 samplers of the RESO-Edition are now also available as Mastertape (Direct to Tape Mastertape).

ITEM NO	
01675015	Great Voices (U-HQCD)
0167501	Great Voices (HQCD)
01675011	Great Voices (2 LP)
01675019	Great Voices (Mastertape Selection)

DIGITAL OPTO

DIGITAL CABLE | OPTICAL



EXZELLENZ

LICHTLEITER
OPTICAL FIBERPMMA-FASER
POLYMER FIBERLOW
JITTERMetallstecker
Solid Metal PlugTEXTILE
JACKET

TOS Link

RoHS
Compliant

ITEM NO		LENGTH	SRP
00604501	TOS-Link	1,0m	74,00
00604502	TOS-Link	2,0m	86,00

DIGITAL CABLE | OPTICAL



PREMIUM

LICHTLEITER
OPTICAL FIBERNylon-Lichtleiter
Nylon Optical FiberRoHS
Compliant

ITEM NO		LENGTH	SRP
0041201	TOS-Link	1,0m	70,00
0041202	TOS-Link	2,0m	80,00
0041203	TOS-Link	3,0m	89,00
0041205	TOS-Link	5,0m	105,00
0041210	TOS-Link	10,0m	155,00

DIGITAL CABLE | OPTICAL



STAR

LICHTLEITER
OPTICAL FIBERRoHS
Compliant

ITEM NO		LENGTH	SRP
00312107	TOS-Link	0,75m	18,89
00312115	TOS-Link	1,5m	22,49
0031213	TOS-Link	3,0m	28,49
00312150	TOS-Link	5,0m	34,99
00312175	TOS-Link	7,5m	43,99
003121100	TOS-Link	10,0m	53,00
003121150	TOS-Link	15,0m	70,00
003121071	TOS-Link > Mini Plug	0,75m	18,89
003121151	TOS-Link > Mini Plug	1,5m	22,49
00312131	TOS-Link > Mini Plug	3,0m	28,49

PHONO CABLE NF-803



The phono cable NF-803 convinces with outstanding clarity, precision and accuracy. Two high speed signal conductors provide the signal transport. At the same time, the DUO-PE II insulation and the air-filled PE tubes reduce unwanted capacitance and enable the signal source to work "comfortably". The PE-Network Jacket also prevents micro-vibrations. Another highlight are the Referenz GAP II RCA plugs which take the symmetrical design of this connection to the limit.

„Conclusion: Both cables (NF-803 & NF-202) should be used in sophisticated systems. This is where they belong. If you're willing to spend 100€ more for the NF-803 it's a good investment in even better quality. You'll get more out of it in every situation, which is certainly due to the higher quality materials. In the end it is pleasant to see that in a HiFi world, where nobody seems to be afraid of high numbers anymore, in-akustik holds products for lovers of analog music at really great value for money. They are therefore very much in line with the trend" (Hörerlebnis | 92)

- High Speed signal conductor
- Symmetrical design
- High-purity OFC copper
- Braided shielding
- DUO-PE II Insulation
- PE-Network Jacket
- 2-fold PE-Tube Isolation



ITEM NO		LENGTH	SRP
0071840215	Phono Cable NF-803 RCA -> RCA	1,5m	507,00
0071840315	Phono Cable NF-803 SME 90° -> RCA	1,5m	564,00

PHONO CABLE NF-202




- Symmetrical design
- High-purity OFC copper
- Foil shielding and weave sleeve
- DUO-PE II Insulation
- PE-Network Jacket
- PE-Tube Isolation



Precisely because audio signals are so sensitive, we have equipped our Reference phono cable NF-202 with some highly-effective technology: optimum DUO-PE II insulation with air-filled PE tubes, an innovative GAP plug, but also in particular an extremely sophisticated, solid conductor made of high-purity OFC copper, which all ensure uniform transit times and crystal-clear signal transmission. The earth and signal conductors are the same size and arranged symmetrically. The PE network jacket prevents micro-vibrations.

ITEM NO		LENGTH	SRP
007181215	Phono Cable NF-202 RCA -> RCA	1,5m	404,00
007181315	Phono Cable NF-202 SME 90° -> RCA	1,5m	465,00

PHONO CABLE



Special phono cable for record players with the MM/MC system. With a separate ground cable to ground the drive. The symmetrical structure and double shielding protect the sensitive signal from external interference factors. The properties of the high-quality PE insulation and the high copper content ensure a detailed, dynamic and powerful sound.

ITEM NO		LENGTH	SRP
00405107	Phono Cable Premium RCA -> RCA	0,75m	79,00
00405115	Phono Cable Premium RCA -> RCA	1,5m	85,00
00405120	Phono Cable Premium RCA -> RCA	2,0m	91,00



PHONO PRE-AMP



The Premium Phono Pre-Amp is also suitable for the digitisation of record collection or the digitisation of other analogue audio sources, such as cassette decks in conjunction with a PC.

- Switchable from Line In to Line Out
- Compatible with MM and MC systems
- Compatible with Win98/ME/2000/XP7/8
- Compatible with Mac OS 2.1 / 10.2 / 10.4
- Sampling rate up to 48 kHz
- Dimensions: approx. 129 x 75 x 31 mm
- Incl. power supply and USB/Phono/RCA cable

ITEM NO	UNIT	SRP
00415004	1 pc	84,00

RECORD BRUSH



This antistatic carbon-fibre brush, with more than a million extremely fine fibres, is especially effective at removing even the tiniest grains of dust and particles of dirt from the record grooves. The static charge is also greatly reduced. The result is an audibly improved sound experience and a longer life for your record collection.

- Antistatic
- Eliminates static discharge on both sides
- More than a million conductive carbon fibres
- Protective guard with stripping edge for cleaning the fibres
- Reduces crackling noises

ITEM NO	UNIT	SRP
004528001	1 pc	15,39

RECORD COVER PROTECTION & SLIPCOVER




The slipcovers are made of anti-static HDPE (high density polyethylene) that prevents electrostatic charge on the vinyl. This decreases the attraction of new dust particles and reduces crackling during play back. The special format offers a particular advantage. One side is rounded off meaning the record inner sleeves easily slide into LP covers and paper sleeves. This is particularly interesting for collectors who want to preserve the original inside cover.

ITEM NO	UNIT	SRP
004528005	Slip Cover Set of 50	36,49
004528006	Cover Protection Set of 50	37,49

ACCESSORIES HOME HIFI

SLITTED CABLE CONDUIT



Hi-fi, TV and computer devices have to be connected with a great many signal and power cables. These cables can often impair the appearance or become trip hazards. This high-quality fabric cable conduit allows cables to be bundled together in an attractive manner. The conduit is slitted and rolls together in an overlapping manner of its own accord. This means that the cables do not need to be pushed through the conduit but can be conveniently inserted in the conduit over its entire length. This means that it can also accommodate power cables with large (Schuko) plugs.



ITEM NO	LENGTH	SRP
009210719	Premium slitted cable conduit 19 mm Price/m 38m	16,69

CABLE CONDUIT



Hi-fi, TV and computer devices have to be connected with a great many signal and power cables. These cables can often impair the appearance or become trip hazards. This high-quality fabric cable conduit allows cables to be bundled together in an attractive manner. The conduit has been designed so that it can accommodate power cables with large (Schuko) plugs. It can be cut to the required length conveniently with a pair of scissors. One notable feature is that the fabric at the ends does not fray as easily as other conduits.

- Simple to cut
- Stabilised braid
- Reduced fraying at the ends
- Diameter: 25-38 mm

ITEM NO	LENGTH	SRP
009210032	25-38mm Price/m 38m	10,29

DAC CONVERTER | USB POWER



The converter can be used, for example, for the faint sound of a new flat-screen television on an older but sound quality hi-fi player. The stereo output provides to the usual line-level and can be connected, for example, to the AUX or TV input of the amplifier. Power supply using AC adapter or through USB.

- Power supply using AC adapter or through USB
- Audio formats LPCM 44/48/96 kHz
- Supports up to 24 Bit
- Stereo Line Out
- Two inputs (optical I coaxial)
- Universal range of application
- compact design (79x50x25mm)
- S/N ratio > 100dB
- Harmonic distortion: 0.05% max.
- Wolfson-Chip

ITEM NO	UNIT	SRP
00315002	Star DAC	1 pc 70,00

OPTO SPLITTER



The Premium Toslink splitter distributes two optical outputs to one input and vice versa. For instance, if the AV receiver only has one optical input but needs to be connected to a CD player as well as a DVD player with optical output.

ITEM NO	UNIT	SRP
01040100	Opto Splitter	1 pc 26,99

OPTO CONVERTER



Converter for adjusting devices with optical digital outputs to devices with coaxial input or vice versa. For instance, this allows a DVD player with an optical output to be connected to the coaxial input of an AV receiver.

ITEM NO	UNIT	SRP
01040101	Coax > Toslink	1 pc 79,00
01040102	Toslink > Coax	1 pc 86,00

DIE STEREO HÖRTEST CD, VOL. IX



Listen and enjoy the most popular test tracks of the STEREO editors! In order to put HiFi and High End products through their paces, high quality music is required. In collaboration with STEREO - the magazine for HiFi, High End and Music - this compilation presents 15 titles as a listening recommendation of the editors. All titles were remastered extensively by Stockfisch.

MEDIUM	ITEM NO	TITEL
U-HQCD	01679345	Die Stereo Hörtest CD, Vol. IX
CD	0167934	Die Stereo Hörtest CD, Vol. IX
LP Audiophile	01679341	Die Stereo Hörtest CD, Vol. IX

EXZELLENZ RCA



- Metal housing
- 24c gold-plated contacts
- 8 mm cable extension
- suitable e.g. for the Excellence digital, audio or sub cable
- Each 1 pc color coding ring yellow, white, gray included in delivery

ITEM NO	UNIT	SRP
006990061	Exzellenz RCA	bulk 8,99

STAR RCA



- Cable extension: 8,0 mm; 6,0 mm
- Solid metal plug
- Red/Black coding
- 24c gold-plated contacts
- Kink protection and strain relief

ITEM NO	UNIT	SRP
008110	Star RCA	bulk 6,49



RCA F- & Y-ADAPTER



- Red/Black coding
- Solid metal plug
- 24c gold-plated contacts

RCA / JACK PLUG ADAPTER



- 24c gold plated contacts
- 3,5mm Jack Plug -> 2 x RCA (w)

RCA DOUBLE COUPLING



- Red/Black coding
- Solid metal plug
- 24c gold-plated contacts

6,3 | 3,5MM JACK PLUG



- Jack Plug Adapter 3,5mm <-> 6,3mm
- 24c gold-plated contacts
- bulk

ITEM NO	UNIT	SRP
0080421	Set of 2	34,99

ITEM NO	UNIT	SRP
0081381	1 pc	10,89

ITEM NO	UNIT	SRP
0080951	Set of 2	15,89

ITEM NO	UNIT	SRP
0082000	bulk	8,29

EXZELLENZ XLR



- Solid metal plug
- 24c gold-plated contacts
- suitable e.g. for the Excellence XLR Audio or Digital Cable (item no. : 0060500098)

PREMIUM XLR



- Cable extension: 8,0 mm; - Tülle 10,0 mm
- Solid metal plug
- Solid XLR plug/coupling for perfectly symmetrical connections.

SOLDER



RoHS conform silver solder with a high content of silver and excellent flow capacities. A perfect electrical connection and corrosion prone contact is achieved.

ITEM NO	UNIT	SRP
006990111	Exzellenz XLR (f)	bulk 15,39
006990101	Exzellenz XLR (m)	bulk 15,39

ITEM NO	UNIT	SRP
0083331	XLR (m)	bulk 13,49
0083332	XLR (f)	bulk 13,49

ITEM NO	UNIT	SRP
010291	Premium Solder	bulk 45,99



HIGH TECH GEL ABSORBER



High-end and hi-fi systems are a combination of highly precise and delicate devices. Perfectly attuned to each other, they allow music to be played back in outstanding quality. So that all components can work without interference, just like sensitive measuring equipment, they need to be kept free of vibrations and shocks as far as possible. Vibrations are caused in different ways and they can be transmitted by structure-borne and airborne noise. The combination of airborne and structure-borne noise causes all of the components of the hi-fi system to vibrate mechanically. Experiments have shown that this has a considerable impact on the sound. This Reference absorber set provides a solid sound basis. The absorbers have a special gel at their core that absorbs vibration energy. This set contains 12 gel pads for various weight classes for the optimum tuning and decoupling of the devices and loudspeakers.



In order to set up components optimally and decouple them, different gel pads are included in this set. In the table you can find the assignment to the respective weight classes. The values are recommendations based on measurements made by in-akustik.

- Gel pad device weight (per set of 4)
- Green*: up to 5 kg (up to 1.25 kg / absorber)
- Blue: 5–10 kg (1.25–2.5 kg / absorber)
- Green: 10–20 kg (2.5–5.0 kg / absorber)
- Black: 20–40 kg (5.0–10.0 kg / absorber)
- 3 x 4 Hightech-Absorber-Gel
- Top and bottom part made from stainless steel
- Covers four weight classes from 5 to 40 kg
- Felt pads and adhesive pads included
- Dimensions approx. 45 x 11.5 mm (D x H)

ITEM NO		UNIT	SRP
00719220	Referenz High-Tech Gel-Absorber	Set	259,00

*Due to the resonance response, we recommend this gel pad for use in two weight classes.



GEL ABSORBER



Hi-fi systems are a combination of highly precise devices. So that they can work without interference, just like sensitive measuring equipment, they need to be kept free of shocks. These gel absorbers provide a solid sound basis without vibrations. They have a special gel at their core that absorbs vibration energy.



- Plates made of stainless steel
- 4 pcs gel absorber
- Withstands up to 20 kg
- Felt pads and adhesive pads
- Dimensions approx. 45 x 5 mm (D x H)

ITEM NO		UNIT	SRP
008560	Gel-Absorber	Set of 4	90,00

PIC & PLATE MAXI



The solid sub-frequency absorber for linking devices and speakers to one place and reducing vibration. They are adjustable with adhesive pads as well as protective discs for sensitive surfaces.

- Withstands up to 40 kg/Set of 4 -> 10 kg/pc

ITEM NO		UNIT	SRP
0084847	Plate 30x5mm Black	Set of 4	24,99

PLATE MINI



The simple sub-frequency protection plates for linking devices and speakers to one place reduces vibrations.

- Withstands up to 8 kg/pc

ITEM NO		UNIT	SRP
008499	Star Plate Mini	bulk	2,32

XL ABSORBER



Shock absorber made of a specially developed rubber compound for effective and wide-ranging vibration damping of sensitive hi-fi equipment such as CD players, turntables or shelf speakers. In addition, the damping feet are also ideally suited for acoustic decoupling of computers or game consoles, as drive noises are no longer transmitted to the surface on which the devices are standing.

- Special rubber compound for effective resonance damping
- A non-slip surface profile guarantees a stable grip on all surfaces
- Diameter 60 mm | Hight: 5mm
- Withstands up to 50 kg / set

ITEM NO		UNIT	SRP
0085010	Star XL Absorber	Set of 4	12,59

BOLIDE ABSORBER



The Exzellenz bolide shock absorber consists of a special rubber compound and a sophisticated in design for optimum damping of vibration between the devices and the standing position.

- Withstands up to 50 kg / set of 4 -> 12,5 kg/pc

ITEM NO		UNIT	SRP
008550	Bolide Shock Absorber	Set of 4	100,00

ABSORBER DOUBLETEN



The Premium doublette in sandwich design consists of metal discs and special rubber for optimum vibration damping between the devices and the standing position.

- Withstands up to 20 kg / set of 4

The sub-absorber made from a special rubber compound for optimum damping of vibration between the devices and the standing position.

- Withstands up to 8 kg / set of 4

ITEM NO		UNIT	SRP
008509	Premium Doublette	Set of 4	46,99
008508	Star Mini Absorber	Set of 4	29,99





REFERENZ CABLE BASES




The Referenz Cable bases are specifically designed cabling-support systems for the finest stereo systems. The base incorporates absorber gel, too, plus extra rubber bands accommodating the freely suspended cables. This way, Referenz Cable Bases not only absorb vibrations but consistently isolate your cables from the floor, reducing unwanted capacitance and minimizing the load of the electronic system.


Referenz Cable Bases are highly versatile because they support various cabling diameters and floor gaps as well as open and closed cable suspension. With open suspension, the cable rests on a rubber band and allows for mounting at three different heights; with closed suspension, cables are fixed using two rubber bands above and below. This approach is advantageous in that minor movements (for example, when aligning your speakers) will not result in the cable falling from the Base—it is fixed in a defined position. The innovative cable supports thus ensure effective mechanical and capacitive decoupling of your RCA, XLR, and phono cables from the floor. A particularly interesting application of Referenz Cable Bases is the decoupling of your phono cables. This is essential because otherwise vibrations would travel to your tone arm and on to your sensitive pick-up system.



CABLE ROUTED ON THE FLOOR =
HIGH CAPACITANCE



CABLE AT A DISTANCE TO THE FLOOR =
LOW CAPACITANCE



FEATURES

- For mechanical and capacitive isolation of cables
- For cable diameters from 10 to 25 mm
- Hi-tech gel pad in the base
- Natural rubber strips for cable routing
- Open or fixed cable routing
- Diameter: 47 mm
- Total height: 48 mm
- Height levels: 25 / 33 / 44 mm

ITEM NO		UNIT	SRP
00719223	Referenz Cable-Base silver satined	Set of 10	518,00
00719222	Referenz Cable-Base silver satined	Set of 6	325,00



HDMI CABLE	38	49	S-VIDEO CABLE
HDMI WIRELESS	44	49	DISPLAYPORT CABLE
HDMI SWITCH	44	49	SCART CABLE
HDMI SPLITTER	45	49	YUV-/RGB CABLE
ANTENNA CABLE	46	50	ACCESSORIES
VIDEO CABLE	49		



HOME VIDEO

Nowadays, projectors and players deliver perfect playback. Nevertheless, the pictures are often out of focus or faded. There is a reason for this: Blu-ray players emit unbelievably large amounts of information simultaneously at high speed. If the cables are not perfectly designed, the colours and contours fade and the picture is grainy. The wrong cables are the main cause for poor pictures and sound. Or in other words: the quality of your device is only as good as the cables it is used with. Picture cables from in-akustik ease the way for signals and protect them from external interference. For all picture connections.



ULTRA HIGH SPEED HDMI CABLE HDMI 2.1 | 10K | OPTICAL FIBRE | 48 GBPS | 100M



HDMI cable with professional fibre optic technology. This technology facilitates data rates of up to 48 Gbps on a transmission path of up to 100 m. It therefore supports high-resolution 10K formats with 120 Hz as well as HDR. It is the solution for connecting devices with an HDMI 2.1 interface over great distances. Due to the build-in electronics the cable has a signal direction.

- Full HD 1080p 120 Hz 4:4:4 HDR
- UHD 4K 3840 x 2160p 120 Hz 4:4:4 HDR
- UHD 4K 4096 x 2160p 120 Hz 4:4:4 HDR
- UHD 5K 5120 x 2160p 120 Hz 4:4:4 (DSC)
- UHD 8K 7680 x 4320p 120 Hz 4:4:4 HDR (DSC)
- UHD 10K 10240 x 4320p 60 Hz 4:4:4 (DSC)
- UHD 10K 10240 x 4320p 120 Hz 4:2:2 (DSC)
- etc
- Optical Fiber Technology
- Based on HDMI 2.1 specification
- Supports 8K@50/60 Hz
- Supports data rate up to 48 Gbps
- Supports HDCP 2.3
- Supports EDID
- Supports HDR | HDR10 | HDR10+
- Supports 4:4:4 | 4:2:2 | 4:2:0 Color subsampling
- Supports 36 Bit colour depth (3 x 12Bit)
- Supports up to 120 Fps
- Supports DSC (Display Stream Compression)
- eARC up to 30m | ARC up to 50m
- Metal plug
- Plug&play
- Powered by the HDMI port
- no additional power supply necessary
- Signal direction marked
- Easy to install
- CE, REACH, RoHS compliant
- Cable diameter: 4mm



ITEM NO	LENGTH	SRP	ITEM NO	LENGTH	SRP
009245001	1m	280,00	009245015	15m	426,00
009245002	2m	291,00	009245020	20m	471,00
009245003	3m	303,00	009245030	30m	560,00
009245005	5m	325,00	009245050	50m	728,00
009245008	8m	359,00	009245070	70m	841,00
009245010	10m	381,00	009245100	100m	897,00



HIGH SPEED HDMI CABLE

HDMI 2.0B | 4K | OPTICAL FIBRE | 24 GBPS | UP TO 100M




HDMI 2.0b cable with professional fibre optic technology. This technology facilitates data rates of up to 24 Gbps on a transmission path of up to 100 m. It therefore supports high-resolution 4K formats with 50 or 60 Hz and is the solution for connecting devices with an HDMI 2.0b interface over great distances.



INAKUSTIK PROFI HDMI LWL € 440+
Testurteil: überragend
Preis/Leistung: befriedigend
 VIDEO Magazin | 12-2017

- Fibre optic technology
- 4K@50/60 Hz up to 100 m
- Supports HDMI 2.0b with 24 Gbps
- Supports HDCP 2.2
- Supports EDID
- eARC up to 30m | ARC up to 50m
- Solid metal plug
- Plug&Play
- Power supply via the HDMI interface
- No separate power supply unit required
- Running direction marked
- Cable diameter of just 4 mm
- Easy to lay
- CE, REACH, RoHS conformant



ITEM NO	LENGTH	SRP
009241001	1m	202,00
009241002	2m	213,00
009241003	3m	235,00
009241005	5m	258,00
009241008	8m	280,00
009241010	10m	303,00
009241015	15m	348,00
009241020	20m	359,00
009241030	30m	404,00
009241050	50m	504,00
009241070	70m	606,00
009241100	100m	706,00


HIGH SPEED HDMI CABLE

HDMI 2.0B | 4K | OPTICAL FIBRE | 24 GBPS | ARMoured | UP TO 100M




Professional HDMI 2.0b cable with fibre optic technology for data rates of up to 24 Gbps with a transmission distance of up to 100 m. The cable therefore supports high-resolution 4K formats with 50 or 60 Hz, 4:4:4 chroma subsampling as well as HDR, and is the solution for connecting devices with an HDMI 2.0b interface over large distances. Thanks to the solid armouring made of a steel helix and Kevlar threads, the cable is very resistant and can withstand tensile loads of up to 100 kg and even 200 kg for a short time. In addition, the solid metal connectors are protected by a plastic sleeve with a screw cap during transport and assembly/disassembly. The cable is therefore suitable for rough use with recurring assembly and disassembly cycles, e.g. in show and stage applications.

SPECIAL FEATURE: Reinforcement made of Stend coil and Kevlar threads



- Fibre optic technology
- Robust design
- Reinforcement made of a steel helix and Kevlar threads
- Plastic sleeve with screw cover to protect the plugs
- Supports HDMI 2.0B up to 24 Gbps
- eARC up to 30m | ARC up to 50m
- Supports HDCP 2.2
- Supports EDID
- Supports High Dynamic Range (HDR)
- Supports 4K@50/60 Hz 4:4:4 up to 100 m
- Solid metal connectors
- Plug & play
- Power supply via the HDMI interface
- Low power consumption (<0.25 watts)
- No separate power supply unit required
- Transmission direction marked
- Cable diameter: approx. 5.8 mm
- CE, REACH, RoHS compliant



ITEM NO	LENGTH	SRP
009244001	1 m	258,00
009244002	2 m	280,00
009244003	3 m	291,00
009244005	5 m	314,00
009244008	8 m	370,00
009244010	10 m	392,00
009244015	15 m	460,00
009244020	20 m	482,00
009244030	30 m	560,00
009244050	50 m	740,00
009244070	70 m	908,00
009244100	100 m	1.110,00

HIGH SPEED HDMI CABLE

HDMI 2.0B | 4K | OPTICAL FIBRE | 24 GBPS | HDMI-ADAPTER | UP TO 100M




HDMI cable with professional fibre optic technology. This technology facilitates data rates of up to 24 Gbps on a transmission path of up to 100 m. The cable therefore supports high-resolution 4K formats with 50 or 60 Hz as well as HDR and is the solution for connecting devices with an HDMI 2.0b interface over great distances. The compact micro HDMI plugs are another special feature of this cable. They can be conveniently pushed through almost any empty conduit. The scope of delivery includes the corresponding adapters to type A HDMI or DVI-D. The plugs and adapters are made of metal, have a precise guide rail and can be fastened together so they form a solid mechanical unit after installation. Important: The running direction must be complied with!




ITEM NO (VERSION 1)	LENGTH	SRP
0092431010	10m	370,00
0092431015	15m	404,00
0092431020	20m	426,00
0092431030	30m	471,00
0092431050	50m	572,00
0092431070	70m	684,00
0092431100	100m	784,00

ITEM NO (VERSION 2)	LENGTH	SRP
0092432010	10m	392,00
0092432015	15m	426,00
0092432020	20m	448,00
0092432030	30m	494,00
0092432050	50m	594,00
0092432070	70m	696,00
0092432100	100m	796,00


VERSION 1



VERSION 2



Variante:



- Fibre optic technology
- Micro HDMI plugs for installing in empty conduits
- The plug is 14.5 mm wide (diagonal) and fits through so-called M20 tubes (hoses with an inner diameter of around 17mm)
- Supports HDMI 2.0b with 24 Gbps
- Supports HDCP 2.2
- EDID compatible
- High Dynamic Range (HDR)
- 4K@50/60 Hz 4:4:4 to 100 m
- eARC up to 30m | ACR up to 50m
- Solid metal plug
- Including an HDMI or DVI-D adapter
- Plug & play
- Power supply via the HDMI interface
- No separate power supply unit required
- Running direction marked
- Cable diameter of just 4 mm
- Easy to lay
- CE, REACH, RoHS compliant





ULTRA HIGH SPEED HDMI CABLE

ULTRA HD | 10K | 8K | 4K | 120 HZ | 48 GBPS | HDR10+



This HDMI Organisation-certified ultra high-speed HDMI cable from the in-akustik Premium series guarantees crystal clear images and dynamic high-definition sound with data rates of 48 Gbps. Enjoy films and games in ultra HD 10k resolution as well as refresh rates of up to 120 Hz. The supported audio formats such as DTS Master, DTS:X, Dolby True HD or Dolby Atmos enable an unmatched home cinema experience. The triple shielding protects sensitive data from external interference. Combined with the 24 k gold-plated connectors and the tin-plated, extra-thick 28 AWG twisted pair data cables made of high-purity OFC copper, the cable guarantees interference- and loss-free signal transmission for uncompromising picture and sound quality. Packed with groundbreaking features such as HDR10+, Dolby Vision or Enhanced ARC (eARC), the cable supports the latest HDMI 2.1 standard and is of course downwards compatible with older HDMI versions. It is specifically designed to connect digital AV components such as set-top boxes, Blu-ray players, AV receivers, TVs, projectors and gaming consoles such as the Xbox One, Xbox One S, Xbox One X, PS3, PS3 Slim, PS4, PS4 Pro or Nintendo Switch and upcoming next-generation consoles such as the Xbox Series X or PlayStation 5 (PS5).

- 3-fold shielding
- Conductors made of high-purity OFC copper
- Extra thick 28 AWG twisted pair data cables
- Tinned OFC copper conductors for additional protection against oxidation
- Additional protective textile jacket
- Supports HDMI 2.1
- Supports 48Gbps
- Supports 10K | 8K | 4K | Full HD
- Supports 120 Hz | 120 FPS
- Supports ARC, eARC, CEC
- Supports HDR, HDR10+, HLG HDR and Dolby Vision
- HDCP 2.3
- Downwards compatible with HDMI2.0 etc.
- 24 c gold-plated contacts
- Ultra Certified Cable
- DSC (Display Stream Compression)
- QMS (Quick Media Switching)
- QFT (Quick Frame Transport)
- VRR (Variable Refresh Rate)
- ALLM (Auto Low Latency Mode)

RESOLUTION FORMATS

- Full HD 1080p 120 Hz 4:4:4 HDR
- UHD 4K 3840 x 2160p 120 Hz 4:4:4 HDR
- UHD 4K 4096 x 2160p 120 Hz 4:4:4 HDR
- UHD 5K 5120 x 2160p 120 Hz 4:4:4 (DSC)
- UHD 8K 7680 x 4320p 120 Hz 4:4:4 HDR (DSC)
- UHD 10K 10240 x 4320p 60 Hz 4:4:4 (DSC)
- UHD 10K 10240 x 4320p 120 Hz 4:2:2 (DSC)
- etc

HDMI-SPECIAL



ITEM NO		LENGTH	SRP
00423520	Ultra High Speed HDMI <=> Ultra High Speed HDMI	2,0m	45,99
00423530	Ultra High Speed HDMI <=> Ultra High Speed HDMI	3,0m	54,00

ULTRA HIGH SPEED HDMI CABLE

ULTRA HD | 10K | 8K | 4K | 120 HZ | 48 GBPS | HDR10+



This officially certified cable guarantees crystal clear images (UHD 10K), smooth image changes (120 Hz) and dynamic HD sound for films and games. Triple shielding and tin-plated OFC copper wires (28 AWG) guarantee interference-free and long-lasting signal transmission

ITEM NO		LENGTH	SRP
00324610	Ultra High Speed HDMI <=> Ultra High Speed HDMI	1,0m	20,49
00324615	Ultra High Speed HDMI <=> Ultra High Speed HDMI	1,5m	23,49
00324620	Ultra High Speed HDMI <=> Ultra High Speed HDMI	2,0m	25,99

- 3-fold shielding
- Conductors made of high-purity OFC copper
- Supports HDMI 2.1
- Supports 48Gbps
- Supports 10K | 8K | 4K | Full HD
- Supports 120 Hz | 120 FPS
- Supports ARC, eARC, CEC
- Supports HDR, HDR10+, HLG HDR and Dolby Vision
- HDCP 2.3
- Downwards compatible with HDMI2.0 etc.
- 24 c gold-plated contacts
- Ultra Certified Cable
- DSC (Display Stream Compression)
- QMS (Quick Media Switching)
- QFT (Quick Frame Transport)
- VRR (Variable Refresh Rate)
- ALLM (Auto Low Latency Mode)

- Full HD | 120 Hz | 4:4:4 | HDR
- UHD 4K | 120 Hz | 4:4:4 | HDR
- UHD | 5K | 120 Hz | 4:4:4 | (DSC)
- UHD | 8K | 120 Hz | 4:4:4 | HDR (DSC)
- UHD | 10K | 60 Hz | 4:4:4 | (DSC)
- UHD | 10K | 120 Hz | 4:2:2 | (DSC)



HDMI CABLE

HIGH SPEED HDMI 2.0B CABLE WITH ETHERNET

EXZELLEENZ



HIGH SPEED HDMI 2.0B* CABLE WITH ETHERNET

PREMIUM



* up to 5,0m

ITEM NO		LENGTH	SRP
0062443015	High Speed HDMI <=> High Speed HDMI	1,5m	91,00
006244303	High Speed HDMI <=> High Speed HDMI	3,0m	130,00
006244305	High Speed HDMI <=> High Speed HDMI	5,0m	190,00
0062443075	High Speed HDMI <=> High Speed HDMI	7,5m	325,00
006244310	High Speed HDMI <=> High Speed HDMI	10,0m	379,00
006244312	High Speed HDMI <=> High Speed HDMI	12,5m	434,00
006244315	High Speed HDMI <=> High Speed HDMI	15,0m	488,00

ITEM NO		LENGTH	SRP
00423007	High Speed HDMI <=> High Speed HDMI	0,75m	37,49
00423015	High Speed HDMI <=> High Speed HDMI	1,5m	43,99
0042302	High Speed HDMI <=> High Speed HDMI	2,0m	47,49
0042303	High Speed HDMI <=> High Speed HDMI	3,0m	54,00
0042305	High Speed HDMI <=> High Speed HDMI	5,0m	70,00
0042308	Standard HDMI <=> Standard HDMI	8,0m	90,00
0042310	Standard HDMI <=> Standard HDMI	10,0m	131,00





HIGH SPEED HDMI 2.0B* CABLE WITH ETHERNET | „PIGGYBACK“

PREMIUM



* up to 5,0m

ITEM NO		LENGTH	SRP
00425015	High Speed HDMI <=> High Speed HDMI	1,5m	43,99
0042502	High Speed HDMI <=> High Speed HDMI	2,0m	47,49
0042503	High Speed HDMI <=> High Speed HDMI	3,0m	54,00
0042505	High Speed HDMI <=> High Speed HDMI	5,0m	70,00
0042508	Standard HDMI <=> Standard HDMI	8,0m	93,00

HIGH SPEED HDMI 2.0B* & STANDARD HDMI CABLE XS VERSION

PREMIUM



ITEM NO		LENGTH	SRP
004246807	High Speed HDMI <=> High Speed HDMI	0,75m	25,99
004246815	High Speed HDMI <=> High Speed HDMI	1,5m	31,49
004246830	High Speed HDMI <=> High Speed HDMI aktiv	3,0m	91,00
004246203	Standard HDMI <=> HDMI Mini C aktiv	3,0m	45,49
004246205	Standard HDMI <=> HDMI Mini C aktiv	5,0m	60,00
004246303	Standard HDMI <=> HDMI Micro D aktiv	3,0m	45,49
004246305	Standard HDMI <=> HDMI Micro D aktiv	5,0m	60,00

- ultra thin (3,6mm)
- active chip (3m/5m)
- highly flexible

* applies to the High Speed HDMI <=> High Speed HDMI version

PROFESSIONAL HDMI 2.0B* CABLE

INSTALLATION



High-quality, 3 fold shielded HDMI cable with stable and compact HDMI plugs (approx. 19.5x11.0x33.0 mm incl. kink protection) for professional installation. Item check on the basis of the HDMI1.4 or HDMI2.0 specifications. Construction fully compliant to CE and RoHS regulation.

- **0,75m - 5m:** HDMI2.0 Cable
- Data rate: 18 Gbps
- Supports 4K60Hz 4:4:4 HDR
- AWG28 Cable
- Diameter: 7mm
- **8,0m - 10,0m:** HDMI1.4 Cable
- Data rate: 10.2 Gbps
- Supports 4K30Hz 4:4:4 bzw. 4K60Hz 4:2:2
- AWG26 Cable
- Diameter: 8mm

* up to 5,0m

ITEM NO		LENGTH	SRP
0092420075	High Speed HDMI <=> High Speed HDMI	0,75m	18,19
009242015	High Speed HDMI <=> High Speed HDMI	1,5m	20,49
00924203	High Speed HDMI <=> High Speed HDMI	3,0m	25,99
00924205	High Speed HDMI <=> High Speed HDMI	5,0m	31,49
00924208	Standard HDMI <=> Standard HDMI	8,0m	66,00
00924210	Standard HDMI <=> Standard HDMI	10,0m	72,00

STANDARD MINI HDMI CABLE

PREMIUM



ITEM NO		LENGTH	SRP
00423215	Standard HDMI <=> HDMI Mini C	1,5m	59,00
0042323	Standard HDMI <=> HDMI Mini C	3,0m	71,00
00423307	Standard HDMI <=> HDMI Micro D	0,75m	33,99

HDMI CABLE

HIGH SPEED HDMI 2.0B* CABLE WITH ETHERNET



* up to 3,0m


ITEM NO		LENGTH	SRP
00324507	High Speed HDMI <=> High Speed HDMI	0,75m	15,89
00324515	High Speed HDMI <=> High Speed HDMI	1,5m	18,69
00324530	High Speed HDMI <=> High Speed HDMI	3,0m	24,99
00324550	Standard HDMI <=> Standard HDMI	5,0m	37,49
00324575	Standard HDMI <=> Standard HDMI	7,5m	47,99
003245100	Standard HDMI <=> Standard HDMI	10,0m	57,00

HDMI WIRELESS

WIRELESS HDMI KIT



- Additional HDMI output on the transmitter
- Transmission up to 30m
- WiFi 5 GHz band
- 128-/256-bit encryption
- Compact design
- Power supply via Micro USB socket
- Latency < 0.5 s
- Dimensions: approx. 85 x 83 x 14mm
- Weight: approx. 400 g (set)



ITEM NO		UNIT	SRP
00912003	Exzellenz Wireless HDMI Kit	1 Set	399,00

HDMI SWITCH

MHL-HDMI SWITCH 3 -> 1



MHL (Mobile High-DefinitionLink) is the new AV interface of mobile devices. Smartphones and tablet PCs that support this standard use their Micro USB port for this. With the appropriate adapter HD picture and sound quality can be played back on a TV with HDMI input. In the Premium MHL / HDMI switch box a MHL adapter is included. MHL - Front smartphones and tablet PCs can be connected if they support the MHL standard. In addition, the switch box has three HDMI inputs that dominate all current HDMI formats.

- 1 MHL and 3 HDMI inputs
- Range up to 750MHz / 7,5Gbps (HDMI)

ITEM NO	UNIT	SRP
00424505	1 Set	179,00

HDMI SWITCH 3 >1 HIGH SPEED



- Output with HDMI cable (50 cm)
- Automatic switching
- Downwardly compatible
- Supports uncompressed audio such as LPCM
- Supports compressed audio such as DTS Digital, Dolby Digital
- Supports HD audio formats such as DTS-HD and Dolby True HD

ITEM NO	UNIT	SRP
0032450314	1 Set	79,00




HDMI SPLITTER 1 >2 HIGH SPEED



- Supports uncompressed audio formats like LPCM
- Supports compressed audio formats such as DTS, Dolby Digital
- Supports HD audio formats such as DTS-HD or Dolby True HD
- Plug & Play
- Compact size (80 x 50 x 20 mm)
- Weight: 100 g

ITEM NO	UNIT	SRP
004245012 HDMI Splitter 1 > 2 High Speed 4K	1 Set	171,00

HDMI SPLITTER 1->2 SCALER HIGH SPEED



ITEM NO	UNIT	SRP
004245142 HDMI Splitter 1 > 2 Scaler High Speed	1 Set	233,00

HDMI SPLITTER 1 -> 8 HIGH SPEED



- Data rate: 10,2 Gbps
- 230VAC respectively 5V / 12W
- 257 x 25 x 120mm
- Cable length IN: 20m; OUT: 20m

ITEM NO	UNIT	SRP
004245118 HDMI Splitter 1 > 8 High Speed	1 Set	469,00

HDMI SPLITTER 1 -> 2 HIGH SPEED



- Data rate: 3 x 2,25 Gbps / 225 MHz
- 230VAC respectively 5V or via HDMI
- 63 x 18 x 54mm
- Cable length OUT: 20m


ITEM NO	UNIT	SRP
003247012 HDMI Splitter 1 > 2 High Speed	1 Set	131,00



UHD ANTENNA CABLE | 120 DB



The Excellence UHD antenna cable has been specially designed for the high requirements of receiving ultra- high resolution television formats (4K UHD). The 4-fold shielding (120 dB) protects the sensitive signal content from external interferences and ensures excellent picture and sound quality. The cable is fitted with high-quality solid metal plugs suitable for connecting DVB-T/-S/-C receivers and TV sets. The 24 carat gold-plated contacts reduce contact resistance to a minimum.



- 120 dB screening
- 4-fold shielding
- Future-proof 3 GHz
- Ultra HD 2160p (4K x 2K Video)
- Digital Video Broadcasting
- Solid core
- Low-loss PE insulation
- 24c gold-plated contacts

ITEM NO		LENGTH	SRP
0062630098	On Spool Price/m	from 1m	12,89
006263015	Coax (m) > Coax (f)	1,5m	68,00
00626303	Coax (m) > Coax (f)	3,0m	80,00
00626305	Coax (m) > Coax (f)	5,0m	102,00
006263075	Coax (m) > Coax (f)	7,5m	159,00
00626310	Coax (m) > Coax (f)	10,0m	179,00
006264015	F-Plug	1,5m	78,00
00626403	F-Plug	3,0m	87,00
00626405	F-Plug	5,0m	116,00



HDTV ANTENNA CABLE A++ | DIN EN 50117-2-4



Professional high-end antenna cable, class A++. The cable meets the requirements of the standard DIN EN 50117-2-4 and has been recommended and approved by Deutsche Telekom. It is ideal for setting up BK systems for HD TV and supports the return channel (cable internet)

- HD-TV Antenna Cable, class A++
- Meets the norm DIN EN 50117-2-4
- Recommended and approved by Deutschen Telekom
- Suitable for return channel (Internet)
- Expanded PE dielectric
- Inner conductor: 1.0 mm bare copper
- Exterior diameter: 6.8 mm +/-0.2 mm
- Bonded film -> suitable for compression connectors etc.
- Small bending radius (50 mm)

- Capacitance: (pF/m) 55
- Velocity factor (v/c): 0.85
- Low signal attenuation
- Weight: 52 kg/km
- Descending metre imprint

ITEM NO		UNIT	SRP
006260036	Professional Antenna Cable A++ Price/m	250m	5,69
00652123	Professional F-Plug	Bulk	2,09
00652124	Coax-Tool	Bulk	26,49

HDTV ANTENNA CABLE
120 DB | HALOGEN FREE

This HDTV antenna cable is especially designed for the sophisticated requirements of high resolution television formats (HDTV). The 4-fold 120 dB shielding protects the sensitive signal contents and ensures excellent picture quality. It is suitable for the installation of BK, SAT and cable TV systems, and can be used indoors and outdoors. It can also be used for connecting DVB-T/-S/-C receivers.

- Cable diameter: 7,0 mm



ITEM NO		UNIT	SRP
006260006	HDTV Antenna cable halogen free Price/m	100m	3,16

HDTV ANTENNA CABLE
120 DB

This HDTV antenna cable is especially designed for the superior requirements of high resolution television formats (HDTV). The 4-fold 120 dB screening protects the sensitive signal content and ensures excellent picture quality. It is suitable for installing BK, SAT and cable TV systems and can be used indoors and outdoors. It can also be used for connecting DVB-T/-S/-C receivers.


- Cable diameter: 7,0 mm



ITEM NO		UNIT	SRP
00626000	Exzellenz HDTV Antenna cable Price/m	100m	3,52
0062600098	Exzellenz HDTV Antenna cable Price/m	500m	3,73

HDTV ANTENNA CABLE 100 DB

PREMIUM



ITEM NO		LENGTH	SRP
004261015	Coax (m) > Coax (f)	1,5m	28,49
00426103	Coax (m) > Coax (f)	3,0m	33,49
00426105	Coax (m) > Coax (f)	5,0m	38,99
004261075	Coax (m) > Coax (f)	7,5m	48,49
00426110	Coax (m) > Coax (f)	10,0m	60,00
004262015	F-Plug	1,5m	30,49
00426203	F-Plug	3,0m	35,49
00426205	F-Plug	5,0m	41,99
00426210	F-Plug	10,0m	56,00

HDTV ANTENNA CABLE 100 DB | 90°

PREMIUM



ITEM NO		LENGTH	SRP
004263015	Coax (m) > Coax (f) 90°	1,5m	28,49
00426303	Coax (m) > Coax (f) 90°	3,0m	33,49
00426305	Coax (m) > Coax (f) 90°	5,0m	38,99
004263075	Coax (m) > Coax (f) 90°	7,5m	48,49
00426310	Coax (m) > Coax (f) 90°	10,0m	60,00

HDTV ANTENNA CABLE 90 DB

STAR



ITEM NO		LENGTH	SRP
003263015	Coax (m) > Coax (f)	1,5m	18,39
00326303	Coax (m) > Coax (f)	3,0m	20,49
00326305	Coax (m) > Coax (f)	5,0m	24,99
003264015	F-Plug	1,5m	22,49
00326403	F-Plug	3,0m	26,49

ANTENNA PLUG

EXZELLEENZ



New high end antenna plug made of solid metal with gold plated contacts. Simple, safe and time-saving „twist-on assembly“.

- suitable e.g. for the Excellence Antenna Cable Art.-No. : 0062630098
- For 7.0 mm cable extension

ITEM NO		UNIT	SRP
006990071	Exzellenz Antenna plug Coax (m)	bulk	8,99
006990081	Exzellenz Antenna plug Coax (f)	bulk	8,99
006990091	Exzellenz Antenna plug F-Plug	bulk	10,29


VIDEO CABLE

VIDEO CABLE



ITEM NO	LENGTH	SRP
0041401	1,0m	29,99
0041403	3,0m	48,49

VIDEO CABLE



ITEM NO	LENGTH	SRP
00316207	0,75m	12,99
00316215	1,5m	16,69
0031623	3,0m	18,89
0031625	5,0m	24,99
00316310	10m	40,49


S-VIDEO CABLE

S-VIDEO CABLE



ITEM NO	LENGTH	SRP
01051101	1,0m	17,69
01051102	2,0m	23,99
01051103	3,0m	29,99
01051105	5,0m	41,49
01051110	10,0m	69,00

S-VIDEO CABLE



ITEM NO	LENGTH	SRP
01011751	1,0m	10,29
01011753	3,0m	15,49
01011755	5,0m	19,99
010117575	7,5m	25,49
010117510	10,0m	32,49
010117515	15,0m	42,99

DISPLAYPORT

DISPLAYPORT



DisplayPort is an interface defined by the VESA (Video Electronics Standards Association). The Excellence DisplayPort cable is fully-wired and has 4 data ducts. Each data duct is designed for a bandwidth of 2.7 Gbit/s. It handles the highest specified data rate of 10.8 Gbit/s.

ITEM NO	LENGTH	SRP
00628015	1,5m	74,00
0062803	3,0m	95,00

SCART CABLE

SCART



ITEM NO	LENGTH	SRP
0042203	3,0m	65,00
0042205	5,0m	95,00
00422075	7,5m	129,00


YUV CABLE

YUV



ITEM NO	LENGTH	SRP
006202007	0,75m	39,99
00620203	3,0m	84,00
00620205	5,0m	111,00
006202075	7,5m	151,00
00620210	10,0m	194,00
00620212	12,0m	228,00
00620215	15,0m	279,00

YUV



ITEM NO	LENGTH	SRP
00320007	0,75m	18,99
00320015	1,5m	27,49
0032003	3,0m	36,99
01012755	5,0m	51,00
010127575	7,5m	69,00
010127510	10,0m	84,00
010127515	15,0m	117,00

HDMI 2.0 REPEATER

★★★★★
EXCELLENZ

- Supports 4K@60Hz 4:4:4 up to 25m
- 4K@30Hz up to 30m
- 1080p up to 50m
- Supports HDCP2.2 & 1.4
- downwardly compatible to HDMI1.4 & 1.3
- No separate power supply required

ITEM NO	UNIT	SRP
00912004	1 pc	104,00

HDMI <> DVI ADAPTER

★★★★★
PREMIUM

- HDMI (m) > DVI-D (w)

ITEM NO	UNIT	SRP
0083241	1 pc	42,99

HDMI ANGLE ADAPTER 90°

★★★★★
PREMIUM

ITEM NO	UNIT	SRP
0090201002	1 pc	15,89

HDMI ANGLE ADAPTER 360°

★★★★★
PREMIUM

This premium HDMI adapter can be bent in any direction you wish. It is ideal for connecting an HDMI cable in narrow spaces, for example behind an LED-TV on the wall, or other components. With gold-plated contacts.

ITEM NO	UNIT	SRP
0045217	1 pc	20,49

HDMI MICRO ADAPTER

★★★★★
PREMIUM

This HDMI adapter allows mobile devices, such as cameras with a micro HDMI connector, to be linked up to a TV using a standard HDMI cable. With gold-plated contacts.

ITEM NO	UNIT	SRP
0045218	1 pc	20,49

ANTENNA PLUGS

★★★★★
EXCELLENZ

New high end antenna plug made of solid metal with gold plated contacts. Simple, safe and time- saving „twist-on assembly“.

- suitable e.g. for the Excellence Antenna Cable Art.-No.: 0062630098
- For 7.0 mm cable extension

ITEM NO		SRP
006990071	Coax (m)	8,99
006990081	Coax (f)	8,99
006990091	F-Plug	10,29



DISPLAYPORT ADAPTER



- 15cm cable length
- Supports Mini DP 1.1
- Supports 1080p
- Supports 225MHz / 2,25Gbps (6,75Gbps total)
- Supports 36 Bit deep color (3 x 12 Bit)
- Power supply over Mini DisplayPort

S-VIDEO PLUG



SCART ADAPTER



- Scart <-> RCA/S-Video; switchable

PROFESSIONAL ANTENNA PLUG



- Professional F-Plug
- Very short and space-saving design
- Easy mounting without screws or crimping
- Suitable for cable #006260036 or other 4.9 / 6.8mm coaxial cable with bonded foil
- Coax tool: suitable for cable #006260036 and plug #00652123
- Coax tool: with wrench to tighten the plug on the devices.

ITEM NO	UNIT	SRP
006285003	1 pc	52,00

ITEM NO	UNIT	SRP
0083409	bulk	34,49

ITEM NO	UNIT	SRP
008323	1 pc	22,49

ITEM NO	UNIT	SRP
00652123	Bulk Plug	2,09
00652124	Bulk Tool	26,49

ANTENNA PLUGS



- Exzellenz antenna plug for antenna cable #0062630098
- For 7.0 mm cable extension
- Simple, safe and time- saving „twist-on assembly“.

ITEM NO		SRP
00652104	Coax (f)	9,69
00652102	Coax (m)	9,69
00652122	F-Plug	4,86

MICHAEL SCHENKER TEMPLE OF ROCK



inakustik presents the World's premiere Music 4K Ultra HD Blu-ray with On A Mission – Live In Madrid.

What on the surface might appear to be a platitude, is a serious invitation for the fans of the "Mad Axeman" and one they are happy to take him up on. Where else could aficionados of high-class guitar rock see such an emotional and energetic show? And one featuring a line-up that leaves connoisseurs of the international music scene rapturously clicking their tongues in appreciation.

During their world tour of 2015/2016, the line-up set up their Temple of Rock in the Joy Eslava theatre in central Madrid. Michael Schenker and his crew chose this unique location with care for the recording of this concert. The musicians clapped along with the fans as they sung along to hits old and new with great enthusiasm. All musical phases of Michael Schenker's career were included and the evening became a joyful party as well as a clear message of how positively Michael Schenker's music can enrich the listener's life.

Michael Schenker played various guitars, including for the first time his new double-neck Flying-M with 2 necks, each with 6 strings, with each neck tuned differently.

MEDIUM	ITEM NO	ARTIST TITEL
U-HQCD	0164193	Michael Schenker Temple Of Rock On A Mission - Live In Madrid

inakustik

3 ▽

IN ▽


REFERENZ AC-3500P

Art.-Nr.: 00716600

in-akustik GmbH & Co. KG
Untermaaten 12-14
40282 Ballreichtun-Verfahren



- 54 POWER FILTER
- 56 POWER BARS
- 57 MAINS CABLE
- 57 POWER CABLE



POWER SUPPLY

Power supplies are the lungs for high-end enjoyment. Power supply cables are increasingly used to carry data. High frequency signals are superimposed on the mains voltage. Normal power cables also function as aerials, picking up the radio frequencies broadcast by mobile phones or PCs. These signals then manifest themselves as interference in the hardware. This is compounded by mains voltage variations and transfer resistances, which impair the power of hi-fi equipment during dynamic peaks. Our power strips, sockets, mains and power cables deliver a clean and stable supply of power from the fusebox to your hi-fi system.

REFERENZ POWER STATION




Where does fine sound begin? Where does it end? Audio enthusiasts have kept asking those questions for ages. As a matter of fact, physical conditions have a considerable impact on the sound quality produced by audio systems. In this, power supply is one of the key factors. In principle, we listen to domestic current modulated by a music signal. This useful signal mixes with modulations or interference from other consumers at your home or even your neighborhood all the time – and this is where sound degradation starts. Countless consumers – in particular, digital devices – and switched-mode power supplies (SMPS) cause heavy distortion in the power system, and their number is still rising. This distortion poses serious problems for your hi-fi components, overlaying your sound like patches of acoustic mist. As the number of hi-fi aficionados running their own power plants is obviously quite low, most devices will almost certainly be fed from a grid under heavy load. So to most of us, this means that sound begins at the power outlet or maybe the fuse box – everything upstream is beyond our control



- Highly efficient centralized parallel filter
- Dampened sub chassis
- Balanced power distribution
- High-end schuko sockets
- High-current power inlet (IEC C20)
- Overvoltage protection
- Supply voltage: 100-250V AC / 50-60Hz
- Operating current (max.): 16 A
- Input power (max.): 3,680 W (230VAC / 16 Ampere)
- All-pole disconnection
- Weight: approx. 12.8 kg
- 450 mm × 370 mm × 160 mm (W × D × H)

PARALLEL FILTER

Therefore, we are bound to filter out interference from the supplied power; traditional filters, however, are notorious dynamics “guzzlers”, which is particularly true for serial circuits: inductors inserted into the feed line definitely increase the transition resistance and hamper dynamic pulse currents. The Referenz AC-3500P pursues a different approach: it implements a highly efficient parallel filter perfectly attuned to the audiophile’s needs. The filter leads off all interference from both the power system and the connected devices themselves without restricting the supply. Add to this the dampened sub chassis that reduces AC-3500P mechanical vibrations of the filter components caused by the 50-Hz grid frequency. In addition, the star-shaped distribution topology ensures uniform supply of all connected units. This way, the Referenz Power Station AC-3500P becomes a key factor to a fine yet powerful sound



The technical design is housed in a stout metal enclosure with a front panel of silver or black anodized brushed aluminum. Six high-quality power sockets are available at the rear panel. The centrally placed high-current power inlet (IEC C20) allows for easy replacement of the supply cable – for example, with a longer one. The built-in surge suppressor protects your precious devices from voltage peaks, and you can conveniently switch all power sockets on and off using the power key on the front panel. An indirect LED light located at the front-panel bottom shows the current operational status: white is for the standby mode while blue indicates that the Power Station is on and the power sockets are active.

ITEM NO		SRP
00763500	Referenz AC-3500P Silver	1.944,00
007635007	Referenz AC-3500P Black	2.061,00
07635007US	Referenz AC-3500P Black US-Version	2.461,00

PRESS

"This is not a voodoo, but one of the best line filters that we have ever tested. 1600 euros is a worthwhile investment for any system." Audio 03-2020

„We have seen many phony. They promised holy water and supplied tap water. In-akustik shows what a good power supply filter can do. The sound gain was clear, even outstanding. There is no better way to improve the high end. We are critical - but here we give a clear high-light." stereoplay 07-2019



POWER BAR AC-2502-SF8

★★★★★
REFERENZ




The in-akustik mains cables and power strips filter the current and deliver "clean" currents for your HiFi system. Use of the best materials and excellent workmanship guarantee maximum dynamics, even for extreme loads. Complete screening and a special filter prevent radio frequencies from being received which would turn the cable into an aerial. Solid line bars in the power strips distribute the power homogeneously to all outlets.

Furthermore, the sockets are divided into two groups with the AC-2502-SF8 power strip. Groupe 1: The two grey sockets are directly and permanently connected to the mains supply. This means that power amplifiers, active subwoofers or other power-hungry devices that should not be disconnected from the mains, can remain connected. Groupe 2: The six black sockets can be separated from the mains supply using a switch. The additional mains filter makes this group especially suitable for source devices such as CD players, preamplifiers, phono pre-amps and other precision electronics.

ITEM NO		LENGTH	SRP
00716402	Referenz Power Bar AC-2502-SF8	1,5m	751,00
00716403	Referenz Power Bar AC-2502-SF8	3,0m	811,00


3 X 2,5 MM² CABLE | FOIL SHIELDED

So that no new interference occurs because of the antenna effect of the cables, the power cable and the power bar are fully screened and shielded. Thus, a cleaned current is supplied to the appliances. The electronics can once more deliver the highest precision entirely unhampered.



IN-PLUG FILTER

A ferrite filter is integrated in the plug of the power bar. This In-Plug Filter blocks interference from the network directly at the socket. The filter is manufactured from a special high-density ferrite that works extremely effectively in the smallest of spaces. A further advantage is that all the live wires of the power cords are led directly through this ferrite. Power losses through additional nips or solder points are eliminated.



POWER BAR AC-2502-P8 & AC-1502-P6

★★★★★
REFERENZ



POWER BAR AC-25.6

★★★★★
EXZELLENZ



The Referenz power bars filter unwanted interference out of the power supply, without introducing additional source impedance. Thanks to the use of high-quality materials and excellent workmanship, they provide maximum dynamics, even for extreme loads. Their full shielding and special filters prevent radio frequencies from being received. Solid power bars in the power strips distribute the power homogeneously to all outlets.

- Fully shielded metal housing
- Foil shielding and additional shielding wire
- In-Plug Filter in the AC plug; 2Y-Filter in the power bar
- Power bar (8 mm²) for even power distribution
- Phase marking
- VDE- und CE conform
- 3 x 2,5 mm² (P8); 3 x 1,5 mm² (P6)
- 8 sockets (P8); 6 sockets (P6)
- Safety protection
- PE-Network Jacket
- Includes phase tester

ITEM NO		LENGTH	SRP
00716302	Referenz Power Bar AC-2502-P8	1,5m	555,00
00716303	Referenz Power Bar AC-2502-P8	3,0m	614,00
00716202	Referenz Power Bar AC-1502-P6	1,5m	451,00
00716203	Referenz Power Bar AC-1502-P6	3,0m	526,00



A stable power supply forms the basis of good quality pictures and sound. Unfortunately, a great deal of quality is often lost due to high contact resistance when using cheap power bars. This is characterised by limited dynamics and slurred bass even at low and medium volumes. The Excellence AC 25.6 power bar consists of high quality, perfectly matched materials such as the solid power plug and the 3 x 2.5 mm² strong power cord. In connection with the solid 4 mm² copper power bars in the strip, the setup ensures low contact resistance and enables the system to reach maximum performance. The strip is complemented by its solid aluminium housing which also has a shielding effect. Power bar in accordance with DIN VDE 0620-2-1.

- 3 x 2,5 mm² cable | 1,65m
- Aluminium housing
- 4mm² copper busbar
- 16A nominal current
- 3680 Watts max.
- Childproof
- 230 V AC nominal voltage

ITEM NO		LENGTH	SRP
006170615	Exzellenz Power Bar AC - 25.6	1,65m	205,00



MAINS CABLE AC-2502



Fundamentally, the output of a hi-fi system is nothing other than modulated household electricity. So this should get to the device with the minimum impediment. Extreme current peaks are the greatest challenge for mains connection cables. They are caused by the connected devices as they convert alternating to direct current. These extreme current peaks cause a whole series of unwanted effects, which is why the power cable is so important. The Referenz AC-2502 power cable is equipped for this demanding task and is designed to connect highquality hi-fi and high-end audio systems. As well as having 3.3 times the prescribed minimum conductor cross-section, it is also equipped with shielding to protect the sensitive audio components in the system from the interference fields caused by the current peaks.

SAFETY FIRST!

But for all the importance of high-quality sound, safety plays a particular role with this category of cable. That's why every AC-2502 undergoes an insulation and high voltage test in addition to the standard function test. The results are recorded and each cable is given a unique serial number.

KEY-FEATURES

- Pure copper wires
- 3 x 2.5 mm² cross section
- Protective conductor protection class 1)
- Dense shielding
- CE conformant
- With certificate

ITEM NO	LENGTH	SRP
007627010 Referenz AC-2502 SCHUKO - C13	1,0m	309,00
007627015 Referenz AC-2502 SCHUKO - C13	1,5m	321,00
007627020 Referenz AC-2502 SCHUKO - C13	2,0m	332,00
007627030 Referenz AC-2502 SCHUKO - C13	3,0m	354,00

ITEM NO	LENGTH	SRP
007627110 Referenz AC-2502 SCHUKO - C19	1,0m	309,00
007627115 Referenz AC-2502 SCHUKO - C19	1,5m	321,00
007627120 Referenz AC-2502 SCHUKO - C19	2,0m	332,00
007627130 Referenz AC-2502 SCHUKO - C19	3,0m	354,00

MAINS CABLE AC-1502 |
AC-1502F | AC-2502F

The Referenz mains cable ensures a stable and clean supply of power. The shielding provides reliable protection from interference and the innovative in-plug filter provides additional decoupling for the equipment.

- Additional shielding wire (CU tin-plated; 1 x 1.5 mm²)
- Ferrite filter in the plug (in-plug filter)
- Phase markings
- PE-Network Jacket
- Foil shielding
- Conforms to VDE and CE

ITEM NO	LENGTH	SRP
00716101 Schuko > rubber connector; 3 x 1,5 mm ²	1,0m	211,00
00716102 Schuko > rubber connector; 3 x 1,5 mm ²	1,5m	227,00
00716103 Schuko > rubber connector; 3 x 1,5 mm ²	3,0m	255,00
00762552 AC-2502F; on spool 13,0 mm; 3 x 2,5 mm ² ; (Price/m)	50m	28,99
00762512 AC-2502F; 10m ring 13,0 mm; 3 x 2,5 mm ²	10m	305,00
00762522 AC-2502F; 20m ring 13,0 mm; 3 x 2,5 mm ²	20m	590,00
00761512 AC-1502F; 10m ring 11,0 mm; 3 x 1,5 mm ²	10m	193,00
00761522 AC-1502F; 20m ring 11,0 mm; 3 x 1,5 mm ²	20m	381,00

POWER CABLE AC-2503M



Electrical installations in buildings are usually carried out expertly, but at the minimum expense. This means that the cables from the fuse box usually pass through a number of junction boxes and terminals before reaching the sockets. Each terminal means additional contact resistance and additional load from other appliances in the room. This leads to losses and disturbances in the power supply. Ideally, there should be a separate cable from the fuse box to the socket of the hi-fi system. The Referenz AC-2503M is perfect for this application. In addition to its large conductor cross-section of 3 x 2.5 mm², it has a shield which protects the components from electromagnetic interference from the fuse box onwards.

- Large cross-section 3 x 2.5 mm²
- Pure copper conductor
- Foil shield
- Auxiliary wire for easily connecting the shield
- Flame retardant as per EN 60332-1-2
- CE compliant
- Rated voltage: 300 / 500 V
- Test voltage: 2000 V
- Bending radius: min. 50 mm.
- Temperature range: -40 to + 70 °C

ITEM NO	LENGTH	SRP
007622503 Referenz AC-2503M Price/m	50m	10,29



JACK CABLE

HEADPHONE EXTENSION

JACK PLUG ADAPTER

60

60

60

62

62

USB CHARGING ADAPTER

HEADPHONE AMP



MOBILE & HEADPHONE

The connection of portable devices such as MP3 players, smartphones, iPod, iPad, iPhone, or tablet PCs with the hi-fi system, high-quality headphones or other AV components becomes increasingly important. As with classic hifi applications, it also depends on the right connection. To transfer the sensitive signals with minimal losses, material selection, design and cable shielding are as important as for audio or digital cables.



JACK CABLE

3,5 | JACK CABLE



ITEM NO	LENGTH	SRP
004101005	0,5m	21,99
0041010075	0,75m	23,49
004101015	1,5m	26,99
00410103	3,0m	33,99

3,5 | JACK CABLE



ITEM NO	LENGTH	SRP
003101005	0,5m	8,99
0031010075	0,75m	9,59
003101015	1,5m	10,89
00310103	3,0m	12,89

3,5 | JACK CABLE



ITEM NO	LENGTH	SRP
004104005	0,5m	21,99
0041040075	0,75m	23,49
004104015	1,5m	26,99
00410403	3,0m	28,49


3,5 | JACK CABLE



ITEM NO	LENGTH	SRP
003104005	0,5m	10,29
0031040075	0,75m	10,89
003104015	1,5m	11,49

HEADPHONE EXTENSION


3,5 | HEADPHONE EXTENSION CABLE



* inkl. 6,3 adapter

ITEM NO	LENGTH	SRP
00410202	2,0m	28,49
00410203	3,0m	36,49
00410205	5,0m	46,99
004102075	7,5m	52,00
00410210	10,0m	60,00

3,5 | HEADPHONE EXTENSION CABLE




ITEM NO	LENGTH	SRP
003105015	1,5m	11,49
00310503	3,0m	13,49
00310505	5,0m	15,39

JACK PLUG ADAPTER



ITEM NO	LENGTH	SRP
00410212	20cm	28,99

JACK PLUG ADAPTER



ITEM NO	LENGTH	SRP
00310302	10cm	12,29

- 3,5 mm Jack Plug -> 2 x 3,5mm Jack Plug (f)

- 3,5 mm Jack Plug -> 2 x 3,5mm Jack Plug (f)



6,3 | HEADPHONE EXTENSION CABLE



The highly complex, dual symmetrical structure of the Excellence headphones extension cable in conjunction with the very densely woven shielding protects the intricate audio signals optimally against external interference that is emitted from smartphones or other electrical devices, for instance. The silver-plated conductors transmit the analogue music signal precisely and enable exceptionally crystal clear and dynamic sound even for high-resolution audio formats. The 24-carat gold-plated contacts ensure optimum contact and minimal transition resistance for low-loss transmission of the music signal.



- Doublesymmetrical Design
- Braided shielding
- Low-loss PE insulation
- Silver-plated conductors
- Wires made of high-purity OFC copper
- Precisely fitting solid metal conductor
- 24c gold-plated contacts
- Textile Jacket



„The headphone extension from in-akustik's Excellence series guarantees optimal signal transport. Thanks to its very complex, double-symmetrical structure in conjunction with the high-density shielding braid the signal is protected from external interferences [...] It is an extremely high-quality solution when your headphone cable is too short.“

ITEM NO	LENGTH	SRP
006046015 6,3 Jack Plug (m) <> 6,3 Jack Plug (f)	1,5m	86,00
00604603 6,3 Jack Plug (m) <> 6,3 Jack Plug (f)	3,0m	104,00
00604605 6,3 Jack Plug (m) <> 6,3 Jack Plug (f)	5,0m	130,00



JACK PLUG ADAPTER


PHONE PLUG ADAPTER



- 3,5 mm Phone Plug -> 2 x RCA

ITEM NO	LENGTH	SRP
004100015	1,5m	26,99
00410003	3,0m	33,99
00410005	5,0m	42,99

PHONE PLUG ADAPTER



- 3,5 mm Phone Plug -> 2 x RCA

ITEM NO	LENGTH	SRP
003100005	0,5m	8,99
0031000075	0,75m	9,59
003100015	1,5m	10,29
00310003	3,0m	12,89
00310005	5,0m	16,29
00310007	7,0m	20,49
00310010	10,0m	22,49

3,5MM JACK PLUG -> RCA-ADAPTER



- 24c gold plated contacts
- 3,5mm Jack Plug -> 2 x RCA (f)

ITEM NO	UNIT	SRP
0081381	1 pc	10,89

6,3 | 3,5MM JACK PLUG ADAPTER



- Jack Plug Adapter 3,5mm <-> 6,3mm
- 24c gold-plated contacts
- bulk

ITEM NO	UNIT	SRP
0082000	bulk	8,29

USB CHARGING ADAPTER

USB CAR CHARGER



- Charging time reduced by up to 60%
- Automatic device recognition
- Automatic adjustment of the output voltage
- Precise current limitation
- Overload protection
- Overtemperature protection
- Input voltage 12 V DC (cigarette lighter)
- Output 5 V – 1.5 A | 9 V – 1.5 A | 12 V – 1.2 A

ITEM NO	UNIT	SRP
00415010	1 pc	20,99

HEADPHONE AMP

HEADPHONE AMP NO.2



The headphone outputs of laptops and PC's are not usually very powerful. This often impairs audio quality. Der Premium Headphone Amp No. 2 has a high-quality digital/analogue converter to replace the integrated, usually basic, sound cards of devices such as PCs and laptops. Its high-quality analogue amplifiers are optimally tuned to each other. They drive and control the connected headphones with exceptional accuracy and provide greater volume, dynamics and precision.

- Also suitable for high-impedance headphones
- Power supply via USB
- Compatible with Windows XP, Vista, Windows 7/8
- Output rating: maximum 2 x 300 mW
- Impedance: 8–300 ohms
- Signal-to-noise ratio: 96 dB
- Crosstalk attenuation: 60 dB
- Amplification: 10 dB
- Distortion factor: < 0.008% (10 mW)
- Frequency range: 22 Hz – 65 kHz


ITEM NO	UNIT	SRP
00415006	Headphone Amp No.2	120,00



HEADPHONE AMP NO.1



The headphone outputs of mobile devices such as smartphones, tablets and laptops are not usually very powerful. This often impairs audio quality. The Premium Headphone Amp No. 1 takes the strain off of the device outputs. Its high-quality analogue amplifiers are optimally tuned to each other. They drive and control the connected headphones with exceptional accuracy and provide greater volume, dynamics and precision. In addition, the unit also protects the battery of the mobile device and increases its service life. The Premium Headphone Amp No. 1 also has a high-quality digital/analogue converter to replace the integrated, usually basic, sound cards of devices such as PCs and laptops. This further boosts the sound quality. The analogue volume controller with integrated on/off switch makes the amplifier very easy to use.



- Two headphones jacks
- Integrated USB Digital Analog Converter
- Latest chip technologies
- Black brushed alu optic housing
- Can operate for up to 60 hours
- Also suitable for high-impedance headphones
- Large dynamic scope
- Compatible with Windows XP, Vista, 7/8
- Output rating: maximum 2 x 320 mW
- Impedance: 16–300 ohms
- Input impedance: 5 kohms
- Signal-to-noise ratio: 96 dB
- Crosstalk attenuation: 60 dB
- Amplification: 10 dB
- Distortion factor: < 0.008 % (10 mW)
- Frequency range: 22 Hz – 65 kHz
- Battery: 3.7 V / 950 mAh (lithium-ion)
- Dimensions: approx. 90 x 13 x 57 mm



ITEM NO		UNIT	SRP
00415005	Premium Headphone Amp No.1	1 pc	241,00



WIFI | BLUETOOTH

DLNA STICK | MHL ADAPTER

USB CABLE

66

67

67

69

71

CAT CABLE

FIREWIRE



NETWORK | STREAMING WIRELESS

"Whether UHD video signals or HD audio formats, with the excellence network cable from in-akustik you can stream your content at the highest data rates and in optimal quality from the source to the playback device." Test result: outstanding." Heimkino


"The digital cables from in-akustik's Excellence series offer excellent signal transmission and great workmanship at a really affordable price. If you want to start optimizing your system beginning from the source, this is the right cable for you." HiFi Eins Null

WIFI AUDIO STREAMING RECEIVER

PREMIUM



A computer is a multimedia centre and has long been a link between a AV receiver, TV or home cinema system and in the meantime also has HDMI, USB, or CAT connections. We supply the cable for all current connections. Of course, at the highest level.

**Compatible systems:**

- Android 4.0 or higher
- Apple iOS7 or higher
- Mac OS10.7 or higher
- Windows XP or higher
- Windows Phone

Recommended app:

- EZcast

Technical data:

- High-Res Audio: 24 Bit/96 kHz
- Stereo output via 3.5 mm jack
- Optical digital output
- USB-A connection for external memory
- Frequency range: 20 – 20,000 Hz -0.5 dB
- Dynamic range: >92 dB
- Power supply: via micro USB
- Weight (approx. 60 g)
- Dimensions: approx. 78 x 78 x 18 mm

Standards/audio formats supported:

- DLNA (WAV, MP3)
- Airplay (MP3, AAC, WMA, WAV, PCM, m4a/ALAC/FLAC)
- USB (MP3, AAC, WMA, WAV, PCM, m4a/ALAC/FLAC)
- Internet radio

ITEM NO	UNIT	SRP
00415007 WiFi Audio Streaming-Receiver	1 pc	116,00



AUDIO BLUETOOTH® RECEIVER

PREMIUM



Enjoy your favourite music from your smart phone, tablet PC or laptop – as well as from your iPhone or iPad – conveniently and wirelessly on your high-end hi-fi system. Thanks to the special aptX technology, you can also enjoy first-class CD quality. The Premium Bluetooth Receiver supports all common standards such as A2DP and SBC and is compatible with almost all Bluetooth-capable devices regardless of brand. The Premium Bluetooth Receiver stores up to eight devices. Once these devices are paired with the receiver, they are automatically recognized again, allowing the connection to be more quickly reestablished. In addition to the usual analogue output (3.5 mm jack), the receiver also has an optical digital output that enables it to be connected to a new generation of amplifiers.



- Bluetooth® 3.0+EDR
- Audiocodex aptX®
- Supports A2DP
- Supports SBC Codec
- Range up to 10m
- Frequency range: 10 Hz – 22.000 Hz
- Dynamic range: >92 dB
- LED display
- Dimensions: 75,9 x 69,8 x 20,3 mm
- Weight: 56 g

ITEM NO	UNIT	SRP
00415003 Premium Bluetooth Audio Receiver	1 pc	123,00

BLUETOOTH® AUDIO TRANSMITTER & SPLITTER

PREMIUM



The Premium Bluetooth Audio Transmitter allows you to conveniently connect Bluetooth headphones or Bluetooth loudspeakers with audio sources such as the television, Hi-Fi system or PC that are not Bluetooth-capable. In combination with the Premium Bluetooth Audio Receiver, a wireless audio connection can be set up between the TV and the Hi-Fi system, for example. The Premium Bluetooth Transmitter can be connected to two Bluetooth receivers simultaneously (splitter function). This is a simple way to set up multi-room solutions. To power it, plug the USB connector into a free USB port on the devices or a USB power supply unit (not included).



- Supports aptX Audio Codec
- Supports aptX LL (Low Latency)
- Supports SBC & A2DP
- Up to 10 m range
- Power supply over USB
- Frequency range: 20 – 20,000 Hz
- Dynamic range: 95 dB
- Channel separation: 85 dB
- Distortion factor: 0.05 %
- Version 3.0+DER (Enhanced Data Rate) #00415012
- Input #00415009: Analog High Level 2V rms max
- Input #00415012: TOS Link

ITEM NO	UNIT	SRP
00415012 Bluetooth Audio Transmitter TOS-Link	1 pc	111,00
00415009 Bluetooth Audio Transmitter 3,5 Phone Plug	1 pc	104,00



CANTON REFERENCE CHECK VOL. 1



t's the sound that makes the music. Experience the perfection of the best music. With pieces full of depth. There's no compromise when it comes to what excites Canton. We all have one passion in common – music. Not just any music, but the very best music. Songs that inspire us. Sounds that make us close our eyes and forget the world around us. Canton has put together a compilation of 12 favorites - each one has its very own nuances. Discover the mid-tones. These 12 pieces are a journey of discovery for your ears and thus put all speakers through their paces.

MEDIUM	ITEM NO	TITEL
U-HQCD	01678105	Canton Reference Check Vol.1
Audiophile LP	01678101	Canton Reference Check Vol.1

MHL-ADAPTER



MHL (Mobile High Definition Link) is a standard defined by Nokia, Toshiba and Silicon Image for connecting smartphones and tablet PCs to the TV. The MHL adapter is connected to the USB port of the mobile devices, and transmits video and audio signals in HD quality. In addition, the CEC function is supported.

ITEM NO	UNIT	SRP
0044101 Premium MHL Adapter	1 pc	49,49

USB CABLE

HIGH SPEED USB B



The Excellence USB cable is specially designed for streaming HD audio and video formats. The three-fold shielded twisted pair data cable protects the sensitive data content against external interferences. The silver-plated signal conductor and the perfectly adjusted impedance ensure fast and smooth data transmission. Thick conductors enable a stable supply for stationary and fast charging mobile devices. The metal connectors with gold-plated contacts provide optimum contact and minimal contact resistance.



ITEM NO	LENGTH	SRP
006700005 Exzellenz High Speed USB 2.0 A > B	0,5m	51,00
006700001 Exzellenz High Speed USB 2.0 A > B	1,0m	62,00
006700015 Exzellenz High Speed USB 2.0 A > B	1,5m	70,00


HIGH SPEED USB MICRO-B



The Excellence USB cable is specially designed for streaming HD audio and video formats. The three-fold shielded twisted pair data cable protects the sensitive data content against external interferences. The silver-plated signal conductor and the perfectly adjusted impedance ensure fast and smooth data transmission. Thick conductors enable a stable supply for stationary and fast charging mobile devices. The metal connectors with gold-plated contacts provide optimum contact and minimal contact resistance.



ITEM NO	LENGTH	SRP
006701005 Exzellenz High Speed USB 2.0 A > Micro B	0,5m	51,00
00670101 Exzellenz High Speed USB 2.0 A > Micro B	1,0m	62,00
006701015 Exzellenz High Speed USB 2.0 A > Micro B	1,5m	70,00
00670103 Exzellenz High Speed USB 2.0 A > Micro B	3,0m	100,00



HIGH SPEED USB 2.0 CABLE



The Referenz USB 2.0 cable has been designed especially for low-loss HD audio streaming. The data lines consist of fine, separately lacquer-insulated copper wires (high speed conductors). In combination with the high-quality materials, they reduce the jitter effects that particularly affect the sound quality when streaming audio data. Sensitive data is additionally protected by 4-fold shielding. Extremely generously proportioned cables for the power supply of e.g. external hard drives minimize voltage fluctuations. Even with particularly long cables, they ensure that the peripheral devices function perfectly and therefore data is transferred with low error rates. The product is rounded off by the high-quality Referenz USB plug and the precise manufacturing.



JITTER

During digital data transmission ones and zeros are transmitted by voltage impulses. The choice of one or zero is made by the length of the impulse. The Jitter effect changes the impulse length due to the cable properties. The receiver then has difficulties in recognising the data.

USB 2.0 A > B

ITEM NO	LENGTH	SRP
007170075	0,75m	350,00
007170015	1,5m	395,00
00717003	3,0m	472,00
00717005	5,0m	553,00
00717075	7,5m	690,00
00717010	10,0m	815,00



HIGH SPEED DATENLEITER

The Referenz USB cable has finely braided signal wires, with each individual wire having a lacquer coating. This lacquer coating insulates the wires from each other, preventing eddy current within the braid and increasing the effective conductor surface. This means digital signals can be quickly and precisely transmitted.

USB 2.0 A > Mini B

ITEM NO	LENGTH	SRP
0071710075	0,75m	330,00
00717103	3,0m	423,00
00717105	5,0m	521,00
00717175	7,5m	651,00
00717110	10,0m	769,00



HIGH SPEED USB B



ITEM NO	LENGTH	SRP
01070001	1,0m	13,49
01070002	2,0m	17,69
01070003	3,0m	18,89
01070005	5,0m	22,49

HIGH SPEED USB MINI-A



ITEM NO	LENGTH	SRP
01070011	1,0m	11,59
01070013	3,0m	16,29

HIGH SPEED USB MINI-B



ITEM NO	LENGTH	SRP
01070021	1,0m	13,49
01070022	2,0m	17,69
01070025	5,0m	22,49


HIGH SPEED USB MICRO-B | -A



ITEM NO	LENGTH	SRP
Micro B		
01070041	1,0m	13,49
01070042	2,0m	17,69
01070045	5,0m	22,49
Micro A		
01070033	3,0m	16,29

CAT CABLE

HIGH END NETWORK CABLE CAT 7



The CAT7 Referenz cable is a LAN cable for high-end network connections. Because of the high production quality, it well surpasses the specifications required by EN50288-4-2 / IEC61156-6 (600 MHz), and reaches band widths of over 1200 MHz. This makes it equipped for high-speed networks with 10 Gbps (10 Giga bits per second). It was however, through exacting maintaining the impedance of its data lines, especially conceived for low-loss HD audio and HD video streaming. The PE-Network Jacket also prevents disturbing microvibrations, while the high-grade CAT Referenz plug rounds off the product.

- Four twisted-pair data lines
- Foamed PE lead insulation
- Data pairs equipped with separate foil shielding
- Common braided shield
- PE-Network Jacket
- Referenz metal plug

- Surpasses CAT7FA specifications
- Cable diameter: 8.2 mm
- 200 MHz band width
- Supports 10 Gbit high-speed LAN networks
- Supports HD-TV streaming
- Supports HD-Audio streaming



ITEM NO	LENGTH	SRP
007150075	0,75m	232,00
00715015	1,5m	250,00
0071503	3m	280,00
0071505	5m	320,00

ITEM NO	LENGTH	SRP
00715075	7,5m	370,00
0071510	10m	419,00
0071515	15m	522,00
0071520	20m	620,00

NETWORK CABLE CAT 6



The Excellence CAT cable is specially designed for high speed gigabit networks and streaming from HD audio and UHD video formats. The threefold shielded twisted pair cables (SF-FTP) protect the sensitive data content against external interferences. The thick silver-plated signal conductors and the perfectly adapted impedance ensure fast and smooth data transmission. The metal plugs with gold-plated contacts ensure optimum contact and minimal contact resistance.



ITEM NO		LENGTH	SRP
006711005	RJ45 <> RJ45; SF-UTP	0,5m	51,00
00671101	RJ45 <> RJ45; SF-UTP	1,0m	62,00
00671102	RJ45 <> RJ45; SF-UTP	2,0m	79,00
00671103	RJ45 <> RJ45; SF-UTP	3,0m	100,00
00671105	RJ45 <> RJ45; SF-UTP	5,0m	139,00
006711075	RJ45 <> RJ45; SF-UTP	7,5m	186,00
00671110	RJ45 <> RJ45; SF-UTP	10,0m	233,00

NETWORK CABLE CAT 7



High-quality network cable with CAT7 cable and compact CAT6A RJ45 plugs for professional installations. The cables have been designed for high-speed networks of up to 10 gigabits. The plugs are fitted with latching lever protection and have gold-plated contacts. Each cable has been individually tested on the basis of ISO/IEC11801.

- Cable: CAT7 AWG26 S/FTP
- Plug: RJ45 CAT6A with latching lever protection
- Diameter: approx. 6mm
- Bandwidth: 500 MHz
- Utilization: 10/100/1000BASE-T, 10 GBASE-T
- Configuration: 1:1
- Item check on the basis of CAT6A ISO/IEC11801
- 24c gold-plated contacts
- Functional packaging
- Construction fully compliant to CE and RoHS regulation


ITEM NO		LENGTH	SRP
009250005	RJ45 <> RJ45; SF-UTP	0,5m	6,29
00925001	RJ45 <> RJ45; SF-UTP	1,0m	7,59
00925002	RJ45 <> RJ45; SF-UTP	2,0m	9,89
00925003	RJ45 <> RJ45; SF-UTP	3,0m	12,29
00925005	RJ45 <> RJ45; SF-UTP	5,0m	16,69
00925008	RJ45 <> RJ45; SF-UTP	8,0m	24,49
00925010	RJ45 <> RJ45; SF-UTP	10,0m	28,49
00925015	RJ45 <> RJ45; SF-UTP	15,0m	39,49
00925020	RJ45 <> RJ45; SF-UTP	20,0m	52,00

NETWORK CABLE CAT 6



ITEM NO		LENGTH	SRP
004803005	RJ45 <> RJ45; SF-UTP	0,5m	10,89
00480301	RJ45 <> RJ45; SF-UTP	1,0m	13,49
00480302	RJ45 <> RJ45; SF-UTP	2,0m	17,69
00480303	RJ45 <> RJ45; SF-UTP	3,0m	20,49
00480305	RJ45 <> RJ45; SF-UTP	5,0m	34,99
00480308	RJ45 <> RJ45; SF-UTP	8,0m	47,99

NETWORK CABLE CAT 6



- Separating cross between the twisted pairs
- SF-UTP (separate braided and foil shielding)
- 4 twisted pairs
- Cable diameter: 6,8 mm

ITEM NO		LENGTH	SRP
004803000	CAT6; AWG24; SF-UTP; Price/m	100m	4,91
004890000	RJ-45 CAT5/6 Stecker; 8P8C	bulk	1,41
00489022;3;4	CAT5/6 insulation grommet; red; yellow; blue	bulk	0,76
00489025;7;8	CAT5/6 insulation grommet; green; black; anthracite	bulk	0,76



FIREWIRE CABLE



The Firewire cable (also IEEE 1394, DV or i-link cable) for data rates of up to 400 Mbit/s is ideal for connecting peripheral devices, such as cameras and hard disks etc, to the DVD recorder, TV or PC.



ITEM NO		LENGTH	SRP
01071103	Premium Firewire Cable 4p <-> 6p	3,0m	22,49
01071105	Premium Firewire Cable 4p <-> 6p	5,0m	32,99
01071201	Premium Firewire Cable 6p <-> 6p	1,0m	12,19
01071202	Premium Firewire Cable 6p <-> 6p	2,0m	17,39

IN-AKUSTIK SOUNDCHECK



Which cable is suitable for your requirements? This HQCD helps you to choose the right one. Because the right cable has a huge impact on the sound of your hi-fi system. This HQCD contains a collection of superior recordings representing all the different sound characteristics. How does the voice come across, how does the acoustic or electric bass sound alike, does the bass manage the drums, which listening impression is coming up listening to Tuba or Trumpet, are spatial depth and Dynamics correct?

- Available as HQCD or 2LP (180 gr.)
- Audiophile Mastering
- Optimized spatial representation
- Improved dynamics
- Improved bass reproduction



MEDIUM	ITEM-NO	INTERPRET TITEL
HQCD	0167505	Der in-akustik Soundcheck
Audiophile Double LP (180 gr.)	01675051	Der in-akustik Soundcheck

QUALITY MANAGEMENT



HIGHEST POSSIBLE PRECISION

In our product design we do everything to ensure excellent Quality from the outset. We subject our products to intense scrutiny and continuously carry out quality controls during the production process. For example, we inspect all materials for compliance with the acceptable quality level (AQL), the standard for "imported" materials and finished products. We check the tolerances of each individual part, the print quality, the colours and the construction. We investigate chemical and hazardous substances in accordance with RoHS and REACH. We test the electrics for short circuits and configuration at each production step. We carry out both functional and mechanical tests. And, of course, we test the live performance. This is what we mean by maximum precision



DIRECTIVES

All our products comply with the stringent RoHS directive. RoHS (Restriction Of Hazardous Substances) is an EU directive (2011/65/EG) aimed at reducing the use of substances in electronic devices that are harmful to health and the environment.

The European REACH ordinance is intended to protect people and the environment from harmful chemicals. Among other things, REACH specifies the obligation to provide Information on substances of particular concern in order to minimise their use.


MULTI-4 HIGH SPEED USB

WHITELINE



4 way Multi USB Cable to connect devices with different USB jacks, such as Smartphone, Tablet, Laptop, PC or charger. A high data rate of up to 10 Gbps allows a fast data synchronization. The cable is equipped on both sides with adapters for various plug combinations.

- 4 way Multi USB Cable for highest flexibility
- Modern design
- Braided jacket for extra protection
- Robust plugs with metal housing
- Adapters are fixed by a ring noose



ITEM-NO	LENGTH
010422010 Multi-4 High Speed USB	1,0m Special Offer POA

USB 3.1 SUPERSPEED + GENERATION 2

WHITELINE



USB 3.1 cable for ultra-fast synchronisation and charging. Future-proof thanks to support for high data speeds (10 Gbit/s). Fast charging mode (FAST): Use the quick charging mode when using suitable chargers (> 3A).

Standard mode: If you connect your mobile device to a PC or laptop, use the standard mode to protect your devices from excessive charging currents.

- New reversible USB Type-CTM plug
- Latest USB 3.1 standard
- Charging function up to 3 ampere (switchable)
- Data exchange / synch up to 10 Gbit/s
- Moulded pluggs

ITEM-NO	LENGTH
010423075 USB 3.1G2 Cm<>Am SWITCH	0,75m Special Offer POA

USB A <> MICRO B 180°

WHITELINE



USB cable for quick synchronisation and charging of smartphones, tablets, powerbanks, etc. Also suitable for tablets with higher power consumption. particular highlight is the design of the braiding.

HIGHLIGHT: Due to the special, hexagonal shape of the USB Micro B connector, it can be placed in both directions in one and the same socket. This way, an optimal cable run is ensured, regardless of the position of the socket on the device.

- charging function
- data synchronisation
- 180 ° angled micro USB plug
- shielded
- high quality braid in „wave design“
- length: 1,0m

ITEM NO	LENGTH
010425011 USB-A <> Micro USB-B 180° (hexagonal)	1,0m Special Offer POA

USB A <> MICRO B 90°

WHITELINE



USB cable for quick synchronisation and charging of smartphones, tablets, powerbanks, etc. Also suitable for tablets with higher power consumption. particular highlight is the design of the braiding.

- charging function
- data synchronisation
- 90° angled micro USB plug
- shielded
- high quality braid in „wave design“
- length: 1,0m

ITEM NO	LENGTH
01042501 USB-A <> Micro USB-B 90°	1,0m Special Offer POA



USB A <> LIGHTNING-ADAPTER

WHITELINE



USB cable for connecting devices with Lightning (Apple) to a computer or laptop etc. For quick syncing and charging. Also suitable for tablets with high power consumption.

- USB-A <> Apple Lightning
- Charging function
- Data synchronisation

STEREO KLINKENKABEL HOCHFLEXIBEL & SUPER SOFT

WHITELINE



Highly flexible and super soft audio cable for connecting portable devices such as smartphones, tablets, MP3 players to amplifiers, AV receivers and car radios etc. The gold plated contacts minimize contact resistance, protect against corrosion and improve the signal transmission.

- Super soft
- Highly flexible
- Gold plated contacts
- Stereo

STEREO KLINKENKABEL HOCHFLEXIBEL | 90°

WHITELINE



Highly flexible phone plug audio cable with additional foil shield against external interference for the connection of portable devices (tablet PCs, MP3 players, etc.) to AV receivers. The gold-plated contacts also improve signal transmission and minimise contact resistance.

- Gold-plated contacts
- Additional foil shielding
- Stereo
- Highly flexible
- 90° angled plug

ITEM-NO	LENGTH
010392120	1,2m Special Offer POA

ITEM-NO	LENGTH
01043001	1,0m Special Offer POA

ITEM-NO	LENGTH
0104310752	Red 0,75m Special Offer POA

HIGH SPEED HDMI CABLE

WHITELINE



The High Speed HDMI cable from the in-akustik WHITE LINE-series supports all HD audio formats and resolutions up to 2160p (4K).

- Ethernet Network (up to 100 Mbit)
- Audio Return Channel
- Additional Color Spaces
- 0,08mm² data line
- Data rate: up to 18 Gbit/s (340 MHz bandwidth)
- 4K-Support (2160p)
- 3D-compatible
- Content Type
- Supports HD Audio
- Lip Sync: automatic synchronisation
- CEC-, HDCP-, EDID- compatible
- Supports x.v. Color und Deep Color multibit (up to 48 Bit)
- Audio: up to 8 channels (24Bit/192kHz)

ITEM-NO	LENGTH
010527502	1,75m Special Offer POA
010527503	3,0m Special Offer POA

ANTENNA CABLE

WHITELINE



This HDTV antenna cable is especially designed for the requirements of high resolution television formats (HDTV). The 4-fold 120 dB screening protects the sensitive signal content. It is suitable for installing BK, SAT and cable TV systems as well as for connecting DVB-T/-S/-C receivers. The space-saving angle plugs round off the product.

- 4 fold shielding
- DVB-T/C/S compatible
- 120 dB shielding
- HDTV compatible
- 24c gold plated contacts
- 3 GHz Bandwidth
- Ferrite cores against interference
- 75 Ohm Impedance

ITEM-NO	LENGTH
01044015	1,5m Special Offer POA

USB CAR POWER ADAPTER

WHITELINE



High-quality, universal USB power adapter for the convenient and time-saving charging of mobile devices such as smartphones, tablets, cameras or power banks etc. during car journeys.

- Universal use
- Intelligent overload protection
- Over-temperature protection
- Plug & Play
- Input: 12–24 V DC (cigarette lighter)
- Output: 5 V–1.0 A
- Conforms to CE
- RoHS conformity

ITEM-NO	LENGTH
010450001	1 pc Special Offer POA



HDMI OPTICAL FIBRE TECHNOLOGY

HDMI CABLE | PLUG | TESTER

POWER CABLE

ANTENNA

CAT CABLE

SPEAKER CABLE

76

78

78

80

80

81

81

84

85

86

87

AV-TERMINALS

HDMI SPLITTER & SWITCH

HD BASE-T RECEIVER & EXTENDER

HDMI REPEATER

HDMI | DIGITAL | ANALOG | AUDIO CONVERTER



INSTALLATION

The range of multimedia products from in-akustik offers you a wide spectrum for fixed multimedia installations in your home. The range consists of various panel jacks and covers for easily integrating video and audio connections in known switch systems. Our professional HDMI optical fibre cables offer yet more options: even for the transmission of 8K HDMI signals without loss over distances of up to 100 metres.

ULTRA HIGH SPEED HDMI CABLE

HDMI 2.1 | 10K | OPTICAL FIBRE | 48 GBPS | UP TO 100M




HDMI cable with professional fibre optic technology. This technology facilitates data rates of up to 48 Gbps on a transmission path of up to 100 m. It therefore supports high-resolution 10K formats with 120 Hz as well as HDR. It is the solution for connecting devices with an HDMI 2.1 interface over great distances. Due to the build-in electronics the cable has a signal direction.



- Optical Fiber Technology
- Based on HDMI 2.1 specification
- Supports 8K@50/60 Hz
- Supports data rate up to 48 Gbps
- Supports HDCP 2.3
- Supports EDID
- Supports HDR, HDR10 und HDR10+
- Supports 4:4:4, 4:2:2 und 4:2:0 Farbrunterabstufung
- Supports 36 Bit Farbtiefe (3 x 12Bit)
- Supports up to 120 Fps
- Supports DSC (Display Stream Compression)
- eARC up to 30m | ARC up to 50m
- Metal plug
- Plug&play
- Powered by the HDMI port
- no additional power supply necessary
- Signal direction marked
- Easy to install
- CE, REACH, RoHS compliant
- Cable diameter: 4mm

- Full HD 1080p 120 Hz 4:4:4 HDR
- UHD 4K 3840 x 2160p 120 Hz 4:4:4 HDR
- UHD 4K 4096 x 2160p 120 Hz 4:4:4 HDR
- UHD 5K 5120 x 2160p 120 Hz 4:4:4 (DSC)
- UHD 8K 7680 x 4320p 120 Hz 4:4:4 HDR (DSC)
- UHD 10K 10240 x 4320p 60 Hz 4:4:4 (DSC)
- UHD 10K 10240 x 4320p 120 Hz 4:2:2 (DSC)
- etc



HIGH SPEED HDMI CABLE


HDMI 2.0B | 4K | OPTICAL FIBRE | 24 GBPS | UP TO 100M



HDMI 2.0b cable with professional fibre optic technology. This technology facilitates data rates of up to 24 Gbps on a transmission path of up to 100 m. It therefore supports high-resolution 4K formats with 50 or 60 Hz and is the solution for connecting devices with an HDMI 2.0b interface over great distances.



- Fibre optic technology
- 4K@50/60 Hz up to 100 m
- Supports HDMI 2.0b with 24 Gbps
- Supports HDCP 2.2
- Supports EDID
- eARC up to 30m | ARC up to 50m
- Solid metal plug
- Plug&Play
- Power supply via the HDMI interface
- No separate power supply unit required
- Running direction marked
- Cable diameter of just 4 mm
- Easy to lay
- CE, REACH, RoHS conformant



ITEM NO	LENGTH	SRP
009241001	1m	202,00
009241002	2m	213,00
009241003	3m	235,00
009241005	5m	258,00
009241008	8m	280,00
009241010	10m	303,00
009241015	15m	348,00
009241020	20m	359,00
009241030	30m	404,00
009241050	50m	504,00
009241070	70m	606,00
009241100	100m	706,00



PROFESSIONAL HDMI 2.0B OPTICAL FIBRE CABLE

HDMI 2.0B WITH 24 GBPS | ARMOURED | UP TO 100M




Professional HDMI cable with fibre optic technology for data rates of up to 18 Gbps with a transmission distance of up to 100 m. The cable therefore supports high-resolution 4K formats with 50 or 60 Hz, 4:4:4 chroma subsampling as well as HDR, and is the solution for connecting devices with an HDMI 2.0b interface over large distances. Thanks to the solid armouring made of a steel helix and Kevlar threads, the cable is very resistant and can withstand tensile loads of up to 100 kg and even 200 kg for a short time. In addition, the solid metal connectors are protected by a plastic sleeve with a screw cap during transport and assembly/disassembly. The cable is therefore suitable for rough use with recurring assembly and disassembly cycles, e.g. in show and stage applications.

Special feature: Reinforcement made of Stend coil and Kevlar threads



- Fibre optic technology
- Robust design
- Reinforcement made of a steel helix and Kevlar threads
- Plastic sleeve with screw cover to protect the plugs
- Supports HDMI 2.0B up to 24 Gbps
- Supports HDCP 2.2
- eARC up to 30m | ARC up to 50m
- Supports EDID
- Supports High Dynamic Range (HDR)
- Supports 4K@50/60 Hz 4:4:4 up to 100 m
- Solid metal connectors
- Plug & play
- Power supply via the HDMI interface
- Low power consumption (<0.25 watts)
- No separate power supply unit required
- Transmission direction marked
- Cable diameter: approx. 5.8 mm
- CE, REACH, RoHS compliant



ITEM NO	LENGTH	SRP
009244001	1 m	258,00
009244002	2 m	280,00
009244003	3 m	291,00
009244005	5 m	314,00
009244008	8 m	370,00
009244010	10 m	392,00
009244015	15 m	460,00
009244020	20 m	482,00
009244030	30 m	560,00
009244050	50 m	740,00
009244070	70 m	908,00
009244100	100 m	1.110,00

HIGH SPEED HDMI CABLE

HDMI 2.0B | 4K | OPTICAL FIBRE | 24 GBPS | HDMI-ADAPTER | UP TO 100M




HDMI cable with professional fibre optic technology. This technology facilitates data rates of up to 24 Gbps on a transmission path of up to 100 m. The cable therefore supports high-resolution 4K formats with 50 or 60 Hz as well as HDR and is the solution for connecting devices with an HDMI 2.0b interface over great distances. The compact micro HDMI plugs are another special feature of this cable. They can be conveniently pushed through almost any empty conduit. The scope of delivery includes the corresponding adapters to type A HDMI or DVI-D. The plugs and adapters are made of metal, have a precise guide rail and can be fastened together so they form a solid mechanical unit after installation. Important: The running direction must be complied with!




- Fibre optic technology
- Micro HDMI plugs for installing in empty conduits
- The plug is 14.5 mm wide (diagonal) and fits through so-called M20 tubes (hoses with an inner diameter of around 17mm)
- Supports HDMI 2.0B with 24 Gbps
- Supports HDCP 2.2
- EDID compatible
- High Dynamic Range (HDR)
- 4K@50/60 Hz 4:4:4 to 100 m
- eARC up to 30m | ARC up to 50m
- Solid metal plug
- Including an HDMI or DVI-D adapter
- Plug & play
- Power supply via the HDMI interface
- No separate power supply unit required
- Running direction marked
- Cable diameter of just 4 mm
- Easy to lay
- CE, REACH, RoHS compliant


VERSION 1



VERSION 2



Variante:



ITEM NO (VERSION 1)	LENGTH	SRP
0092431010	10m	370,00
0092431015	15m	404,00
0092431020	20m	426,00
0092431030	30m	471,00
0092431050	50m	572,00
0092431070	70m	684,00
0092431100	100m	784,00

ITEM NO (VERSION 2)	LENGTH	SRP
0092432010	10m	392,00
0092432015	15m	426,00
0092432020	20m	448,00
0092432030	30m	494,00
0092432050	50m	594,00
0092432070	70m	696,00
0092432100	100m	796,00

HDMI CABLE & PLUG

PROFESSIONAL HIGH SPEED CABLE & HDMI PLUG



CABLE

- Supports HDMI 2.0a with 18 Gbps
- Ultra HD 2160p (4K@50/60 Hz x 2K Video)
- High Dynamic Range (HDR)
- Conductors made of high-purity OFC copper
- 24 AWG solid conductors
- HEC (HDMI Ethernet Channel) |
- ARC (Audio Return Channel)

PLUG

- Simple, solderless IDC method of termination
- Suitable for AWG26 and AWG24 cables
- Metal housing
- Strain-relief
- 24c gold-plated contacts

ITEM NO		UNIT	SRP
0062443000	High Speed HDMI cable with Ethernet Price/m	50m	21,99
00924001	HDMI Plug	bulk	17,69

PROFESSIONAL HDMI 2.0B* CABLE



High-quality HDMI cable with stable and compact HDMI plugs for professional installation. The cables up to 5 m in length support HDMI2.0b and are suitable for applications up to the 18 Gbps (e.g. 4K60Hz 4:4:4 HDR). The 8- and 10-metre cables support HDMI1.4 and are suitable for applications up to 10.2 Gbps (e.g. 4K30Hz 4:4:4 or 4K60Hz 4:2:2). All cables are downwards compatible and support the widely used 1080p full-HD formats. Each cable is checked individually according to the corresponding specifications.

- **0,75m - 5m:** HDMI2.0b Cable
- Data rate: 18 Gbps
- Supports 4K60Hz 4:4:4 HDR
- AWG28 Cable
- Diameter: 7mm
- **8,0m - 10,0m:** HDMI1.4 Cable
- Data rate: 10.2 Gbps
- Supports 4K30Hz 4:4:4 bzw. 4K60Hz 4:2:2
- AWG26 Cable
- Diameter: 8mm

ITEM NO		LENGTH	SRP
0092420075	High Speed HDMI <> High Speed HDMI	0,75m	18,19
009242015	High Speed HDMI <> High Speed HDMI	1,5m	20,49
00924203	High Speed HDMI <> High Speed HDMI	3,0m	25,99
00924205	High Speed HDMI <> High Speed HDMI	5,0m	31,49
00924208	Standard HDMI <> Standard HDMI	8,0m	66,00
00924210	Standard HDMI <> Standard HDMI	10,0m	72,00

* up to 5,0m

HDMI TESTER

HDMI CABLE TESTER



The Exzellenz HDMI Cable Tester (HDMI = High Definition Multimedia Interface) is designed to check the pin connections of HDMI cables, and to correct any errors. It is ideal for checking the passage of the individual wires of an HDMI cable before it is connected to the equipment.

- Separate main and remote unit
- Review of the signals of all pins of HDMI cable
- Auto power on, ease of use
- LED indicator on both the main unit and on the remote
- Incl. carrying case

ITEM NO		UNIT	SRP
009920001	Exzellenz HDMI Cabletester	1 pc	168,00

POWER CABLE

POWER CABLE AC-2503M



Electrical installations in buildings are usually carried out expertly, but at the minimum expense. This means that the cables from the fuse box usually pass through a number of junction boxes and terminals before reaching the sockets. Each terminal means additional contact resistance and additional load from other appliances in the room. This leads to losses and disturbances in the power supply. Ideally, there should be a separate cable from the fuse box to the socket of the hi-fi system. The Referenz AC-2503M is perfect for this application. In addition to its large conductor cross-section of 3 x 2.5 mm², it has a shield which protects the components from electromagnetic interference from the fuse box onwards.

- Large cross-section 3 x 2.5 mm²
- Pure copper conductor
- Foil shield
- Auxiliary wire for easily connecting the shield
- Flame retardant as per EN 60332-1-2
- CE compliant
- Rated voltage: 300 / 500 V
- Test voltage: 2000 V
- Bending radius: min. 50 mm.
- Temperature range: -40 to + 70 °C

ITEM NO		LENGTH	SRP
007622503	Referenz AC-2503M Price/m	50m	10,29



MANUFACTURING OF CABLES AND ASSEMBLIES

As a medium-sized, owner-managed company with flat hierarchies, we respond quickly to market changes and especially to your individual requirements.

Profit from the wide spectrum of manufacturing possibilities of our Ballrechten-Dottingen location, our cable plant in the group and our international network of manufacturers and suppliers.



Benefit from our employees' many years of experience. Their areas of expertise cover materials procurement, logistics, product development, craftsmanship in production and goods shipping. Our employees all handle resources sparingly and have a high affinity for quality and reliability. You can find out more about our OEM solutions and our entire range of services on our website www.in-akustik.de

Some partners that we are allowed to mention:

beyerdynamic **GIRA** **nubert** **CANTON** **T+A** **ALB JORDAN** **allstar**

ANTENNA

HDTV ANTENNA CABLE A++ DIN EN 50117-2-4



- Recommended and approved by Deutschen Telekom
- Suitable for return channel (Internet)
- Expanded PE dielectric
- Inner conductor: 1.0 mm bare copper
- Exterior diameter: 6.8 mm +/- 0.2 mm
- Bonded film -> suitable for compression connectors etc.
- Small bending radius (50 mm)
- Capacitance: (pF/m) 55
- Velocity factor (v/c): 0.85
- Low signal attenuation
- Weight: 52 kg/km
- Descending metre imprint



ITEM NO	LENGTH	SRP
006260036 Professional Antenna Cable A++ Price/m	250m	5,69

PROFESSIONAL ANTENNA PLUG & COAX TOOL




Professional high end F-Plug. Easy mounting without screws or crimping. The connector is simply plugged onto the prepared cable and locks itself automatically.

- Professional F-Plug
- Very short and space-saving design
- Easy mounting without screws or crimping
- Suitable for cable #006260036 or other 4.9 / 6.8mm coaxial cable with bonded foil
- Coax tool: suitable for cable #006260036 and plug #00652123
- Coax tool: with wrench to tighten the plug on the devices. Coax-Tool: passend für Cable #006260036 und Stecker #00652123

ITEM NO	UNIT	SRP
00652123 Professional Antenna F-Plug	Bulk	2,09
00652124 Coax-Tool	Bulk	26,49

CAT CABLE

NETWORK CABLE CAT 6



- Separating cross between the twisted pairs
- SF-UTP (separate braided and foil shielding)
- 4 twisted pairs
- Cable diameter: 6,8 mm

ITEM NO	LENGTH	SRP
004803000 CAT6; AWG24; SF-UTP; Price/m	100m	4,91
004890000 RJ-45 CAT5/6 Stecker; 8P8C	bulk	1,41
00489022;3;4 CAT5/6 insulation grommet; red; yellow; blue	bulk	0,76
00489025;7;8 CAT5/6 insulation grommet; green; black; anthracite	bulk	0,76

NETWORK CABLE CAT 7



High-quality network cable with CAT7 cable and compact CAT6A RJ45 plugs for professional installations. The cables have be designed for high-speed networks of up to 10 gigabits. The plugs are fitted with latching lever protection and have gold-plated contacts. Each cable has been individually tested on the basis of ISO/IEC11801.

- Cable: CAT7 AWG26 S/FTP
- Plug: RJ45 CAT6A with latching lever protection
- Diameter: approx. 6mm
- Bandwidth: 500 MHz
- Utilization: 10/100/1000BASE-T, 10 GBASE-T
- Configuration: 1:1
- Item check on the basis of CAT6A ISO/IEC11801
- 24c gold-plated contacts
- compliant to CE and RoHS

ITEM NO	LENGTH	SRP
009250005 0,5m	6,29	
00925001 1,0m	7,59	
00925002 2,0m	9,89	
00925003 3,0m	12,29	
00925005 5,0m	16,69	
00925008 8,0m	24,49	
00925010 10,0m	28,49	
00925015 15,0m	39,49	
00925020 20,0m	52,00	

SPEAKER CABLE

SPEAKER CABLE FLAME RETARDANT



- Cross section: 1,5mm² & 2,5mm²
- Structure 30 x 0,25 mm CU & 50 x 0,25 mm CU
- High flexibility due to transposed wires
- Extruded sheathing simplifies removal of the insulation
- Insulation: PVC
- Diameter: approx. 6,5mm & 9,5mm
- Flame-retardant, conforms to IEC 60332-1-2 Class E
- Conforms to RoHS Directive 2011/65/EU



FLEXIBLE PIN



- Cable cross-section: up to 6 mm²
- For safe and easy connections on clip terminals
- For crimping or soldering
- 24c gold plated

CABLE CONDUIT

CABLE CONDUIT



Hi-fi, TV and computer devices have to be connected with a great many signal and power cables. These cables can often impair the appearance or become trip hazards. This high-quality fabric cable conduit allows cables to be bundled together in an attractive manner. The conduit has been designed so that it can accommodate power cables with large (Schuko) plugs. It can be cut to the required length conveniently with a pair of scissors. One notable feature is that the fabric at the ends does not fray as easily as other conduits.

- Simple to cut
- Stabilised braid
- Reduced fraying at the ends
- Diameter: 25-38 mm

ITEM NO	LENGTH	SRP
00402709	2x1,5mm ² Price/m 150m	3,87
00402718	2x2,5mm ² Price/m 100m	5,69

ITEM NO	UNIT	SRP
008155	bulk	4,78
0081551	Set of 4	20,49

ITEM NO	LENGTH	SRP
009210032	25-38mm Price/m 38m	10,29

AV PANEL TERMINALS

AV PANELS



With the Premium installation terminals, audio and video connections can be easily integrated into known switch systems and into the AmbienTrack cabling run system. Inside a terminal area, two half AV covers can be installed so that various connections and interfaces can be combined. Suitable for standard switch systems with cutout dimensions 56 x 56 mm and 71 x 71 mm. The installation or connection terminals can be replaced or extended at any time. Then you will be ideally-equipped for future needs. Stainless-steel optic.

ITEM NO	UNIT	SRP
00980037016	Premium AV Panel HDMI 70	bulk 38,99
00980035016	Premium AV Panel HDMI 56	bulk 37,99
00980127016	Premium AV Panel VGA 70	bulk 35,49

ITEM NO	UNIT	SRP
00980125016	Premium AV Panel VGA 56	bulk 33,99
00980105026	Premium AV Panel Speaker Terminal 56	bulk 39,49
00980107026	Premium AV Panel Speaker Terminal 70	bulk 40,49
00980005006	Premium AV Panel blind 56	bulk 21,49
00980085016	Premium AV Panel Video / Digital 56	bulk 26,99
00980087016	Premium AV Panel Video / Digital 70	bulk 26,99
00980087026	Premium AV Panel Stereo Audio 70	bulk 33,99
00980085036	Premium AV Panel YUV 56	bulk 37,49
00980087036	Premium AV Panel YUV 70	bulk 38,99

HDMI DOUBLE COUPLING



- 24c gold-plated contacts
- HDMI (f) <--> HDMI (f)
- With assembly straps
- Angled at 90° or straight

ITEM NO		SRP
0090201001	HDMI (f) <--> HDMI (f)	13,49
0090201000	HDMI (f) <--> HDMI (f) 90°	13,49

HDMI DOUBLE COUPLING WITH CABLE (ROUND)



- 24c gold-plated contacts
- HDMI (f) <--> HDMI (f)
- With 25 cm cable
- For round assembly openings (Ø 23 mm)

ITEM NO		SRP
0090203025	HDMI (f) <--> HDMI (f) round	18,59
0090202025	HDMI (f) <--> HDMI (f)	17,19

VGA (SUB-D) PANEL JACK



- 24c gold-plated contacts
- 15-pin
- 3 rows
- Soldered connection

ITEM NO		SRP
0090601000	VGA SUB-D 15p. (f) solderable	8,19

VGA (SUB-D) DOUBLE COUPLING WITH CABLE



- 24c gold-plated contacts
- 15-pin
- 3 rows
- With 25 cm cable

ITEM NO		SRP
0090602025	VGA (f) <--> (f); 25 cm	7,39

SPEAKER TERMINAL



- 24c gold-plated contacts
- Fully-insulated
- Banana and spade lugs compatible
- For cables up to 6.0 mm²

ITEM NO		SRP
0091001002	red	12,29
0091001007	black	12,29

RCA PANEL JACK



- 24c gold-plated contacts
- Soldered connection
- Grommets
- For 8 / 9.5 mm drill holes

ITEM NO		SRP
0090801005	green	4,99
0090801003	yellow	4,99
0090801002	red	4,99
0090801007	black	4,99
0090801004	blue	4,99

RCA DOUBLE COUPLING



High-quality RCA mounting double coupling with screw thread for installing in front panels, etc. Solid design with gold-plated contacts. Allows the use of prefabricated RCA cable inside the installation. Colour coding available in five different colours.

ITEM NO		SRP
0090802004	blue	6,09
0090802005	green	6,09
0090802002	red	6,09
0090802003	yellow	6,09
0090802007	black	6,09

AV PANEL HDMI



Premium AV cover with HDMI double coupling (round) for quick and easy installation with a HDMI cable. Stainless steel optic.

ITEM NO		SRP
00980027256	25 cm round; 70x35	40,49
00980025256	25 cm round; 56x28	39,49

AV PANEL VGA



Premium AV cover with VGA double coupling for quick and easy installation with a VGA connection cable. Stainless steel optic.

ITEM NO		SRP
00980125256	25 cm round; 56x28	29,99
00980127256	25 cm round; 70x35	30,99




SUPPORT RING



The support ring forms the base for all applications. It is screwed to a standard in-wall socket or surface socket. In contrast to the support ring for the AmbienTrack System #0098000, the new version #0098001 will fix the frame of the switch system by screwing the AV panels. The new support ring is suitable for all AV panels except for the version with 3 RCA jacks.

ITEM NO		SRP
0098000	AV Tragering AmbienTrack	10,49
0098001	AV Tragering	11,09

IP-RAHMEN



When the the Premium AV-terminals are installed in a plaster wall, this frame forms an elegant seam to the wall.

ITEM NO		SRP
0098000001	Single model	8,29
0098000002	Double model	12,59
0098000003	Triple model	20,99

HDMI IP INSTALLATION BOX



Inexpensive HDMI wall socket for 65 mm flushmounted sockets. With a 90° angled HDMI dual coupling and white plastic frame.

ITEM NO		SRP
00980018016	HDMI (f) HDMI (f) 90°	12,79

AMBIENTECH

AmbienTech gets more out of buildings, houses and rooms where people live, work, eat and shop. It is a spatial concept that is ideal for private homes and commercial use. It offers new dimensions for interior design. You can look forward to more style, flair and personal space.

AMBIENTRACK

There is more than meets the eye – more style! Combining flexibility with design this cable conduit system ensures that switches and sockets are exactly where you need them.

AMBIENTONE

The sound coming from the walls: these flat-membrane loudspeakers can be invisibly slotted into walls and ceilings. Large box-loudspeakers are no longer necessary.



AMBIENART

The unlimited facets of light open up brand new opportunities for interior design. It requires only few technical components, which you can combine in any way you want.

Further information on AmbientTech can be found on page 86

HDMI SPLITTER

HDMI SPLITTER 1 -> 2 HIGH SPEED



STAR




- Bandwidth up to 3 x 2.25 Gbps / 225 MHz
- Operating voltage: 230VAC / 5V or via HDMI
- Dimensions: 62 x 54 x 18 mm
- Cable length OUT: 20m

ITEM NO	SRP
003247012	131,00

HDMI 2.0 SPLITTER 1 >2 HIGH SPEED | 4K



PREMIUM



- Supports uncompressed audio formats like LPCM
- Supports HD audio formats such as DTS-HD or Dolby True HD
- Supports compressed audio formats such as DTS, Dolby Digital
- Compact size: 80 x 50 x 20 mm
- Weight: 100 g

ITEM NO	SRP
004245012	171,00



MICHAEL SCHENKER TEMPLE OF ROCK

4K ULTRAHD



in-akustik presents the World's premiere Music 4K Ultra HD Blu-ray with On A Mission – Live In Madrid.

What on the surface might appear to be a platitude, is a serious invitation for the fans of the "Mad Axeman" and one they are happy to take him up on. Where else could aficionados of high-class guitar rock see such an emotional and energetic show? And one featuring a line-up that leaves connoisseurs of the international music scene rapturously clicking their tongues in appreciation.

Michael Schenker played various guitars, including for the first time his new double-neck Flying-M with 2 necks, each with 6 strings, with each neck tuned differently.

MEDIUM	ITEM NO	ARTIST TITEL
U-HQCD	0164193	Michael Schenker On A Mission - Live In Madrid

HDMI SPLITTER 1 -> 8 HIGH SPEED



PREMIUM



- Data rate: 10,2 Gbps
- Dimensions: 257 x 25 x 120mm
- Operating voltage: 230VAC; 5V / 16W
- Cable length IN:20m; OUT:20m

ITEM NO	SRP
004245118	469,00



HDMI SPLITTER 1->2 SCALER HIGH SPEED



PREMIUM



The integrated scaler allows older and newer devices to be combined and makes the suitable format available to each device. This ensures that a new 4K-capable TV receives a 4K format even if an older Full HD TV is being operated on the splitter at the same time. The EDID management system (EDID Engine) generates the necessary EDID data for the source automatically. Overall, the splitter ensures that the connected devices can provide the maximum performance.



ITEM NO	SRP
0042451142	233,00



MHL-HDMI SWITCH 3 -> 1



MHL (Mobile High-DefinitionLink) is the new AV interface of mobile devices. Smartphones and tablet PCs that support this standard use their Micro USB port for this. With the appropriate adapter HD picture and sound quality can be played back on a TV with HDMI input. In the Premium MHL / HDMI switch box a MHL adapter is included. MHL - Front smartphones and tablet PCs can be connected if they support the MHL standard. In addition, the switch box has three HDMI inputs that dominate all current HDMI formats.

- 1 MHL and 3 HDMI inputs
- Range up to 750MHz / 7,5Gbps (HDMI)

ITEM NO	UNIT	SRP
00424505	1 Set	179,00

HDMI SWITCH 3 >1 HIGH SPEED



- Output with HDMI cable (50 cm)
- Automatic switching
- Downwardly compatible
- Supports uncompressed audio such as LPCM
- Supports compressed audio such as DTS Digital, Dolby Digital
- Supports HD audio formats such as DTS-HD and Dolby True HD

ITEM NO	UNIT	SRP
0032450314	Set of 1	79,00

HD BASE-T RECEIVER

HD-BASE-T RECEIVER IP-WALL SOCKET



Converter with one HD-BaseT input and one HDMI output as well as additional Ethernet port and IR channel (forward or back). For installation in mounting boxes (double boxes). Suitable for the HD-BaseT transmitters, splitters and matrix.

- Data rate: 10,2 Gbps
- Dimensions: 145 x 84,5mm
- Operating voltage: 100-240VAC bzw. 5VDC
- Cable length IN: 80m; OUT: 20m

ITEM NO	SRP
009120304	390,00

HD BASE-T RECEIVER




Converter with one HD-BaseT input and one HDMI output as well as additional Ethernet port and IR channel (forward or back). Suitable for the HD-BaseT transmitters, splitters and matrix.

- Data rate: 10,2 Gbps
- 110 x 23,5 x 75mm
- Operating voltage: 100-240VAC bzw. 5VDC
- Cable length IN: 80m; OUT: 20m

ITEM NO	SRP
009120302	355,00

HD BASE-T RECEIVER | POE



Converter with one HD-BaseT input and one HDMI output as well as additional Ethernet port and IR channel (forward or back). This unit is powered via the CAT cable (PoE). Suitable for the HD-BaseT transmitters, splitters and matrix with PoE support.

- Data rate: 10,2 Gbps
- 110 x 23,5 x 75mm
- Operating voltage: 100-240VAC bzw. 5VDC
- CableLength IN: 80m; OUT: 20m

ITEM NO	SRP
009120402	452,00



HDMI REPEATER

HDMI REPEATER

HDMI 2.0 REPEATER



The Pro HDMI 2.0 repeater amplifies and improves the HDMI signal so that HDMI cables can be extended and larger distanced bridged with it. Thanks to state-of-the-art technology, the repeater supports the current 4K 60 Hz 4:4:4 formats (18 Gbps) and is backwards compatible. Using plug & play, it is simply plugged between the HDMI cables and supplied with power automatically via the HDMI port (no extra power supply unit required). The longer HDMI cable is installed between the source and the repeater and the shorter HDMI cable between the repeater and the TV/projector.

- 4K@60Hz 4:4:4 up to 25m
- 4K@30Hz up to 30m
- 1080p up to 50m
- supports HDCP2.2 & 1.4
- downwardly compatible to HDMI1.4 & 1.3
- Power supply via HDMI

ITEM NO		SRP
00912004	Profi HDMI 2.0 Repeater 18 Gbps	104,00

PROFESSIONAL
HDMI 2.0B* CABLE



High-quality, 3 fold shielded HDMI cable with stable and compact HDMI plugs (approx. 19.5x11.0x33.0 mm incl. kink protection) for professional installation. Item check on the basis of the HDMI1.4 or HDMI2.0 specifications. Construction fully compliant to CE and RoHS regulation.

- **0,75m - 5m:** HDMI2.0 Cable
- Data rate: 18 Gbps
- Supports 4K60Hz 4:4:4 HDR
- AWG28 Cable
- Diameter: 7mm
- **8,0m - 10,0m:** HDMI1.4 Cable
- Data rate: 10.2 Gbps
- Supports 4K30Hz 4:4:4 bzw. 4K60Hz 4:2:2
- AWG26 Cable
- Diameter: 8mm

* up to 5,0m

ITEM NO		LENGTH	SRP
0092420075	High Speed HDMI <> High Speed HDMI	0,75m	18,19
009242015	High Speed HDMI <> High Speed HDMI	1,5m	20,49
00924203	High Speed HDMI <> High Speed HDMI	3,0m	25,99
00924205	High Speed HDMI <> High Speed HDMI	5,0m	31,49
00924208	Standard HDMI <> Standard HDMI	8,0m	66,00
00924210	Standard HDMI <> Standard HDMI	10,0m	72,00





AUDIO CONVERTER



- 16 Mbps max.
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO	SRP
01040101 Coax > Toslink; 230V AC	79,00
01040102 Toslink > Coax; 230V AC	86,00

DAC | USB POWER



- Audio: 44 / 48 / 96kHz | 24 Bit
- Dimensions: 79 x 24 x 49mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO	SRP
00315002	70,00

AUDIO CONVERTER ANALOG > DIGITAL



- Audio out: 48kHz | 24Bit
- Dimensions: 50 x 34 x 40mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO	SRP
009120502	70,00

HDMI KONVERTER HDMI > HDMI + AUDIO



- Extrahiert das Audiosignal aus dem HDMI Signal und stellt es an einem analogen Ausgang (Stereo 3,5 Klinke) sowie digitalen Ausgang (koaxial und optisch) bereit.
- Das Audioformat kann zwischen 2 Kanal und 5.1 Kanal umgeschaltet werden (Digital).
- Datenrate: 18 Gbps | 4K/60 Hz/12 Bit | HDCP 2.2 und 1.4
- 70 x 20,5 x 66,6mm
- Stromversorgung 5V / 2 Watt | Inkl. Netzteil 5V / 1A

ITEM NO	SRP
0091206014	135,00

HDMI CONVERTER HDMI > FBAS + AUDIO



- The converter changes the HDMI signal to a standard analogue signal (FBAS). The output format can be switched between PAL and NTSC. An analogue audio output is also available.
- PAL (576) / NTSC (480i)
- Dimensions: 100 x 25 x 100mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO	SRP
009120602	192,00

HDMI CONVERTER VGA + AUDIO > HDMI



- changes the analogue VGA and stereo audio signal to an HDMI signal.
- VGA in: 800x600 / 1024x768 / 1360x768 / 1600x1200
- HDMI out: 800x600 / 1024x768 / 1360x768 / 1600x1200
- Audio out: 24 Bit / 48kHz (HDMI)
- Dimensions: 88 x 25,5 x 68mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO	SRP
009120603	123,00

HDMI CONVERTER VGA/AUDIO > HDMI WITH SCALER



- changes the analogue VGA and stereo audio signal to an HDMI signal
- The output format can be switched between 720p and 1080p.
- VGA in: 800x600 / 1024x768 / 1360x768 / 1600x1200
- HDMI out: 720p / 1080p
- Audio out: 24 Bit / 48kHz (HDMI)
- Dimensions: 88 x 25,5 x 68mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO	SRP
009120604	123,00

CONVERTER HDMI A | MINI C | MICRO D > VGA



- HDMI in: 480/576/720/1080p
- Audio in: 2 Channel 32/44.1/48kHz; 16/20/24Bit (HDMI)
- VGA out: 480/576/720/1080p
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO	SRP
009120605 HDMI A > VGA	48,99
009120606 HDMI Mini C > VGA	48,99
009120607 HDMI Micro D > VGA	46,49



● AMBIENTTRACK	90
● AMBIENART	93
● AMBIENTONE	96



AmbienTrack & Ambientone

A M B I E N T E C H

AmbienTech gets more out of buildings, houses and rooms where people live, work, eat and shop. It is a spatial concept that is ideal for private homes and commercial use. It offers new dimensions for interior design. You can look forward to more style, flair and personal space.

AmbienTrack

There is more than meets the eye – more style! Combining flexibility with design this cable conduit system ensures that switches and sockets are exactly where you need them.

Ambienart

The unlimited facets of light open up brand new opportunities for interior design. It requires only few technical components, which you can combine in any way you want.

Ambientone

The sound coming from the walls: these flat-membrane loudspeakers can be invisibly slotted into walls and ceilings. Large box-loudspeakers are no longer necessary.


WALL PILLAR | BASIC PROFILE



The AmbienTrack wall pillar is made of aluminium and can be installed at half room height or at full room height. The wall pillar is used for guiding cables and for fitting installation components. The fixed installation of main circuits into the rooms ends in the wall pillar. The transition from a classic installation to flexible cabling is therefore effected in the wall pillar. It can be installed both surface-mounted and flush-mounted in the wall.

ITEM NO	LENGTH	SRP
0011004 wall pillar high; alu optic	1.800 mm	116,00

CORNER PILLAR | BASIC PROFILE



The corner pillar is also fully made of aluminium and can be installed at half-height or room height in corner spaces. It boasts the same installation options as the wall pillar, and is also well suited for vertical installation over several floors. The same cover panels are used as for the wall pillar.

ITEM NO	LENGTH	SRP
0011201 corner pillar; alu optic	900 mm	82,00
0011203 corner pillar; alu optic	1.800 mm	136,00

WALL PILLAR FLAT | BASIC PROFILE



The flat wall pillar is made of aluminium and can be installed at half room height or at room height, and is solely for cable routing. It can be installed both surface-mounted and flush-mounted in the walls.

ITEM NO	LENGTH	SRP
0010803 wall pillar flat; alu optic; anodized	900 mm	49,00
0010810 wall pillar flat; alu optic; anodized	1860 mm	107,00

SKIRTING BOARD | BASIC PROFILE + COVER



The AmbienTrack skirting board is used for horizontal distribution of cables in a room, which generally lead out of an AmbienTrack pillar. It is however also possible to feed into an AmbienTrack skirting board directly from the wall.

ITEM NO	LENGTH	SRP
0010004 skirting board; alu optic	1.800 mm	76,00
0010005 skirting board; alu optic	1.800 mm	278,00

SKIRTING BOARD DUCT | BASIC PROFILE



- No need for earthing when using the tool box
- special geometry for integration in drywall constructions
- Replaces the floor skirting board
- Can be installed directly on screed flooring (replacement of the flooring without removing the duct).
- Variable positioning of sockets and installation devices along the wall
- Shadow gaps on both sides created a free-floating impression
- Screwless clip cover assembly
- Complete camouflaging of the baseboard by the cover (no longitudinal joint)
- Option of indirect LED lighting (light lines on both sides)

The AmbienTrack skirting board duct is installed on the floor and is a horizontal guide for cables, as well as a fitting for installation components near floor level. Combined with drywall construction, it is possible to partially integrate the skirting board duct into the wall.

ITEM NO	LENGTH	SRP
0010202 skirting board duct; Basic profile; alu optic; anodized	625 mm	93,00
0010204 skirting board duct; Basic profile; alu optic; anodized	1.875 mm	192,00





COVER



The same aluminium covers are used for the wall duct, corner duct, skirting board duct and the flat wall duct baseboard. There are two standard surface finishes (natural anodised and stainless steel). The covers are clipped onto the baseboard without screws. To match the various installation products and light modules, there are covers with the corresponding perforations. A special design feature is the frame-free installation of standard switch systems.

ITEM NO		LENGTH	SRP
00114501	Cover System 56 alu optic / 1 cutout	900 mm	48,49
00114503	Cover System 56 alu optic / 2 cutout	900 mm	49,99
00114505	Cover System 56 alu optic / 3 cutout	900 mm	54,00
00114507	Cover System 56 alu optic / 4 cutout	900 mm	56,00
00114508	Cover System 56 alu optic / 5 cutout	900 mm	58,00
00114504	Cover System 56 alu optic / 2 cutout	2.250 mm	149,00
00114506	Cover System 56 alu optic / 2+1 cutout	2.250 mm	151,00

ITEM NO		LENGTH	SRP
00114601	Cover System 65 alu optic / 1 cutout	900 mm	48,49
00114603	Cover System 65 alu optic / 2 cutout	900 mm	49,99
00114604	Cover System 65 alu optic / 3 cutout	900 mm	54,00
00114605	Cover System 65 alu optic / 4 cutout	900 mm	56,00
00114606	Cover System 65 alu optic / 5 cutout	900 mm	58,00

ITEM NO		LENGTH	SRP
00114701	Cover System 71 alu optic / 1 cutout	900 mm	48,49
00114703	Cover System 71 alu optic / 2 cutout	900 mm	49,99
00114704	Cover System 71 alu optic / 3 cutout	900 mm	54,00
00114705	Cover System 71 alu optic / 4 cutout	900 mm	56,00
00114706	Cover System 71 alu optic / 5 cutout	900 mm	58,00

ITEM NO		LENGTH	SRP
00114003	Cover without cutout alu optic	900 mm	43,49
001140031	Cover without cutout alu optic	1860 mm	89,00

TOOL BOX



The tool box allows installation components such as switches, sockets, computer and speaker connections, sensors, operating elements and so on to be installed modularly in any combination in the AmbienTrack wall ducts, corner ducts and skirting board ducts. Furthermore, the tool box can be used as a distributor and branching box. The installation of power supply units and electronic components, e.g. for building automation, is also possible.

ITEM NO		UNIT	SRP
0013051	A-Track Tool Box; 56mm 1 cutout	1 Set	7,29
0013052	A-Track Tool Box; 56mm 2 cutout	1 Set	10,59
0013053	A-Track Tool Box; 56mm 3 cutout	1 Set	12,39
0013054	A-Track Tool Box; 56mm 4 cutout	1 Set	15,19
0013055	A-Track Tool Box; 56mm 5 cutout	1 Set	17,89

ITEM NO		UNIT	SRP
0013061	A-Track Tool Box; 65mm 1 cutout	1 Set	7,29
0013062	A-Track Tool Box; 65mm 2 cutout	1 Set	10,59
0013063	A-Track Tool Box; 65mm 3 cutout	1 Set	12,39
0013064	A-Track Tool Box; 65mm 4 cutout	1 Set	15,19
0013065	A-Track Tool Box; 65mm 5 cutout	1 Set	17,89

ITEM NO		UNIT	SRP
0013071	A-Track Tool Box; 71mm 1 cutout	1 Set	5,19
0013072	A-Track Tool Box; 71mm 2 cutout	1 Set	5,89
0013073	A-Track Tool Box; 71mm 3 cutout	1 Set	6,29
0013074	A-Track Tool Box; 71mm 4 cutout	1 Set	6,69
0013075	A-Track Tool Box; 71mm 5 cutout	1 Set	7,29

ITEM NO		UNIT	SRP
0013001	A-Track Tool Box blind size like 1 cutout	1 Set	5,99
0013002	A-Track Tool Box blind size like 2 cutout	1 Set	6,69
0013003	A-Track Tool Box blind size like 3 cutout	1 Set	7,49
0013004	A-Track Tool Box blind size like 4 cutout	1 Set	8,29
0013005	A-Track Tool Box blind size like 5 cutout	1 Set	9,09



DEVICE SUPPORT



The AmbienTrack device support is installed on the skirting board and allows you to vary the position of sockets, a computer or multimedia connections. It can also be easily added to at a later date.

ITEM NO		UNIT	SRP
0013200	Device support SET without cutout ALU	1 Set	80,00
0013251	Device support SET System 56 ALU	1 Set	108,00
0013261	Device support SET System 65 ALU	1 Set	108,00
0013271	Device support SET System 71 ALU	1 Set	108,00


COVER WITH CABLE OUTLET



Cover panel for wall and corner pillar with universal outlet. For example, for wiring the flat screen or the surround speakers.

ITEM NO		UNIT	SRP
0011490	Cover alu optic; with cable outlet	1 pc	21,49

MOULDINGS FOR WALL PILLAR



The mouldings allow any combination of transitions between the wall or corner columns and the skirting board or skirting duct. Each moulding consists of a half base profile (left and right), and is plugged onto the respective baseboard of the wall or corner column using coupling pins (included in the set).

Example: A transition between a wall column and a skirting board on the left, and an on-wall skirting duct on the right is assembled as follows:

1 x 0011017 A-Track wall column, high moulding transition SL LEFT

1 x 0011018 A-Track wall column, high moulding transition SK on-wall RIGHTS

ITEM NO		SRP
0011017	wall pillar high; moulding transition skirting board left	21,49

ITEM NO		SRP
0011018	wall pillar high; moulding transition skirting board duct on-wall right	17,49
0011019	wall pillar high; moulding transition skirting board duct on-wall left	17,49
0011020	wall pillar high; moulding transition skirting board duct in-wall right	30,99
0011021	wall pillar high; moulding transition skirting board duct in-wall left	30,99

MOULDING FOR CORNER PILLAR



SKIRTING BOARD OUTSIDE CORNER 90°



ITEM NO		UNIT	SRP
0011208	corner pillar high; moulding closed right / left	1 pc	16,29
0011210	corner pillar high; moulding transition skirting board right	1 pc	22,49
0011211	corner pillar high; moulding transition skirting board left	1 pc	22,49

ITEM NO		UNIT	SRP
0010008	skirting board; alu optic	1 pc	32,49



END SECTIONS FOR SKIRTING BOARD & SKIRTING BOARD DUCT



ITEM NO		UNIT	SRP
0010010	A-Track skirting board; alu optic; left	1 pc	29,99
0010009	A-Track skirting board; alu optic; right	1 pc	29,99
0010205	A-Track skirting board duct; alu optic; right	1 pc	29,99
0010206	A-Track skirting board duct; alu optic; left	1 pc	29,99
0010207	A-Track skirting board duct; stainless steel optic; right	1 pc	33,99
0010208	A-Track skirting board duct; stainless steel optic; left	1 pc	33,99

END SECTION FOR CORNER PILLAR



ITEM NO		UNIT	SRP
0011205	A-Track corner pillar; alu optic	1 pc	32,49

END SECTION FOR WALL PILLAR AND FLAT WALL PILLAR



ITEM NO		UNIT	SRP
0011009	wall pillar high; alu optic (old version)	1 pc	29,99
0010804	wall pillar flat; alu optic	1 pc	27,99

STRAIN RELIEF FOR TOOL BOX



ITEM NO		UNIT	SRP
00190003	A-Track strain relief (M5861)	1 pc	1,21

AMBIENART

LED STRIP



For installation in the shadow gap of the AmbientTrack ducts (wall duct, corner duct, skirting board, skirting duct, device support, TV wall duct) there are LED strips in a variety of designs. Monochrome strips in the colours white, warm white and blue can be clipped into the profiles – no need for tools. They are supplied directly using appropriate 24 volt power supply units from the AmbientTrack range, or using the AmbientTrack controller/dimmer. In addition, the LED strip is also available in a RGB version. This allows the light lines to be realised in any imaginable colour and even with dynamic changes of

colour. The RGB strip is clipped into the AmbientTrack profile together with a small retaining profile and activated using the AmbientTrack controller/dimmer. A comprehensive range of accessories, such as connector or coupling pieces, is available for the LED strips. A flexible LED strip with the three base colours red, green and blue for individual and variable colour palettes. Dust and water proof, moulded with a self-adhesive rear side for universal use. The short LED intervals of just 25 mm provide a high luminosity and evenly distribute the illumination. The strips are easy to combine by joining together.

ITEM NO		LENGTH	SRP
0015201	LED strip RGB 24V (447x10/2xPCB connector/ESD)	450 mm	35,99
0015202	LED strip RGB 24V (897x10/2xPCB connector/ESD)	900 mm	71,00


LED CUBE



The LED cubes have an edge length of just 30 mm, can be rotated by 360°, can be individually combined and can be placed and replaced on the AmbienTrack profiles anytime. The matching jacks with the LED circuit electronics are installed ready to connect to the AmbienTrack tool boxes. The focused light beam from the cube, with an illumination angle of 20°, is generated using power LED technology. The power is supplied and the cube activated using the 24-volt power supply unit and the controller/dimmer from the AmbienTrack range. Ceilings, walls, accessories and even entire rooms can now be accentuated with cool or warm light colours according to pReferenz

ITEM NO		UNIT	SRP
0015401	LED cube monochrom 350mA/1W 90° white	1 pc	53,00
0015402	LED cube monochrom 350mA/1W 90° warm white	1 pc	53,00
0015405	LED cube monochrom 350mA/1W 90° green	1 pc	53,00

LED CUBE | PLUG-IN BASE



The AmbienArt plug-in base performs both the electrical adjustment as well as the mechanical adaptation of the LED cubes. They fit into the AmbienTrack tool box perfectly, where an adapter fitting guides the pluggable connections out of the tool box. In combination with the in-wall covers, available separately, the plug-in base and the LED cube can be installed in standard in-wall sockets independently of the AmbienTrack system. There are three different base modules:

1) AMBIENART PLUG-IN BASE MASTER MONOCHROME

The Master plug-in base contains the constant current converter required for the LED cube (24 volt / 350 mA) and can be dimmed by PWM. A DIP switch allows you to decide which system channel the LED cube reacts to. The Master plug-in base can power up to four further LED cubes using Slave plug-in bases.

ITEM NO		UNIT	SRP
0015510	plug in base monochrome; 1 gang Master	1 pc	41,00
0015511	plug in base monochrome; 1 gang Slave	1 pc	17,49
0015513	plug in base monochrome; 2 gang Master/Slave	1 pc	56,50
0015514	plug in base monochrome; 2 gang Master/Master	1 pc	77,00
0015551	plug in base RGB 1 gang Master	1 pc	41,00
0015552	plug in base RGB 2 gang Master	1 pc	77,00
0015593	LED cube plug base connecting adapter for toolbox	1 pc	19,49

2) AMBIENART PLUG-IN BASE SLAVE MONOCHROME

The Slave plug-in base is for extending the Master plug-in base (see above). It can also be used as a purely mechanical plug-in base for activating the LED cubes using other systems. CAUTION: In this case, it must be activated using 350 mA constant current!

3) AMBIENART PLUG-IN BASE RGB

This plug-in base has been designed especially for the LED cubes RGB. It contains a separately-dimable constant current converter for every colour channel (red, green and blue). It is activated using PWM.

ITEM NO		UNIT	SRP
0015603	plug in base; BOX 2 gang Master/Slave	1 pc	74,00
0015604	plug in base; BOX 2 gang Master/Master	1 pc	98,00
0015607	plug in base; BOX 3 gang Master/Master/Master	1 pc	140,00
0015651	plug in base; BOX 1 gang; RGB	1 pc	56,00
0015652	plug in base; BOX 2 gang; RGB	1 pc	98,00



LED WALL SPOTLIGHT



A powerful LED spotlight in monochrome and RGB versions which is integrated into the end sections of the wall and corner pillars, as well as the device support. The beam of light emerging from the front face of the profile is generally directed towards the ceiling, and produces a fascinating light reflection on the wall – in particular during the dynamic colour changes. The power is supplied and the cube activated using the 24-volt power supply unit and the controller/dimmer from the AmbientTrack range.

ITEM NO		UNIT	SRP
0015802	wall pillar ALU 350mA/1W white	1 Set	84,00
0015821	corner pillar ALU 350mA/1W blue	1 Set	89,00

LED-RGB-CONTROLLER




The AmbienArt light system is controlled by a RGB controller, which takes care of the colour setting, changing the colour or dimming the light components. The controller is elegantly integrated into the wall pillars along with the tool box and can be easily operated by remote control. The power is supplied using the 24-volt system power supply unit. The controller's user interface is very high quality and has a clear layout, and can be combined with any switches and sockets..

ITEM NO		UNIT	SRP
0016605	RGB Controller 2432 PWM / 12-24V/3x2A / 56	1 Set	199,00
0016606	RGB Controller 2432 PWM / 12-24V/3x2A / 65	1 Set	199,00
0016607	RGB Controller 2432 PWM / 12-24V/3x2A / 71	1 Set	199,00
0016600	RGB Controller 2432 PWM / 12-24V/3x2A / PCB	1 Set	115,00
0016620	RGB Repeater	1 Set	49,00
0017002	AC-Adapter 230V -> 350mA / 6W	1 pc	22,49
0017102	AC-Adapter 90-264V AC>24V DC/0,84A/20W	1 pc	22,49
0017103	AC-Adapter 90-264V AC>24V DC/2,5A/60W	1 pc	49,00
0017104	AC-Adapter 90-264V AC>24V DC/4A/96W	1 pc	69,00
0017105	AC-Adapter 90-280V AC>24V DC/6,3A /150W	1 pc	105,00
0017110	AC-Adapter 90-264V AC>24V DC/2,5 A/60W RGB	1 pc	39,00



AMBIENTONE NO.4 | NO.1



AmbienTone is a flat panel loudspeaker in a modified gypsum plasterboard. It is installed in drywall constructions. In very few work steps. Once connected, fitted and sealed, AmbienTone can be wallpapered over, painted and even plastered over. A coat with a thickness of up to 2 mm will result in only a minimal loss of sound quality.

- AmbienTone is a flat-membrane loudspeaker based on a bending wave convertor.
- Also suitable for wet rooms (bathroom, wellness, etc.).
- Ideal for multiroom and home cinema applications.
- Can be used in both private and public areas (restaurants, galleries, etc.).
- Large box-loudspeakers are no longer necessary.
- The speakers can be connected to any amplifier or hi-fi system.

	NO.4	NO.1 (100V)
- Power:	60 Watts	25 Watts (6/12/20/25 Watts adjustable)
- Impedance:	6 Ohm	
- Frequency range:	80–18.000 Hz	80–18.000 Hz
- Sensitivity:	92,5 dB	85 dB (1W/m)
- Overload protection	Yes	Yes
- Size:	625 x 500 x 44 mm	700 x 500 x 44 mm
- Weight:	5,5 kg	5,8 kg
- System:	2 ways	2 ways
- Dispersion angel:	H x V 180° x 180°	H x V 180° x 180°
- Connection:	10 m speaker cable	10m speaker cable
- Max. SPL:	108 dB	102 dB
- Plasterboard:	12,5 mm	12,5 mm



ITEM NO	UNIT	SRP
0025004 AmbienTone No.4; 2 ways; 6 Ohm; 60 Watts	1 pc	1577,00

AMBIENTONE NO.6



AmbienTone No.6 is a speaker module for invisible integration in solid walls. The flat-panel speaker constructed according to the principle of the bending wave convertor. The module is embedded into a niche constructed in the wall and plastered over completely. Available as an option in a 100 V model. Note: the design of the AmbienTone No.6 module ensures an extremely high decoupling between the membrane surface and the surrounding surface of the wall. However, structure-borne sound which spreads through the walls can still occur, depending on the construction and workmanship of the masonry. Before installing the panel, check the static function of the wall you would like to use.

- Power:	40 Watt	- Weight:	ca. 3,5 kg
- Impedance:	4 Ohm	- System:	2 Wege
- Frequency range:	80–18.000 Hz	- Dispersion angel:	H x V 180° x 180°
- Sensitivity:	85 dB	- Connection:	10 m speaker cable
- Overload protection	Ja	- Carrier:	Foam membrane
- Size:	435 x 570 x 45 mm		

ITEM NO	UNIT	SRP
0025006 AmbienTone No.6	1 pc	1455,00

AMBIENTONE NO.2



The AmbienTone No. 2 universal modules blend in indiscernably with panelling materials such as MDF, wood or chipboard. Panelling materials such as parts of a multimedia wall, or wall or ceiling cladding sections, are prepared in a way which allows the self-adhesive AmbienTone No. 2 to be installed on the back of these and the front side of the panelling material is used as a surface membrane. This means the AmbienTone No. 2 surface loudspeaker can be integrated into wood panelling, furnishings, etc., remaining out of sight and without visible joints.

- Power:	40 Watts	- Weight:	ca. 3,5 kg
- Impedance:	4 Ohm	- System:	2 ways
- Frequency range:	80–18.000 Hz	- Dispersion angel:	H x V 180° x 180°
- Sensitivity:	85 dB (1 Watt/1m)	- Connection:	10 m speaker cable
- Overload protection	Yes	- Version:	Self-adhesive membrane
- Size:	435 x 570 x 45 mm		

ITEM NO	UNIT	SRP
0025002 AmbienTone No.2	1 pc	1298,00



AMBIENTONE SUB NO.2



This speaker is specialized for deep bass reproduction and can be perfectly combined with the AmbientTone panels No.4, No.2, and No.1. This hi-tech in-wall subwoofer features a very low structure-borne sound thanks to its special design. Wall vibrations and the transmission of noise to neighbouring rooms are therefore reduced to a minimum, even without additional decoupling. The front of the subwoofer consists of a gypsum plasterboard. In the same way as AmbientTone No.4, it is screwed onto the substructure of drywall constructions and plastered over flush with the surrounding plasterboard. A 10 mm narrow slit acts as a sound outlet and can be positioned inconspicuously above the skirting board or close to the ceiling. The integrated special switch enables a direct connection to a standard amplifier.

- Power: 2 x 100 Watts max.
- Impedance: 2 x 6 Ohm
- Frequency range: 38–100Hz
- Sensitivity: 85 dB
- Size: 500 x 625 x 86 mm
- Installation depth: 73 mm
- Cutout: 435 x 570 mm
- Weight: 9 kg
- System: Passive stereo system
- Crossover: Integrated special cross switch
- Connection: 2 x 10 m speaker cable
- Max. SPL: 108 dB
- Carrier: 12,5 mm plasterboard

ITEM NO	UNIT	SRP
0025202 AmbientTone Sub No.2	1 pc	2425,00

AMBIENTONE NO.8



- Möbellautsprecher
- Für Plattenwerkstoffe wie MDF-Holz-/Spanplatten
- Inkl. 10m Speaker Cable
- Abstrahlwinkel: HxV 180°x180°
- Gewicht: ca. 1,2 kg
- Überlastschutz
- 2-Wege
- 320 x 360 x 45 mm
- Sonderanfertigungen auf Anfrage

ITEM NO	UNIT	SRP
0025008 AmbientTone No.8	1 pc	1395,00

AMBIENTONE Q1



The AmbientTone Q1 is a high-quality 2-way built-in loudspeaker with outstanding sound properties. The quick-lock system facilitates, and saves a lot of time during, assembly. The speaker can be used in stereo applications, as complete home cinema systems or as multi-room installations. The loudspeakers can be used everywhere: in the kitchen, bath and living room, as well as in all other living areas. They can also be used in conference rooms, restaurants, hotel facilities, shops or health spas etc.

- Power: 50 Watts
- Impedance: 8 Ohms
- Frequency range: 61 Hz–20 kHz
- Sensitivity: 87 dB
- Dimensions: 310 x 196 x 79,3 mm
- Cutout: 286 x 172 mm
- Installation depth: 72,3 mm
- Sub-woofer/mid-range driver: 6 1/2" (16,5 cm)
- Tweeter: 20 mm Soft Dome
- Tuneable: Tweeter 0/-3/-6 dB
- Weight: ca. 1,4 kg
- System: 2 ways
- Locking: Quick-lock, operated from the front
- Membrane material: PP (Polypropylen)
- Conform to CE

ITEM NO	UNIT	SRP
0024201 50 Watts; rectangular; 310 x 196 x 80 mm	pair	143,00


AMBIENTONE R1



The AmbientTone R1 is a high-quality 2 way built in ceiling and wall loudspeaker. It can be used in stereo applications, as complete home cinema systems or as multi-room installations. The loudspeakers can be used everywhere: in the kitchen, bath and living room, as well as in all other living areas. They can also be used in conference rooms, restaurants, hotel facilities, shops or health spas etc.

- Power: 50 Watts
- Impedance: 8 Ohms
- Frequency range: 72 Hz–20 kHz
- Sensitivity: 86 dB
- Dimensions: Ø 240 mm
- Cutout: Ø 205 mm
- Installation depth: 68 mm
- Sub-woofer/mid-range driver: 6 1/2" (16,5 cm)
- Tweeter: 13 mm Dome
- Weight: ca. 1 kg
- System: 2 ways
- Locking: Hooks with screws accessible from the front
- Membrane material: PP (Polypropylen)
- Conform to CE

ITEM NO	UNIT	SRP
0024001 50 Watts; round; 240 x 68 mm	pair	110,00



LS-4004 AIR



LS-2404 AIR



LS-2404 AIR



LS-1204 AIR



NF-1204 AIR



NF-2404 AIR



NF-2404 AIR



REFERENZ AIR

The AIR technology is a milestone in our more than 40-year company history and is causing a worldwide sensation in the hi-fi industry. The approach sounds relatively banal: Physical losses must be minimized in order to transmit the original music signal as unchanged and neutral as possible. And AIR technology comes closer than ever to lossless transmission. It leads to significantly better sound reproduction, which is not only subjectively audible, but also objectively measurable.

The insulation or dielectric of the AIR cables is almost perfect thanks to the air insulation and hardly influences the sound any more. The construction, dimensions and arrangement of the conductors are optimized and fully exploit what is physically feasible.

The air-helix construction is wholly unique. We have developed a special clip to ensure air insulation that is as close to perfection as possible. A large number of these clips form the supporting structure on the inside of the cable. This holds the signal conductor free in the air in a helix form and guides it through the cable at defined intervals. The flexibility of this construction is attained with two bridges that hold the clips together evenly and at exact intervals. The Cross Link Super Speed waveguides are threaded and fitted with clips by hand with extreme care in our own manufacturing unit. Afterwards the air-helix created in this manner is given its PE network jacket – again by hand. Finally the rhodium-coated plugs are fitted and the cable function is tested

LS-4004 AIR PURE SILVER



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length

BFA & SPADE | SW
ANGLE ADJUSTABLE

SRP
14.090,00
18.902,00
23.714,00
28.526,00
33.308,00
38.150,00
42.962,00

*2x3,0m # 007714038

BFA & SPADE | SBW
ANGLE ADJUSTABLE

SRP
14.707,00
19.519,00
24.331,00
29.143,00
33.925,00
38.767,00
43.579,00

*2x3,0m #0077140381



FIDELITY

„This is a cable with the license to thrill: The LS-4004 Air Pure Silver is as thick as your forearm and a real statement piece that's very hard to beat in terms of appearance, workmanship and sound quality. The serpent destined to entice high end users who enjoy lingering in the garden of good listening [...] but rather one of the best speaker cables money can buy.“ Fidelity | 43

LS-4004 AIR



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length

BFA | SW
ANGLE ADJUSTABLE

SRP
3.137,00
4.174,00
5.211,00
6.248,00
7.255,00
8.322,00
9.359,00

*2x3,0m # 007714032

BFA | SBW
ANGLE ADJUSTABLE

SRP
3.525,00
4.562,00
5.599,00
6.636,00
7.643,00
8.710,00
9.747,00

*2x3,0m #0077140321

SPADE | SW
ANGLE ADJUSTABLE

SRP
3.137,00
4.174,00
5.211,00
6.248,00
7.255,00
8.322,00
9.359,00

*2x3,0m # 007714033

SPADE | SBW
ANGLE ADJUSTABLE

SRP
3.525,00
4.562,00
5.599,00
6.636,00
7.643,00
8.710,00
9.747,00

*2x3,0m #0077140331



„This cable carries a lot of consideration and manual work. The LS-4004 AIR is one of the finest cables we've ever heard. It is gifted with a phenomenal analysis.“ stereoplay 01-2018

LS-2404 AIR PURE SILVER



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length

BFA & SPADE | SW
ANGLE ADJUSTABLE

SRP
7.925,00
10.886,00
13.847,00
16.808,00
19.739,00
22.730,00
25.691,00

*2x3,0m #007712438

BFA & SPADE | SBW
ANGLE ADJUSTABLE

SRP
8.541,00
11.502,00
14.463,00
17.424,00
20.355,00
23.346,00
26.307,00

*2x3,0m #0077124381



LS-2404 AIR



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length

BFA | SW | MK II
ANGLE ADJUSTABLE

SRP
2.202,00
2.799,00
3.396,00
3.993,00
4.560,00
5.187,00
5.784,00

*2x3,0m # 007712436

BFA | SBW | MK II
ANGLE ADJUSTABLE

SRP
2.553,00
3.150,00
3.747,00
4.344,00
4.911,00
5.538,00
6.135,00

*2x3,0m # 0077124361

SPADE | SW | MK II
ANGLE ADJUSTABLE


SRP
2.202,00
2.799,00
3.396,00
3.993,00
4.560,00
5.187,00
5.784,00

*2x3,0m #007712437

SPADE | SBW | MK II
ANGLE ADJUSTABLE

SRP
2.553,00
3.150,00
3.747,00
4.344,00
4.911,00
5.538,00
6.135,00

*2x3,0m #0077124371





LS-2404 AIR



BFA 45° SW	BFA 45° SBW	BFA SW	BFA SBW	LENGTH
SRP	SRP	SRP	SRP	
1.995,00	2.177,00	1.918,00	2.062,00	1,0m Stereo
2.592,00	2.774,00	2.515,00	2.659,00	1,5m Stereo
3.189,00	3.371,00	3.112,00	3.256,00	2,0m Stereo
3.786,00	3.968,00	3.709,00	3.853,00	2,5m Stereo
4.353,00	4.535,00	4.276,00	4.420,00	3,0m Stereo*
4.980,00	5.162,00	4.903,00	5.047,00	3,5m Stereo
5.577,00	5.759,00	5.500,00	5.644,00	4,0m Stereo
*2x3,0m #007712435	*2x3,0m #0077124351	*2x3,0m #007712432	*2x3,0m #0077124321	*standard length



LS-2404 AIR



SPADE SW	SPADE SBW	SCREW TYPE SW	SCREW TYPE SBW	LENGTH
SRP	SRP	SRP	SRP	
1.995,00	2.177,00	1.991,00	2.192,00	1,0m Stereo
2.592,00	2.774,00	2.588,00	2.789,00	1,5m Stereo
3.189,00	3.371,00	3.185,00	3.386,00	2,0m Stereo
3.786,00	3.968,00	3.782,00	3.983,00	2,5m Stereo
4.353,00	4.535,00	4.349,00	4.550,00	3,0m Stereo*
4.980,00	5.162,00	4.976,00	5.177,00	3,5m Stereo
5.577,00	5.759,00	5.573,00	5.774,00	4,0m Stereo
*2x3,0m #007712433	*2x3,0m #0077124331	*2x3,0m #007712434	*2x3,0m #0077124341	*standard length



LS-2404 AIR



„It's difficult to describe – you have to experience it yourself. Or to put it in terms of money, a hi-fi combination worth €20,000 can be improved by 20% simply with the LS-2404 AIR. That amounts to an extraordinary value.“ stereoplay 01-2017



EASY PLUG SW	EASY PLUG SBW	LENGTH
SRP	SRP	
1.788,00	1.866,00	1,0m Stereo
2.385,00	2.463,00	1,5m Stereo
2.982,00	3.060,00	2,0m Stereo
3.579,00	3.657,00	2,5m Stereo
4.146,00	4.224,00	3,0m Stereo*
4.773,00	4.851,00	3,5m Stereo
5.370,00	5.448,00	4,0m Stereo
*2x3,0m #007712431	*2x3,0m #0077124311	*standard length



LS-1204 AIR PURE SILVER



BFA SW	SPADE SW	LENGTH
SRP	SRP	
4.470,00	4.470,00	1,0m Stereo
6.290,00	6.290,00	1,5m Stereo
8.110,00	8.110,00	2,0m Stereo
9.930,00	9.930,00	2,5m Stereo
11.720,00	11.720,00	3,0m Stereo*
13.570,00	13.570,00	3,5m Stereo
15.390,00	15.390,00	4,0m Stereo
*2x3,0m #0077013382	*2x3,0m #0077013383	*standard length





LS-1204 AIR



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length

BFA | SW

SRP
933,00
1.258,00
1.583,00
1.908,00
2.203,00
2.558,00
2.883,00

*2x3,0m #007701332

SPADE | SW

SRP
1.010,00
1.335,00
1.660,00
1.985,00
2.280,00
2.635,00
2.960,00

*2x3,0m #007701333



„A stroke of genius that shows the competitors the limits | precious finish: outstanding“ AUDIO 12-2018

LS-804 AIR



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length

BFA | SW

SRP
785,00
983,00
1.181,00
1.379,00
1.547,00
1.775,00
1.973,00

*2x3,0m #007710832

SPADE | SW

SRP
853,00
1.051,00
1.249,00
1.447,00
1.615,00
1.843,00
2.041,00

*2x3,0m #007710833

EASY PLUG | SW

SRP
471,00
669,00
867,00
1.065,00
1.233,00
1.461,00
1.659,00

*2x3,0m #007710831



„There's no getting away from it: €1000 is a lot of money for a loudspeaker cable. But in our listening room we tested much more expensive cables that couldn't do what the LS-804 manages. The concept is fantastic, the sound is finely balanced and exceeds our expectations in every respect. In all honesty a masterpiece.“ AUDIO 06-2019





DIGITAL 2404 AIR PURE SILVER



RCA
SRP
2.148,00
2.524,00
2.961,00
3.337,00
3.774,00
4.150,00
4.587,00

*1,00m # 007189110
*1,50m # 007189115
*2,00m # 007189120

XLR
SRP
2.499,00
2.916,00
3.396,00
3.814,00
4.293,00
4.711,00
5.190,00

*1,00m # 0071891103
*1,50m # 0071891153
*2,00m # 0071891203

LENGTH
0,75m Mono
1,00m Mono*
1,25m Mono
1,50m Mono*
1,75m Mono
2,00m Mono*
2,25m Mono

*standard length



DIGITAL 2404 AIR



RCA
SRP
767,00
947,00
1.175,00
1.349,00
1.584,00
1.763,00
1.992,00

*1,00m #007187110
*1,50m #007187115
*2,00m #007187120

XLR
SRP
845,00
1.012,00
1.253,00
1.427,00
1.662,00
1.841,00
2.070,00

*1,00m #0071871103
*1,50m #0071871153
*2,00m #0071871203

LENGTH
0,75m Mono
1,00m Mono*
1,25m Mono
1,50m Mono*
1,75m Mono
2,00m Mono*
2,25m Mono

*standard length



REFERENZ SELECTION PHONO CABLE

PHONO 2404 AIR



RCA -> RCA
SRP
895,00
1.064,00
1.296,00
1.466,00
1.697,00
1.881,00
2.098,00

*1,00m #0071872010
*1,50m #0071872015
*2,00m #0071872020

RCA -> SME 90°
SRP
972,00
1.129,00
1.373,00
1.543,00
1.774,00
1.944,00
2.175,00

*1,00m #0071872110
*1,50m #0071872115
*2,00m #0071872120

RCA -> SME
SRP
972,00
1.129,00
1.373,00
1.543,00
1.774,00
1.944,00
2.175,00

*1,00m #0071872210
*1,50m #0071872215
*2,00m #0071872220

XLR -> SME 90°
SRP
1.037,00
1.207,00
1.438,00
1.608,00
1.839,00
2.022,00
2.240,00

*1,00m #0071872310
*1,50m #0071872315
*2,00m #0071872320

LENGTH
0,75m Stereo
1,00m Stereo*
1,25m Stereo
1,50m Stereo*
1,75m Stereo
2,00m Stereo*
2,25m Stereo

*standard length



PHONO-2404 AIR




XLR -> SME
SRP
1.037,00
1.207,00
1.438,00
1.608,00
1.839,00
2.022,00
2.240,00

*1,00m #0071872410
*1,50m #0071872415
*2,00m #0071872420

LENGTH
0,75m Stereo
1,00m Stereo*
1,25m Stereo
1,50m Stereo*
1,75m Stereo
2,00m Stereo*
2,25m Stereo

*standard length





NF-2404 AIR PURE SILVER



	RCA	XLR
LENGTH	SRP	SRP
0,75m Stereo	2.835,00	3.591,00
1,00m Stereo*	3.365,00	4.318,00
1,25m Stereo	3.956,00	5.105,00
1,50m Stereo*	4.486,00	5.832,00
1,75m Stereo	5.077,00	6.619,00
2,00m Stereo*	5.608,00	7.346,00
2,25m Stereo	6.198,00	8.133,00
*standard length	*1,00m #007189010 *1,50m #007189015 *2,00m #007189020	*1,00m #0071890103 *1,50m #0071890153 *2,00m #0071890203



NF-2404 AIR



	RCA	XLR
LENGTH	SRP	SRP
0,75m Stereo	1.324,00	1.461,00
1,00m Stereo*	1.634,00	1.771,00
1,25m Stereo	2.004,00	2.141,00
1,50m Stereo*	2.314,00	2.451,00
1,75m Stereo	2.684,00	2.821,00
2,00m Stereo	3.024,00	3.161,00
2,25m Stereo	3.364,00	3.501,00
*standard length	*1,00m #007187010 *1,50m #007187015	*1,00m #0071870103 *1,50m #0071870153



„The NF-2404 Air RCA cable has magical cubic metres more than a competitor model. A clear vote for the in-akustik alternative.“ stereoplay 01-2017



NF-1204 AIR



	RCA	XLR
LENGTH	SRP	SRP
0,75m Stereo*	778,00	1.111,00
1,00m Stereo*	908,00	1.234,00
1,25m Stereo	1.073,00	1.382,00
1,50m Stereo*	1.167,00	1.482,00
1,75m Stereo	1.321,00	1.642,00
2,00m Stereo	1.445,00	1.772,00
2,25m Stereo	1.569,00	1.902,00
*standard length	*0,75m #007185107 *1,00m #007185110 *1,50m #007185115	*0,75m #0071851073 *1,00m #0071851103 *1,50m #0071851153



NF-1603



	RCA	XLR
LENGTH	SRP	SRP
0,75m Stereo*	775,00	868,00
1,00m Stereo*	892,00	978,00
1,25m Stereo	1.088,00	1.088,00
1,50m Stereo*	1.170,00	1.264,00
1,75m Stereo	1.313,00	1.313,00
2,00m Stereo	1.425,00	1.425,00
2,25m Stereo	1.538,00	1.538,00
*standard length	*0,75m #007186007 *1,00m #007186010 *1,50m #007186015	*0,75m #0071860073 *1,00m #0071860103 *1,50m #0071860153





inakustik

REFERENZ
LS-4004 AIR

SPEAKER

SE.-NO.:SW 00225



AC-4004 AIR HIGH QUALITY



LENGTH
1,0m*
1,5m*
2,0m*
3,0m*
3,5m
4,0m

*standard length

SCHUKO -> C19

SRP
2.540,00
2.963,00
3.386,00
4.232,00
4.685,00
5.108,00

*1,0m #007628310
*1,5m #007628315
*2,0m #007628320
*3,0m #007628330

SCHUKO -> C15 (C13)

SRP
2.540,00
2.963,00
3.386,00
4.232,00
4.685,00
5.108,00

*1,0m #007628210
*1,5m #007628215
*2,0m #007628220
*3,0m #007628230



HQ C19



HQ C15 (C13)



HQ SCHUKO

AC-4004 AIR HIGH QUALITY | US



LENGTH
1,0m*
1,5m*
2,0m*
3,0m*
3,5m
4,0m

*standard length

SCHUKO -> C19

SRP
2.540,00
2.963,00
3.386,00
4.232,00
4.685,00
5.108,00

*1,0m #007628510
*1,5m #007628515
*2,0m #007628520
*3,0m #007628530

SCHUKO -> C15 (C13)

SRP
2.540,00
2.963,00
3.386,00
4.232,00
4.685,00
5.108,00

*1,0m #007628410
*1,5m #007628415
*2,0m #007628420
*3,0m #007628430



HQ C19



HQ C15 (C13)



HQ US

AC-2404 AIR HIGH QUALITY



LENGTH
1,0m*
1,5m*
2,0m*
3,0m*
3,5m
4,0m

*standard length

SCHUKO -> C19

SRP
1728,00
1975,00
2221,00
2715,00
2851,00
3063,00

*1,0m #007626310
*1,5m #007626315
*2,0m #007626320
*3,0m #007626330

SCHUKO -> C15 (C13)

SRP
1728,00
1975,00
2221,00
2715,00
2851,00
3063,00

*1,0m #007626210
*1,5m #007626215
*2,0m #007626220
*3,0m #007626230



HQ C19



HQ C15 (C13)



HQ SCHUKO





AC-2404 AIR



C19

C13

SCHUKO



SCHUKO -> C19

SRP
1234,00
1482,00
1728,00
2221,00
2358,00
2570,00

*1,0m #007626110
*1,5m #007626115
*2,0m #007626120
*3,0m #007626130

SCHUKO -> C13

SRP
1234,00
1482,00
1728,00
2221,00
2358,00
2570,00

*1,0m #007626010
*1,5m #007626015
*2,0m #007626020
*3,0m #007626030

LENGTH
1,0m*
1,5m*
2,0m*
3,0m*
3,5m
4,0m

*standard length



AC-2404 AIR | US



HQ C19

HQ C15 (C13)

HQ US

SCHUKO -> C19

SRP
1728,00
1975,00
2221,00
2715,00
2851,00
3063,00

*1,0m #007626510
*1,5m #007626515
*2,0m #007626520
*3,0m #007626530

SCHUKO -> C15 (C13)

SRP
1728,00
1975,00
2221,00
2715,00
2851,00
3063,00

*1,0m #007626410
*1,5m #007626415
*2,0m #007626420
*3,0m #007626430

LENGTH
1,0m*
1,5m*
2,0m*
3,0m*
3,5m
4,0m

*standard length



AC-1204 AIR MKII



Basic C19

Basic C15 (C13)

Basic SCHUKO



SCHUKO -> C19

SRP
900,00
1.032,00
1.164,00
1.429,00
1.486,00
1.592,00

*1,0m #007629710
*1,5m #007629715
*2,0m #007629720
*3,0m #007629730

SCHUKO -> C15 (C13)

SRP
900,00
1.032,00
1.164,00
1.429,00
1.486,00
1.592,00

*1,0m #007629610
*1,5m #007629615
*2,0m #007629620
*3,0m #007629630

LENGTH
1,0m*
1,5m*
2,0m*
3,0m*
3,5m
4,0m

*standard length





SAFETY IS VERY IMPORTANT TO US



For all its love of audiophile sound, safety plays a special role in this cable category. That's why every Reference AIR power cord is tested and inspected extremely carefully. In addition to an intensive functional test, each cable is also subjected to an insulation and high-voltage test. The results are registered, and each cable is given an individual serial number.



AC-1204 AIR MKII | US



Basic C19



Basic C15 (C13)



Basic US

SCHUKO -> C19

SRP
900,00
1.032,00
1.164,00
1.429,00
1.486,00
1.592,00

*1,0m #007629910
 *1,5m #007629915
 *2,0m #007629920
 *3,0m #007629930

SCHUKO -> C15 (C13)

SRP
900,00
1.032,00
1.164,00
1.429,00
1.486,00
1.592,00

*1,0m #007629810
 *1,5m #007629815
 *2,0m #007629820
 *3,0m #007629830

LENGTH
1,0m*
1,5m*
2,0m*
3,0m*
3,5m
4,0m

*standard length



AC-1204 AIR



C19



C13



SCHUKO

SCHUKO -> C19

SRP
582,00
688,00
794,00
1.006,00
1.142,00
1.248,00

*1,0m #007629110
 *1,5m #007629115
 *2,0m #007629120
 *3,0m #007629130

SCHUKO -> C13

SRP
582,00
688,00
794,00
1.006,00
1.142,00
1.248,00


*1,0m #007629010
 *1,5m #007629015
 *2,0m #007629020
 *3,0m #007629030

LENGTH
1,0m*
1,5m*
2,0m*
3,0m*
3,5m
4,0m

*standard length



Dynamic music impulsively loads the power amplifiers of an audiophile hi-fi system. Therefore, the power cable Reference AC-2404 AIR was developed this way and now completed by the AC-4004 AIR and the AC-1204 AIR. Specially developed clips keep the individual wires at a fixed distance. The resulting „air dielectric“ reduces power losses to a minimum and improves the electrical parameters significantly. The Reference AC-4004 AIR with a multi-core structure of 16 conductors is a combination of the AC-2404 AIR power cable, which has received particularly excellent ratings in various test reports, and the LS-4004 AIR loudspeaker cable, sometimes referred to as a „dream cable“. As a basis for the development of the Reference AC-1204 AIR, the technology of the speaker cable LS-1204 AIR was used, which has also caused an excitement in the hi-fi scene. The multi-core construction leads to an overlapping and thus compensation of the magnetic fields around the individual wires. Depending on the number of cores, the line inductance is thus extremely minimized, and the skin effect caused by steep current flanks at high frequencies is significantly and audibly reduced. In addition, the usable conductor cross-section is expanded effectively and without the negative effects of thick cables. A dense shielding braid of tinned copper protects nearby cables and audio components from external interference and also prevents oxidation.





stoic


STOIC WALL MOUNTS & BASES

Vinyl on the turntable is a sensitive passion, nothing disturbs the enthusiasm for music more than an impaired sound. Every vibration, however delicate is annoying, unless the fundament is right. HighStandArt delivers it: with the STOIC-Wallmount and the STOIC-Base.

Every STOIC combines all the features it needs for a perfect music reproduction. It decouples Hi-Fi devices completely and securely from vibrating floors, furniture or HiFi-racks and thereby from annoying vibrations and resonances. For all HiFi-components. Be it analogue or digital.

The metal frame filled with sand, kills vibrations by its enormous mass, as well as the use of low-resonance materials such as natural slate or plywood.

A hard, unsprung coupling between the frame and the support ensures that no swinging is produced.





VOLUME



stair



FRAME | WALL MOUNT

ITEM NO	EAN	VERSION		SRP
00269001	4001985516469	Wall Mount black	40x55	893,00
00269011	4001985517862	Wall Mount white	40x55	893,00
00269003	4001985516483	Wall Mount steel	40x55	1355,00
00269002	4001985516476	Wall Mount black	50x55	977,00
00269012	4001985057306	Wall Mount white	50x55	977,00
00269004	4001985516490	Wall Mount steel	50x55	1428,00



FRAME | ABSORBER BASE

ITEM NO	EAN	VERSION		SRP
00269013	4001985517879	Absorber Base black	40x55	788,00
00269014	4001985517886	Absorber Base white	40x55	788,00
00269015	4001985517893	Absorber Base steel	40x55	1071,00
00269016	4001985517909	Absorber Base black	50x55	872,00
00269017	4001985517916	Absorber Base white	50x55	872,00
00269018	4001985517923	Absorber Base steel	50x55	1239,00



PLATE 40X55

ITEM NO	EAN	VERSION		SRP
00269021	4001985517954	Multiplex clear	40x55	389,00
00269022	4001985517961	Multiplex black	40x55	567,00
00269023	4001985517978	Multiplex white	40x55	567,00
00269024	4001985517985	Slate	40x55	1376,00
00269025	4001985517992	Sandwich clear	40x55	609,00
00269026	4001985518425	Sandwich black	40x55	725,00
00269027	4001985518432	Sandwich white	40x55	725,00

PLATE 50X55

ITEM NO	EAN	VERSION		SRP
00269028	4001985518449	Multiplex clear	50x55	536,00
00269029	4001985518456	Multiplex black	50x55	714,00
00269030	4001985518463	Multiplex white	50x55	714,00
00269031	4001985518470	Slate	50x55	1523,00
00269032	4001985518487	Sandwich clear	50x55	672,00
00269033	4001985518494	Sandwich black	50x55	788,00
00269034	4001985518500	Sandwich white	50x55	788,00

PLATE 40X55 WITH CABLE OUTLET



ITEM NO	EAN	VERSION		SRP
00269005	4001985516506	Multiplex clear	40x55	389,00
00269006	4001985516513	Multiplex black	40x55	567,00
00269019	4001985517930	Multiplex white	40x55	567,00
00269007	4001985516520	Slate	40x55	1376,00

PLATE 50X55 WITH CABLE OUTLET







ITEM NO	EAN	VERSION		SRP
00269008	4001985516537	Multiplex clear	50x55	536,00
00269009	4001985516544	Multiplex black	50x55	714,00
00269020	4001985517947	Multiplex white	50x55	714,00
00269010	4001985516551	Slate	50x55	1523,00





SCOPE OF DELIVERY - ACCESSORIES










COMPARISON OF SIZES












MASTERTAPE SELECTION

This Mastertape Selection from in-akustik has been assembled with a love of musical detail. RESO Mastering, the new high definition mastering procedure, provides significant acoustic improvements in transparency, dynamics, bass reproduction and depth differentiation. The music is gaining more atmosphere and emotion. The transfer to „Master Selection“ tapes „Recording The Masters SM 468“ is done by calibrated and professionally maintained studio tape machines Studer A 80 (38 cm/sec) and Telefunken M 15/21 (19 cm/sec) directly from the original master. Each tape is produced directly and without any detour. Haute couture for the ears, real master quality.



- RESO Mastering
- Direkt-Copy from Master without sound influencing intermediate steps
- Premium professional backcoated Studio-Tape
- Metal Reel 10.5 inch / 26,5 cm
- Available as 19 cm/s (1 Reel) or 38 cm/s (2 Reels)
- Incl. empty Metal Reel



in-akustik Firmensitz:
Wein- und Erholungsort Ballrechten-Dottingen

LEGAL NOTICE

Our general terms and conditions (GTC 03/2009) apply: www.in-akustik.de. Deliveries occur ex works (EXW) D - Ballrechten-Dottingen (Incoterms 2000). Place of performance for all deliveries and obligations is D - Ballrechten-Dottingen.

This in-akustik catalogue is valid from 01.12.2021. All prices in EUR. The printed matter we designed to provide information and advice to the best of our knowledge. Any legal obligations, however, may not be derived from such printed matter. Images, particularly relating size and features of the products shown, are non-binding. We reserve the right to make technical and formal changes to our products in the interests of technical progress.



iPod®/iPhone®/iPad® are trademarks of Apple Inc., registered in the U.S. and other countries.



“© 2013 CSR plc and its group companies. The aptX® mark and the aptX logo are trade marks of CSR plc or one of its group companies and may be registered in one or more jurisdictions.”



“The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth® SIG, Inc. and any use of such marks by in-akustik is under license. Other trademarks and trade names are those of their respective owners.”



The Terms HDMI® and HDMI® High-Defintion Multimedia Interface, and the HDMI® Logo are trademarks or registered trademarks of HDMI® Licensing LLC in the United Stated and other countries.

in-akustik memberships:



in-akustik GmbH & Co. KG
Untermatten 12-14
79282 Ballrechten-Dottingen
Germany

Tel.: +49 (0) 7634 5610-70
Fax: +49 (0) 7634 5610-80
E-Mail: info@in-akustik.de
Web: www.in-akustik.de

All previous prices hereby lose their validity. All prices in EUR. This in-akustik catalogue is valid from 01.12.2021. The printed matter we designed to provide information and advice to the best of our knowledge. Any legal obligations, however, may not be derived from such printed matter. Images, particularly relating size and features of the products shown, are non-binding. We reserve the right to make technical and formal changes to our products in the interests of technical progress.

